

To: 1 060195 11-6
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-101-21,667-00-00
C NE SW, SEC. 9, T 18 S, R 28 W
1980 feet from S section line
3300 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5011
Operator: Viking Resources, Inc.
Name & Address: 105 S. Broadway, Ste. 1040
Wichita, KS 67202

Lease Name Yost A Well # 1
County Lane
Well Total Depth 4655 151.28 feet
Conductor Pipe: Size feet
Surface Casing: Size 8 5/8 feet 221

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Mallard JV, Inc. License Number 4958

Address P.O. Box 1009, McPherson, KS 67460

Company to plug at: Hour: 3 a.m. Day: 6 Month: 11 Year: 1993

Plugging proposal received from Judy
(company name) Mallard JV, Inc. (phone) 316-241-4640

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2126-56'

- 1st plug at 2200' with 50 sx cement, 2nd plug at 1450' with 50 sx cement,
- 3rd plug at 750' with 40 sx cement, 4th plug at 250' with 50 sx cement,
- 5th plug at 40' with 10 sx cement, 6th plug to circulate rathole with 15 sx cement,
- 7th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Case Morris (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 5:15 a.m. Day: 6 Month: 11 Year: 1993

ACTUAL PLUGGING REPORT 1st plug at 2200' with 50 sx cement,
2nd plug at 1450' with 50 sx cement, 3rd plug at 750' with 40 sx cement,
4th plug at 250' with 50 sx cement, 5th plug at 40' with 10 sx cement,
6th plug to circulate rathole with 15 sx cement,
7th plug to circulate mousehole with 10 sx cement.

RECEIVED
STATE CORPORATION COMMISSION

NOV 12 1993

Used 60/40 Pozmix 6% gel by Allied.

CONSERVATION DIVISION
Wichita, Kansas

(If additional description is necessary, use BACK of this form.)

DATE (XXXX-XX-XX) observe this plugging.

INV. NO. 39309

Signed [Signature] (TECHNICIAN)

11-6 JAN 31 1994 MAR 16 1995

EXPIRES DATE: 10-31-93
DISTRICT 8
STATE: Kan.

State of Kansas
NOTICE OF INTENTION TO DRILL 101-21,667-0000

FORM C-1 7/91
FORM MUST BE TYPED
FORM MUST BE SIGNED
ALL BLANKS MUST BE FILLED

Must be approved by the K.S.C. five (5) days prior to commencing well

Expected Spud Date: 10/29/93
month day year

Spot: V.C. NE-SW Sec 9, Twp 18 S, Rg 28 West

OPERATOR: License # 5011
Name: Viking Resources, Inc.
Address: 105 S. Broadway, Ste. 1040
City/State/Zip: Wichita, Kansas 67202
Contact Person: Rob Patton
Phone: 262-2502

1980 feet from South / N&S line of Section
3300 feet from East / W&E line of Section
IS SECTION REGULAR IRREGULAR

(NOTE: Locate well on the Section Plat on Reverse Side)
County: Lane
Lease Name: Yost "A" Well #: 1
Field Name: WC

CONTRACTOR: License # 4958
Name: Mallard JV, Inc.

Is this a Prorated/Spaced Field? yes X no
Target Formation(s): Mississippi

Well Drilled For: Well Class: Type Equipment:
X Oil ... Enh Rec ... Infield ... X Mud Rotary
... Sec ... Storage ... Pool Ext. ... Air Rotary
... O&G ... Disposal ... * Wildcat ... Cable
... Seismic ... # of Holes ... Other

Nearest lease or unit boundary: 660'
Ground Surface Elevation: unknown
Water well within one-quarter mile: yes X no

If O&G, old well information as follows:
Operator:
Well Name:
Comp. Date: Old Total Depth

Public water supply well within one mile: yes X no
Depth to bottom of fresh water: 900'
Depth to bottom of usable water: 350'

directional, deviated or horizontal wellbore? yes X no
If yes, true vertical depth:
Bottom Hole Location:

Surface Pipe by Alternate: 1 X 2
Length of Surface Pipe Planned to be set: 200'
Length of Conductor pipe required: 0'
Projected Total Depth: 4600'

Exp. 4/26/94

AFFIDAVIT

200' Alt. II Req.

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq.

Pusher: Judy
SPUD DATE: Oct 28-1993 INIT. GB
LENGTH SURFACE PLANNED: 200'
RESERVE PIT STATUS- REMOVE FLUID LINED after salt sect. bbls. when done bbls.
RATHOLED AHEAD? Y N SIZE HOLE
SURFACE PIPE 8 1/2" @ 221 CONDUCTOR
ANHYDRITE T- 212, B- 2156 ELEVATION
TD 4655 FORMATION MS
RAN PIPE @ DV TOOL ALT II DONE SX Y N
Arbuckle Plug @ Ft. W/ SX
Hug./Council @ Ft. W/ SX
Anhydrite Base @ 2200 Ft. W/ 50 SX
1/2 Base Anyh. @ 1750 Ft. W/ 50 SX
1/2, 1/2 Plug @ 750 Ft. W/ 40 SX
Bottom Surface @ 250 Ft. W/ 50 SX
40' Plug @ 40 Ft. W/ 10 SX
RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ 10 SX
WATER WELL SX (Irr. Well Pond Hauling X)
TECHNICIAN CA DATE 11-3-93
TYPE OF CEMENT 60/40 670
STARTING TIME 3:00 (AM/PM) DATE 11-6-93
COMPLETION TIME 5:15 (AM/PM) DATE 11-6-93
CEMENT COMPANIES ACC 152
RECEIVED NOV 1 1993
STATE COMMISSION
Wichita, Kansas
Wanda Collier