

1 090067

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 13- 101-21,576 -00-00

C NW SE, SEC. 11, T. 18 S, R. 28 W/4

1980 feet from S section line

1980 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5123

Lease Name Selfridge "J" Well # 1

Operator: Pickrell Drilling Company, Inc.

County Lane 150.96

Name & Address 110 N. Market, Ste. 205

Well Total Depth 4645 feet

Wichita, KS 67202

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 267

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Pickrell Drilling Company, Inc. License Number 5123

Address 110 N. Market, Ste. 205, Wichita, KS 67202

Company to plug at: Hour: 2 p.m. Day: 4 Month: 4 Year: 19 91

Plugging proposal received from Doyle Folkerts

(company name) Pickrell Drilling Company, Inc. (phone) 316-262-8427

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2105-38'

1st plug at 2140' with 50 sx cement, 2nd plug at 1270' with 80 sx cement,

3rd plug at 635' with 50 sx cement, 4th plug at 290' with 50 sx cement,

5th plug at 40' with 10 sx cement,

6th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Steve Middleton (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 4 p.m. Day: 4 Month: 4 Year: 19 91

ACTUAL PLUGGING REPORT 1st plug at 2140' with 50 sx cement,

2nd plug at 1270' with 80 sx cement,

3rd plug at 635' with 50 sx cement,

4th plug at 290' with 50 sx cement,

5th plug at 40' with 10 sx cement,

6th plug to circulate rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel 1/2# floseal by Allied.

(if additional description is necessary, use BACK of this form.)

(xxx / did not) observe this plugging.

INVOICED

DATE 4-11-91

INV. NO. 31493

Signed (TECHNICIAN)

RECEIVED STATE CORPORATION COMMISSION

APR 09 1991

CONSERVATION DIVISION Wichita, Kansas

EFFECTIVE DATE: 3-18-91

State of Kansas 15- 101-21,576 -00-00

NOTICE OF INTENTION TO DRILL

Must be approved by the K.C.C. five (5) days prior to commencing well

Expected Spud Date 3 20 1991
month day year

C. NW.. SE. Sec 11.. Twp 18.. S, Rg 28.. X East West

OPERATOR: License # 5123
Name: Pickrell Drilling Co. Inc.
Address: 110 N. Market, Suite 205
City/State/Zip: Wichita, Kansas 67202
Contact Person: Don Beauchamp
Phone: 316-262-8427

1980 feet from South line of Section
1980 feet from East line of Section
(Note: Locate well on Section Plat on Reverse Side)

CONTRACTOR: License #: 5123
Name: Company Tools

County: Lane
Lease Name: Selfridge 'J' Well #: 1
Field Name: Wildcat

Well Drilled For: Well Class: Type Equipment:
X Oil ... Inj ... Infield X Mud Rotary
... Gas ... Storage ... Pool Ext. ... Air Rotary
... OWWO ... Disposal X Wildcat ... Cable
... Seismic; ... # of Holes

Is this a Prorated Field? ... yes X no
Target Formation(s): Lansing - Mississippian
Nearest lease or unit boundary: 660'
Ground Surface Elevation: 2726' feet MSL

If OWWO: old well information as follows:
Operator: _____
Well Name: _____
Comp. Date: _____ Old Total Depth _____

Domestic well within 330 feet: ... yes X no
Municipal well within one mile: ... yes X no
Depth to bottom of fresh water: 120'
Depth to bottom of usable water: 1300'
Surface Pipe by Alternate: ... 1 X 2
Length of Surface Pipe Planned to be set: 250'
Length of Conductor pipe required: None

Directional, Deviated or Horizontal wellbore? ... yes X no
If yes, total depth location: _____

Projected Total Depth: 4650'
Formation at Total Depth: Mississippian
Water Source for Drilling Operations:
... well ... farm pond X other

DWR Permit #: _____
Will Cores Be Taken?: ... yes X no
If yes, proposed zone: _____

RECEIVED
STATE CORPORATION COMMISSION
AFFIDAVIT

Exp. 9/13/91

200' Alt. II Req.

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq.
It is agreed that the following minimum requirements will be met:

CONSERVATION DIVISION
Wichita, Kansas

Pusher Doyle Folkerts

SPUD DATE 3-21-91 INIT. DG

LENGTH SURFACE PLANNED 265' LINED after salt sect. _____ bbls. when done _____ bbls.

RATHOLED AHEAD? Y N SIZE HOLE SURFACE PIPE 8 1/2" @ 267 CONDUCTOR ANHYDRITE T-2105 B-2128 ELEVATION TD 4645 FORMATION MISSISSIPPI

RAN PIPE @	DV TOOL	ALT II DONE	Y	N	SX	Ft.	W/	SX
Arbuckle Plug @								
Hug./Council @								
1 Anhydrite Base @						2140	W/	50 SX
2 1/2 Base Anyh. @						1270	W/	80 SX
3 1/2, 1/2 Plug @						635	W/	50 SX
4 Bottom Surface @						290	W/	90 SX
5 40' Plug @						40	W/	10 SX

RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ _____ SX

WATER WELL _____ SX (Irr. Well Pond Hauling)

TECHNICIAN S.M DATE 3-29-91

TYPE OF CEMENT 60/46 6 3/4 14 Absorb

STARTING TIME 2:00 (AM/PM) DATE 4-4-91

COMPLETION TIME 4:00 (AM/PM) DATE 4-4-91

CEMENT COMPANY Allied