

1 020183

R

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-101-21,120-00-00

NW NW NW, SEC. 1, T 19 S, R 28

4950 feet from N/S section line

4950 feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 9641

Lease Name M. Dodge Well # 1

Operator: Stauffer Oil & Gas

County Lane 151.62

Name & Address P. O. Box 6

Well Total Depth 4665 feet

Liberal, KS 67901

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 261

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Blue Goose Drilling Co., Inc. License Number 5104

Address Box 1413, Great Bend, KS 67530

Company to plug at: Hour: 4:00 am Day: 27 Month: January Year: 19 85

Plugging proposal received from Frank Boswell

(company name) Blue Goose (phone) 316-792-5633

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 2090' with 50 sx cement

2nd plug at 1290' with 60 sx cement

3rd plug at 310' with 50 sx cement

solid bridge

4th plug hulls - plug at 40' -- cement to surface with 10 sx cement

6th plug to circulate rat hole with 15 sx cement

Plugging Proposal Received by *Tom J. Wilson* (TECHNICIAN)

RECEIVED
CORPORATION COMMISSION
FEB 04 1985
04-04-1985
CONSERVATION DIVISION
Wichita, Kansas

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 5:30 am Day: 27 Month: January Year: 19 85

ACTUAL PLUGGING REPORT 1st plug at 2090' with 50 sx cement, 2nd plug at 1290' with 60 sx cement, 3rd plug at 310' with 50 sx cement, 4th & 5th plugs - solid bridge ÷ hulls - plug at 40' -- cement to surface with 10 sx cement, 6th plug to circulate rat hole with 15 sx cement.

Remarks: Used 60/40 Pozmix 2% gel 3% cc by Dowell.
(If additional description is necessary, use BACK of this form.)

INVOICED (did not) observe this plugging.

DATE 2-8-85

Signed *Tom J. Wilson* (TECHNICIAN)

INV. NO. 6898