

1 061110

6-22-88

141 R

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-101-21,477-00-00

C SW SE, SEC. 23, T 19 S, R 28 W/EX

660 feet from S section line

1980 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5393

Lease Name Hineman "D" Well # 1

Operator: A.L. Abercrombie, Inc.

County Lane 152.75

Name & Address 801 Union Center

Well Total Depth 4700 feet

Wichita, KS 67202

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 209

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Abercrombie Drilling, Inc. License Number 5422

Address 801 Union Center, Wichita, KS 67202

Company to plug at: Hour: 12:15 a.m. Day: 22 Month: 6 Year: 19 88

Plugging proposal received from Harvey Moore

(company name) Abercrombie Drilling, Inc. (phone) 316-262-1841

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2761' GL  
Anhydrite 2125'

1st plug at 2125' with 50 sx cement, 2nd plug at 1310' with 80 sx cement,

3rd plug at 240' with 50 sx cement, 4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Paul Luthi (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 5 a.m. Day: 22 Month: 6 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug at 2125' with 50 sx cement,

2nd plug at 1310' with 80 sx cement,

3rd plug at 240' with 50 sx cement,

4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION

JUN 23 1988  
06-23-1988  
CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by B.J. Titan.

(If additional description is necessary, use BACK of this form.)

INVOICED (did not) observe this plugging.

Signed Paul A. Luthi (TECHNICIAN)

DATE 7-13-88

INV. NO. 21293

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date. 6 month 7 day 88 year

API Number 15-101-21,477-00-DL

OPERATOR: License # 5393
Name A.L. Abercrombie, Inc.
Address 801 Union Center
City/State/Zip Wichita, Ks. 67202
Contact Person Jack L. Partridge
Phone 262-1841

C SW SE 23 Twp. 19 S, Rg. 28
660'
1980'

CONTRACTOR: License # 5422
Name Abercrombie Drilling, Inc.
City/State Wichita, Ks. 67202

(Note: Locate well on Section Plat on reverse side)
Nearest lease or unit boundary line 660 feet

Well Drilled For: Oil Storage Infield Pool Ext. Wildcat
Type Equipment: Mud Rotary Air Rotary Cable

County Lane
Lease Name Hineman "D" Well # 1
Ground surface elevation 2756 feet MSL

If OWWO: old well info as follows:
Operator
Well Name N/A
Comp Date Old Total Depth

Domestic well within 330 feet: yes X no
Municipal well within one mile: yes X no

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.
Date 6-8-88 Signature of Operator or Agent

Depth to bottom of fresh water 100'
Depth to bottom of usable water 1250'

For KCC Use:
Conductor Pipe Required feet; Minimum Surface Pipe Required 200 feet per Alt.

Surface pipe by Alternate: 1 2 X
Surface pipe planned to be set 200
Conductor pipe required None

This Authorization Expires 12-8-88

Projected Total Depth 4700 feet
Formation Mississippi

EFFECTIVE DATE: 6-13-88

Approved By [Signature] Title Exec. Vice President

SPUD 6-12-88

200'-8 5/8"

Approved By [Signature] Title Exec. Vice President

C SW SE 23 Twp. 19 S, Rg. 28 X East West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep BANhydrite Base/Dakota or formation with 50sx feet of 60-40 posmix 6% gel
2nd plug @ ft. deep 80sx feet of 60-40 posmix 6% gel
3rd plug @ ft. deep 230! or formation with 50sx feet of 60-40 posmix 6% gel
4th plug @ ft. deep Top 40! or formation with 10sx feet of 60-40 posmix 6% gel
5th plug @ ft. deep w/15sx or formation with feet of 60-40 posmix 6% gel
(2) Rathole to surface minus 5 feet w/10sx (b) Mousehole to surface minus 5 feet

PUSHER Harney Merrill
TD 4700 FORMATION M155
SURFACE PIPE 8 5/8 @ 209
ANHYDRITE 2/25 ELEVATION 2761.3
STARTING TIME & DATE 12:15 PM 6-22-88
COMPLETION TIME & DATE 5:00 AM 6-22-88
1st PLUG @ 2/25 FT. W/ 50 SX
2nd PLUG @ 1310 FT. W/ 80 SX
3rd PLUG @ 240 FT. W/ 50 SX
4th PLUG @ 40-0 FT. W/ 10 SX
RAT HOLE CIRCULATED W/ 15 SX
MOUSE HOLE CIRCULATED W/ SX
WATER WELL PLUGGED W/ none
CEMENT COMPANY B. J. Stanton
TECHNICIAN Paul Luthi

RECEIVED
STATE CORPORATION COMMISSION
JUN 23 1988
06-23-1988
CONSERVATION DIVISION
Wichita, Kansas