

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-101-20,599-00-00

NE 1/4, Sec. 23, T 19 S, R 28 W 1/4  
(NW SW NE) feet from N/S section line

TECHNICIAN'S PLUGGING REPORT

\_\_\_\_\_ feet from W/E section line

Operator License # 5729

Lease Name HINEMAN "O" Well # 9

Operator: DYNAMAR Energy, Inc.  
Name &  
Address Derby, KS

County LANE

Well Total Depth 4715 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 457'

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Clarke Corporation License Number 5105

Address 107 W. Fowler, Medicine Lodge, KS, 67104

Company to plug at: Hour: 9:30 AM Day: 17 Month: dec Year: 1982

VERBAL PLUGGING ORDERS GIVEN TO Elmo Margantern

(company name) Clarke (phone) \_\_\_\_\_

were: sand bottom to 4150' stop w/ 5 sy cmt.

Recover pipe and then pump @ 3 sy hells - 100 gal,  
70 sy 50/50 foam mix, 40 gal - 3% CC. Follow w/ 15 gal,  
1 sy hells, & release 8 5/8 plug followed by  
70 sy foam mix.

Signed R. Barluttan  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 10:25 AM Day: 17 Month: dec Year: 1982

ACTUAL PLUGGING REPORT Plugged as ordered

Cementing by Suni

RECEIVED  
STATE CORPORATION COMMISSION  
DEC 22 1982  
15-2-1982  
CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Surface set w/ 250 sy cmt. 5 1/2" set @ 4713'  
w/ 150 sy cmt. PBD @ 4307' - Perfs. @ 4299-4305.  
Rec. 1980' of 5 1/2".

I hereby certify that the above plugging instructions were given as herein stated  
and that I (did / ~~did not~~) observe this plugging.

Signed R. Barluttan  
(TECHNICIAN)

INVOICED

DATE 12-28-82  
INV. NO. 2067-U