TO: API Well Number: <u>15-051-22315-00-00</u> STATE CORPORATION COMMISSION Spot: CSESWNW Sec/Twnshp/Rge: 26-13S-20W **CONSERVATION DIVISION - PLUGGING** 4290 feet from S Section Line, 2970 feet from E Section Line 130 SOUTH MARKET, SUITE 2078 Lease/Unit Name: YOUNGER B Well Number: 4 **WICHITA, KANSAS 67202** County: ELLIS Total Vertical Depth: 3848 feet Operator License No.: 101 Conductor Pipe: Size feet: Surface Casing: Size 8.625 feet: 156 Op Name: KCC FEE FUND <u>w/130 sxs cmt</u> **Production: Size 4.5** feet: 3833 w/175 sxs cmt Address: 130 S. MARKET, ROOM 2078 Liner: Size feet: WICHITA, KS 67202 Well Type: OIL **UIC Docket No: Date/Time to Plug:** <u>11/02/2001 9:30 AM</u> Plug Co. License No.: 6426 Plug Co. Name: EXPRESS WELL SERVICE INC Proposal Revd. from: DUANE ACHTERBERG Company: FLATLAND MAINTENANCE SERVI Phone: (785) 635-7335 Proposed Ordered out 180 sxs 60/40 pozmix - 10% gel - 500# hulls. Plugging |Fluid level 1500'. Method: Plugging Proposal Received By: JAY PFEIFER WitnessType: Plugging Operations 100% Witnessed (Complete) Date/Time Plugging Completed: 11/02/2001 10:30 AM KCC Agent: JAY PFEIFER **Actual Plugging Report:** Perforated casing at 750' - 1500' - 2240'. Tied onto 4 1/2" and pumped to pressure with 180 sxs cmt and 500# hulls. Max. P.S.I. 400#. S.I.P. 200#. Instant pressure on annulus. Remarks: SWIFT SERVICES, INC. Plugged through: CSG District: 04 Signed (TECHNICIAN)

RECEIVED

Form CP-2/3


NOV 0 5 2001

KCC WICHITA

NOV 1 3 2001

JOHN B. COLLINS	- Δ	REPLACEMENT CARD	26-13-20W SE SW NW
HAYS, KS 67601	DIL, INC.	CTY ELLIS	
GEOL LAWRENCE I	GRAY	FIELD IRVIN	 + + + + +
2183 GL API 15-051-22	7/81 CARD ISSUEI 315	o <u>6/25/81</u> IP <u>OIL WEL</u> FORM-&	INTV NA
	Depth/Datum 3466–1278 3485–1297	8 5/8 " 156 / 130 SX, 4 1/2 " 3833 NO CORES OR DSTS MICT – CO, PF (FORM & INTV NA) NOT RPTD) – TIGHT HOLE – NO OPERATOR	
		CORRECTION: 10/2/86 – ORIGINALLY	' First reported in NW SW

COPYRIGHT 1985
INDEPENDENT OIL & GAS SERVICE, INC.
WICHITA, KANSAS



+ 30 sec to Fluid

750° 1560° 2240°