

1 010093

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 135-23,008 -0000

NW SE NW, SEC. 30, T 17 S, R 25 W

3630 feet from S section line

3630 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5190

Lease Name Popp Well # 1

Operator: Sabre Exploration, Inc.

County Ness 145.44

Name & Address 310 W. Central, Suite 214

Well Total Depth 4475 Mississippi feet

Wichita, KS 67202

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 278

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Republic Drilling, Inc. License Number 9943

Address 310 W. Central, Suite 214, Wichita, KS 67202

Company to plug at: Hour: 3:00 am Day: 25 Month: February Year: 19 86

Plugging proposal received from Mike Lanigan

(company name) Republic (phone) 316-264-0079

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2480' Anhydrite 1801'

1st plug at 1800' with 50 sx cement

2nd plug at 800' with 60 sx cement

3rd plug at 280' with 40 sx cement

4th plug solid bridge hulls - plug at 40' -- cement to surface with 10 sx cement

6th plug to circulate rat hole with 15 sx cement

Plugging Proposal Received by Jack L. Luthi (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 4:30 am Day: 25 Month: February Year: 19 86

ACTUAL PLUGGING REPORT 1st plug at 1800' with 50 sx cement, 2nd plug at 800' with 80 sx cement, 3rd plug at 300' with 40 sx cement, 4th & 5th plugs - solid bridge - hulls - plug at 40' -- cement to surface with 10 sx cement, 6th plug to circulate rat hole with 15 sx cement.

RECEIVED STATE CORPORATION COMMISSION

MAR 4 1986

Remarks: Used 60/40 Pozmix 6% gel by BJ-Titan (If additional description is necessary, use BACK of this form.) CONSERVATION DIVISION Wichita, Kansas

INVOICED (check) / did not observe this plugging.

DATE MAR 04 1986

Signed [Signature] (TECHNICIAN)

INV. NO. 12855 2-25-APR 10 1986

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

V

Starting Date 2/14/86 month day year

API Number 15-135-22,008-0000

OPERATOR: License # 5190 Name Sabre Exploration, Inc. Address 310 W. Central, Suite 214 City/State/Zip Wichita, Kansas 67202 Contact Person Matt Totten Phone 264-2635

NW SE NW Sec 30 Twp 17 S Rg 25 East West 3630 Ft. from South Line of Section 3630 Ft. from East Line of Section (Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 9943 Name Republic Drilling, Inc. City/State Wichita, Kansas

Nearest lease or unit boundary line 990 feet County Ness Lease Name Popp Well # 1 Ground surface elevation 2480 est feet MSL Domestic well within 330 feet yes no Municipal well within one mile yes no Surface pipe by Alternate 1 2 X Depth to bottom of fresh water 100 Depth to bottom of usable water 800 Surface pipe planned to be set 250 Projected Total Depth 4500 feet Formation Mississippian

Well Drilled For: Well Class: Type Equipment: X Oil SWD Infield X Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl X Wildcat Cable

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date Signature of Operator or Agent Matt Totten Title President

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 200 feet per 200 This Authorization Expires 8-5-86 Approved By 2-5-86

Move in 2-11-86

8 5/8 - 250'

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 1800 feet depth with 50 sxs of 60/40 poz 2nd plug @ 800 feet depth with 80 sxs of 60/40 poz 3rd plug @ 280 feet depth with 40 sxs of 60/40 poz 4th plug @ 40 feet depth with 10 @ Solid bridge sxs of 60/40 poz 5th plug @ feet depth with sxs of (2) Rathole with 15 sxs (b) Mousehole with sxs

PUSHER Jandiger TD 4475 FORMATION Tplio SURFACE PIPE 8 5/8 @ 278 ANHYDRITE 1801 ELEVATION 2490 STARTING TIME & DATE 5:00 am 2-25-86 COMPLETION TIME & DATE 4:30 am 2-25-86 1st PLUG @ 1800 FT. W/ 50 SX 2nd PLUG @ 800 FT. W/ 80 SX 3rd PLUG @ 300 FT. W/ 40 SX 4th PLUG @ 40 FT. W/ 10 SX RAT HOLE CIRCULATED W/ 15 SX MOUSE HOLE CIRCULATED W/ SX WATER WELL PLUGGED W/ SX CEMENT COMPANY B & Tiler TECHNICIAN

RECEIVED STATE CORPORATION COMMISSION MAR 4 1986 CONSERVATION DIVISION Wichita, Kansas