



KANSAS CORPORATION COMMISSION 1073873  
OIL & GAS CONSERVATION DIVISION

Form ACO-1  
June 2009  
Form Must Be Typed  
Form must be Signed  
All blanks must be Filled

**CONFIDENTIAL**

**WELL COMPLETION FORM**  
**WELL HISTORY - DESCRIPTION OF WELL & LEASE**

OPERATOR: License # 34192  
Name: SandRidge Exploration and Production LLC  
Address 1: 123 ROBERT S. KERR AVE  
Address 2: \_\_\_\_\_  
City: OKLAHOMA CITY State: OK Zip: 73102 + 6406  
Contact Person: Tiffany Golay  
Phone: (405) 429-6543  
CONTRACTOR: License # 34464  
Name: Lariat Services, Inc.  
Wellsite Geologist: Kathy Gentry  
Purchaser: NCRA (oil), DCP Midstream, LP (gas)

Designate Type of Completion:  
 New Well     Re-Entry     Workover  
 Oil     WSW     SWD     SIOW  
 Gas     D&A     ENHR     SIGW  
 OG     GSW     Temp. Abd.  
 CM (Coal Bed Methane)  
 Cathodic     Other (Core, Expl., etc.): \_\_\_\_\_

If Workover/Re-entry: Old Well Info as follows:  
Operator: \_\_\_\_\_  
Well Name: \_\_\_\_\_  
Original Comp. Date: \_\_\_\_\_ Original Total Depth: \_\_\_\_\_  
 Deepening     Re-perf.     Conv. to ENHR     Conv. to SWD  
 Conv. to GSW  
 Plug Back: \_\_\_\_\_ Plug Back Total Depth  
 Commingled    Permit #: \_\_\_\_\_  
 Dual Completion    Permit #: \_\_\_\_\_  
 SWD    Permit #: \_\_\_\_\_  
 ENHR    Permit #: \_\_\_\_\_  
 GSW    Permit #: \_\_\_\_\_  
1/9/2012    3/1/2012    3/5/2012  
Spud Date or    Date Reached TD    Completion Date or  
Recompletion Date       Recompletion Date

API No. 15 - 15-033-21614-01-00  
Spot Description: \_\_\_\_\_  
N2 N2 NW NW Sec. 6 Twp. 32 S. R. 19  East  West  
165 Feet from  North /  South Line of Section  
660 Feet from  East /  West Line of Section  
Footages Calculated from Nearest Outside Section Corner:  
 NE  NW  SE  SW  
County: Comanche  
Lease Name: Brentley Well #: 1-6H  
Field Name: \_\_\_\_\_  
Producing Formation: Mississippi  
Elevation: Ground: 2148 Kelly Bushing: 2168  
Total Depth: 9710 Plug Back Total Depth: \_\_\_\_\_  
Amount of Surface Pipe Set and Cemented at: 1009 Feet  
Multiple Stage Cementing Collar Used?  Yes  No  
If yes, show depth set: \_\_\_\_\_ Feet  
If Alternate II completion, cement circulated from: \_\_\_\_\_  
feet depth to: \_\_\_\_\_ w/ \_\_\_\_\_ sx cmt.

**Drilling Fluid Management Plan**  
(Data must be collected from the Reserve Pit)  
Chloride content: 18500 ppm Fluid volume: 6330 bbls  
Dewatering method used: Haul Off Pit  
Location of fluid disposal if hauled offsite:  
Operator Name: Triple C Soil Farming  
Lease Name: unknown License #: 99999  
Quarter NE Sec. 22 Twp. 26 S. R. 18  East  West  
County: Woodward, OK Permit #: 19661

**AFFIDAVIT**

I am the affiant and I hereby certify that all requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Submitted Electronically

**KCC Office Use ONLY**

Letter of Confidentiality Received  
Date: 05/03/2012  
 Confidential Release Date: \_\_\_\_\_  
 Wireline Log Received  
 Geologist Report Received  
 UIC Distribution  
ALT  I  II  III Approved by: NAOMI JAMES Date: 05/03/2012





Company: Sandridge Energy  
 Field: Comanche County  
 County: Comanche  
 Well Name: Brentley #1-6H  
 Rig: Lariat 3

Job Number: 4417611  
 Magnetic Decl: 5.64  
 Grid Corr: -0.57  
 Total Survey Corr: 6.21  
 Date Printed: 10-Feb-12

Proposed Azimuth: 180.43  
 Target Inclination: 0.00  
 TVD: 4420.38  
 BRN From Survey: 6.33  
 BRN From Bit: 6.33

Projection	40.00	Depth (ft)	9707.00	Incl.	89.53	Azimuth	182.22	TVD	5325.92	VS	4797.49	N/S	4797.46 S	E/W	21.00 W
No.	Tool Type	Depth (ft)	Incl (°)	Azimuth (°)	Quadrant	Course Lgth(ft)	TVD (ft)	VS (ft)	Coordinates		Closure		DLS	Bld Rate	Wlk Rate
									N/S (ft)	E/W (ft)	Dist (ft)	Ang (°)	(%/100')	(%/100')	(%/100')
0	TIE	18	0.00	0.00			18.00	0.00	0.00 N	0.00 E	0.00	0.00	0.00	0.00	0
1	M/S	267	0.51	0.00	N 0.00 E	249	267.00	-1.11	1.11 N	0.00 E	1.11	0.00	0.20	0.20	0.00
2	M/S	460	0.42	0.00	N 0.00 E	193	459.99	-2.67	2.67 N	0.00 E	2.67	0.00	0.05	-0.05	0.00
3	M/S	750	0.60	0.00	N 0.00 E	290	749.98	-5.26	5.26 N	0.00 E	5.26	0.00	0.06	0.06	0.00
4	MWD	1030	0.30	36.01	N 36.01 E	290	1029.97	-7.32	7.31 N	0.43 E	7.33	3.37	0.14	-0.11	12.86
5	MWD	1093	0.15	142.63	S 37.37 E	63	1092.97	-7.39	7.38 N	0.58 E	7.41	4.48	0.59	-0.24	169.24
6	MWD	1187	0.21	155.54	S 24.46 E	94	1186.97	-7.13	7.13 N	0.72 E	7.16	5.80	0.08	0.06	13.73
7	MWD	1374	0.39	92.05	S 87.95 E	187	1373.97	-6.80	6.79 N	1.50 E	6.96	12.47	0.19	0.10	-33.95
8	MWD	1852	0.96	103.56	S 76.44 E	478	1851.93	-5.85	5.80 N	7.02 E	9.10	50.46	0.12	0.12	2.41
9	MWD	2330	2.12	133.10	S 46.90 E	478	2329.76	1.05	1.18 S	17.37 E	17.41	93.90	0.29	0.24	6.18
10	MWD	2809	1.27	122.68	S 57.32 E	479	2808.54	9.89	10.10 S	28.31 E	30.06	109.64	0.19	-0.18	-2.18
11	MWD	3289	1.45	114.50	S 65.50 E	480	3288.41	15.21	15.49 S	38.31 E	41.32	112.02	0.06	0.04	-1.70
12	MWD	3576	1.31	80.38	N 80.38 E	287	3575.33	16.11	16.45 S	44.85 E	47.77	110.14	0.29	-0.05	-11.89
13	MWD	3864	0.90	115.96	S 64.04 E	288	3863.28	16.52	16.89 S	50.13 E	52.90	108.62	0.27	-0.14	12.35
14	MWD	4151	1.03	93.23	S 86.77 E	287	4150.24	17.61	18.02 S	54.73 E	57.62	108.23	0.14	0.05	-7.92
15	MWD	4325	1.48	75.88	N 75.88 E	174	4324.20	17.12	17.56 S	58.47 E	61.05	106.72	0.34	0.26	-9.97
16	MWD	4373	1.42	95.68	S 84.32 E	48	4372.18	17.02	17.47 S	59.66 E	62.17	106.32	1.05	-0.13	41.25
17	MWD	4405	2.72	142.40	S 37.60 E	32	4404.16	17.66	18.11 S	60.52 E	63.17	106.66	6.34	4.06	146.00
18	MWD	4437	5.00	159.95	S 20.05 E	32	4436.09	19.56	20.02 S	61.46 E	64.64	108.05	7.94	7.13	54.84
19	MWD	4469	7.64	165.62	S 14.38 E	32	4467.89	22.93	23.40 S	62.47 E	66.71	110.53	8.47	8.25	17.72
20	MWD	4501	9.93	168.21	S 11.79 E	32	4499.52	27.68	28.16 S	63.56 E	69.52	113.89	7.26	7.16	8.09
21	MWD	4534	11.80	174.86	S 5.12 E	33	4531.92	33.82	34.30 S	64.44 E	73.01	118.03	6.82	5.67	20.21
22	MWD	4566	13.90	179.58	S 0.42 E	32	4563.12	40.92	41.41 S	64.76 E	76.87	122.59	7.33	6.56	14.69
23	MWD	4598	16.29	182.58	S 2.58 W	32	4594.02	49.25	49.74 S	64.59 E	81.52	127.60	7.86	7.47	9.38
24	MWD	4630	18.52	184.08	S 4.08 W	32	4624.55	58.81	59.29 S	64.03 E	87.26	132.80	7.11	6.97	4.69
25	MWD	4662	20.15	186.36	S 6.36 W	32	4654.74	69.36	69.84 S	63.06 E	94.09	137.92	5.61	5.09	7.13
26	MWD	4694	22.21	186.24	S 6.24 W	32	4684.58	80.86	81.33 S	61.79 E	102.14	142.78	6.44	6.44	-0.38
27	MWD	4725	23.71	187.17	S 7.17 W	31	4713.12	92.88	93.34 S	60.37 E	111.16	147.10	4.98	4.84	3.00
28	MWD	4757	23.91	188.35	S 8.35 W	32	4742.40	105.69	106.14 S	58.63 E	121.25	151.08	1.61	0.62	3.69
29	MWD	4789	25.00	190.10	S 10.10 W	32	4771.53	118.78	119.21 S	56.50 E	131.92	154.64	4.09	3.41	5.47
30	MWD	4821	26.79	190.79	S 10.79 W	32	4800.32	132.55	132.95 S	53.96 E	143.49	157.91	5.67	5.59	2.16
31	MWD	4853	27.53	193.22	S 13.22 W	32	4828.79	146.85	147.24 S	50.92 E	155.79	160.92	4.17	2.31	7.59
32	MWD	4885	28.74	193.53	S 13.53 W	32	4857.01	161.56	161.92 S	47.43 E	168.72	163.67	3.81	3.78	0.97
33	MWD	4916	31.25	193.21	S 13.21 W	31	4883.85	176.66	176.99 S	43.85 E	182.35	166.09	8.11	8.10	-1.03
34	MWD	4948	33.60	192.87	S 12.87 W	32	4910.86	193.40	193.71 S	39.98 E	197.79	168.34	7.37	7.34	-1.06
35	MWD	4980	35.53	192.64	S 12.64 W	32	4937.21	211.14	211.42 S	35.97 E	214.45	170.34	6.05	6.03	-0.72
36	MWD	5012	37.80	191.90	S 11.90 W	32	4962.88	229.84	230.09 S	31.92 E	232.29	172.10	7.23	7.09	-2.31
37	MWD	5044	40.40	189.82	S 9.82 W	32	4987.71	249.69	249.90 S	28.12 E	251.48	173.58	9.10	8.13	-6.50
38	MWD	5076	42.75	191.11	S 11.11 W	32	5011.65	270.59	270.78 S	24.26 E	271.87	174.88	7.82	7.34	4.03
39	MWD	5108	44.18	191.83	S 11.83 W	32	5034.87	292.20	292.36 S	19.88 E	293.03	176.11	4.73	4.47	2.25
40	MWD	5140	47.17	191.53	S 11.53 W	32	5057.23	314.65	314.77 S	15.25 E	315.14	177.23	9.37	9.34	-0.94
41	MWD	5172	49.51	190.96	S 10.96 W	32	5078.50	338.13	338.22 S	10.59 E	338.38	178.21	7.43	7.31	-1.78
42	MWD	5204	50.11	191.37	S 11.37 W	32	5099.15	362.15	362.20 S	5.86 E	362.25	179.07	2.12	1.88	1.28
43	MWD	5236	50.13	191.31	S 11.31 W	32	5119.67	386.26	386.28 S	1.03 E	386.28	179.85	0.16	0.06	-0.19
44	MWD	5268	50.24	190.99	S 10.99 W	32	5140.16	410.41	410.39 S	3.72 W	410.41	180.52	0.84	0.34	-1.00
45	MWD	5300	50.27	190.74	S 10.74 W	32	5160.62	434.61	434.56 S	8.36 W	434.64	181.10	0.61	0.09	-0.78
46	MWD	5332	51.20	190.74	S 10.74 W	32	5180.87	458.98	458.90 S	12.98 W	459.08	181.62	2.91	2.91	0.00
47	MWD	5363	54.25	189.89	S 9.89 W	31	5199.64	483.28	483.16 S	17.39 W	483.48	182.06	10.08	9.84	-2.74
48	MWD	5395	57.76	188.95	S 8.95 W	32	5217.53	509.49	509.34 S	21.73 W	509.80	182.44	11.30	11.03	-2.94
49	MWD	5427	61.65	189.04	S 9.04 W	32	5233.66	536.81	536.62 S	26.05 W	537.26	182.78	12.10	12.09	0.28
50	MWD	5458	64.27	188.88	S 8.88 W	31	5247.75	564.11	563.90 S	30.35 W	564.71	183.08	8.46	8.45	-0.52
51	MWD	5490	66.61	188.19	S 8.19 W	32	5261.05	592.92	592.68 S	34.67 W	593.69	183.35	7.57	7.31	-2.16
52	MWD	5522	69.61	187.40	S 7.40 W	32	5272.98	622.37	622.09 S	38.69 W	623.29	183.56	9.65	9.38	-2.47
53	MWD	5554	72.58	186.85	S 6.85 W	32	5283.35	652.43	652.13 S	42.45 W	653.51	183.72	9.42	9.28	-1.72



Company: Sandridge Energy  
 Field: Comanche County  
 County: Comanche  
 Well Name: Brentley #1-6H  
 Rig: Lariat 3

Job Number: 4417611  
 Magnetic Decl: 5.64  
 Grid Corr: -0.57  
 Total Survey Corr: 6.21  
 Date Printed: 10-Feb-12

Proposed Azimuth: 180.43  
 Target Inclination: 0.00  
 TVD: 4420.38  
 BRN From Survey: 6.33  
 BRN From Bit: 6.33

Projection	40.00	Depth (ft)	9707.00	Incl.	89.53	Azimuth	182.22	TVD	5325.92	VS	4797.49	N/S	4797.46	S	E/W	21.00	W
No.	Tool Type	Depth (ft)	Incl (°)	Azimuth (°)	Quadrant	Course Lgth(ft)	TVD (ft)	VS (ft)	Coordinates		Closure		DLS (°/100')	Bld Rate (°/100')	Wlk Rate (°/100')		
54	MWD	5586	75.42	185.70	S 5.70 W	32	5292.17	683.03	682.70	S	45.80	W	684.24	183.84	9.52	8.88	-3.59
55	MWD	5598	76.45	185.05	S 5.05 W	12	5295.09	694.62	694.29	S	46.89	W	695.87	183.86	10.06	8.58	-5.42
56	MWD	5652	80.70	183.14	S 3.14 W	54	5305.78	747.43	747.07	S	50.67	W	748.79	183.88	8.60	7.87	-3.54
57	MWD	5684	84.16	182.92	S 2.92 W	32	5310.00	779.11	778.74	S	52.34	W	780.50	183.85	10.83	10.81	-0.69
58	MWD	5716	88.24	182.34	S 2.34 W	32	5312.12	811.01	810.63	S	53.81	W	812.42	183.80	12.88	12.75	-1.81
59	MWD	5748	88.39	182.20	S 2.20 W	32	5313.06	842.98	842.59	S	55.07	W	844.39	183.74	0.64	0.47	-0.44
60	MWD	5812	90.46	181.14	S 1.14 W	64	5313.70	906.96	906.56	S	56.94	W	908.34	183.59	3.63	3.23	-1.66
61	MWD	5876	90.37	180.78	S 0.78 W	64	5313.24	970.96	970.55	S	58.01	W	972.28	183.42	0.58	-0.14	-0.56
62	MWD	5972	90.49	180.31	S 0.31 W	96	5312.52	#####	#####	S	58.92	W	1068.17	183.16	0.51	0.12	-0.49
63	MWD	6067	90.89	179.74	S 0.26 E	95	5311.37	#####	#####	S	58.97	W	1163.03	182.91	0.73	0.42	-0.60
64	MWD	6163	91.39	179.63	S 0.37 E	96	5309.46	#####	#####	S	58.44	W	1258.87	182.66	0.53	0.52	-0.11
65	MWD	6260	89.42	178.79	S 1.21 E	97	5308.78	#####	#####	S	57.10	W	1355.70	182.41	2.21	-2.03	-0.87
66	MWD	6356	89.32	178.51	S 1.49 E	96	5309.83	#####	#####	S	54.84	W	1451.50	182.17	0.31	-0.10	-0.29
67	MWD	6451	89.45	178.51	S 1.49 E	95	5310.85	#####	#####	S	52.37	W	1546.31	181.94	0.14	0.14	0.00
68	MWD	6548	88.64	177.78	S 2.22 E	97	5312.47	#####	#####	S	49.23	W	1643.10	181.72	1.12	-0.84	-0.75
69	MWD	6644	88.55	177.51	S 2.49 E	96	5314.82	#####	#####	S	45.29	W	1738.84	181.49	0.30	-0.09	-0.28
70	MWD	6740	88.98	177.46	S 2.54 E	96	5316.89	#####	#####	S	41.07	W	1834.59	181.28	0.45	0.45	-0.05
71	MWD	6837	89.14	177.30	S 2.70 E	97	5318.48	#####	#####	S	36.64	W	1931.37	181.09	0.23	0.16	-0.16
72	MWD	6934	89.23	176.99	S 3.01 E	97	5319.86	#####	#####	S	31.81	W	2028.14	180.90	0.33	0.09	-0.32
73	MWD	7031	89.57	176.52	S 3.48 E	97	5320.88	#####	#####	S	26.32	W	2124.89	180.71	0.60	0.35	-0.48
74	MWD	7128	89.54	176.34	S 3.66 E	97	5321.63	#####	#####	S	20.28	W	2221.63	180.52	0.19	-0.03	-0.19
75	MWD	7225	89.45	175.95	S 4.05 E	97	5322.49	#####	#####	S	13.76	W	2318.35	180.34	0.41	-0.09	-0.40
76	MWD	7320	89.82	176.48	S 3.52 E	95	5323.09	#####	#####	S	7.49	W	2413.11	180.18	0.68	0.39	0.56
77	MWD	7416	90.09	176.15	S 3.85 E	96	5323.17	#####	#####	S	1.32	W	2508.90	180.03	0.44	0.28	-0.34
78	MWD	7512	89.35	176.79	S 3.21 E	96	5323.64	#####	#####	S	4.59	E	2604.72	179.90	1.02	-0.77	0.67
79	MWD	7608	89.35	175.89	S 4.11 E	96	5324.73	#####	#####	S	10.72	E	2700.54	179.77	0.94	0.00	-0.94
80	MWD	7703	89.94	177.04	S 2.96 E	95	5325.31	#####	#####	S	16.58	E	2795.38	179.66	1.36	0.62	1.21
81	MWD	7798	90.49	177.06	S 2.94 E	95	5324.96	#####	#####	S	21.47	E	2890.29	179.57	0.58	0.58	0.02
82	MWD	7892	89.91	178.07	S 1.93 E	94	5324.63	#####	#####	S	25.46	E	2984.23	179.51	1.24	-0.62	1.07
83	MWD	7988	89.88	178.58	S 1.42 E	96	5324.81	#####	#####	S	28.27	E	3080.21	179.47	0.53	-0.03	0.53
84	MWD	8083	90.15	179.06	S 0.94 E	95	5324.78	#####	#####	S	30.22	E	3175.20	179.45	0.58	0.28	0.51
85	MWD	8178	90.46	179.00	S 1.00 E	95	5324.27	#####	#####	S	31.83	E	3270.20	179.44	0.33	0.33	-0.06
86	MWD	8274	90.62	179.33	S 0.67 E	96	5323.37	#####	#####	S	33.23	E	3366.19	179.43	0.38	0.17	0.34
87	MWD	8369	90.68	178.79	S 1.21 E	95	5322.29	#####	#####	S	34.79	E	3461.18	179.42	0.57	0.06	-0.57
88	MWD	8427	89.14	179.54	S 0.46 E	58	5322.38	#####	#####	S	35.63	E	3519.18	179.42	2.95	-2.66	1.29
89	MWD	8491	88.80	180.99	S 0.99 W	64	5323.53	#####	#####	S	35.34	E	3583.16	179.43	2.33	-0.53	2.27
90	MWD	8586	88.71	180.92	S 0.92 W	95	5325.60	#####	#####	S	33.75	E	3678.11	179.47	0.12	-0.09	-0.07
91	MWD	8682	88.89	181.44	S 1.44 W	96	5327.61	#####	#####	S	31.78	E	3774.04	179.52	0.57	0.19	0.54
92	MWD	8777	90.18	182.47	S 2.47 W	95	5328.38	#####	#####	S	28.54	E	3868.95	179.58	1.74	1.36	1.08
93	MWD	8873	89.78	182.57	S 2.57 W	96	5328.41	#####	#####	S	24.32	E	3964.83	179.65	0.43	-0.42	0.10
94	MWD	8969	90.80	182.90	S 2.90 W	96	5327.93	#####	#####	S	19.74	E	4060.69	179.72	1.12	1.06	0.34
95	MWD	9064	91.08	182.90	S 2.90 W	95	5326.37	#####	#####	S	14.93	E	4155.53	179.79	0.29	0.29	0.00
96	MWD	9160	91.20	183.42	S 3.42 W	96	5324.46	#####	#####	S	9.64	E	4251.35	179.87	0.56	0.13	0.54
97	MWD	9255	89.48	183.26	S 3.26 W	95	5323.89	#####	#####	S	4.10	E	4346.18	179.95	1.82	-1.81	-0.17
98	MWD	9350	89.45	183.79	S 3.79 W	95	5324.78	#####	#####	S	1.74	W	4440.99	180.02	0.56	-0.03	0.56
99	MWD	9446	90.00	183.20	S 3.20 W	96	5325.24	#####	#####	S	7.59	W	4536.82	180.10	0.84	0.57	-0.61
100	MWD	9541	89.69	183.00	S 3.00 W	95	5325.50	#####	#####	S	12.73	W	4631.69	180.16	0.39	-0.33	-0.21
101	MWD	9637	90.09	183.04	S 3.04 W	96	5325.68	#####	#####	S	17.78	W	4727.57	180.22	0.42	0.42	0.04
102	MWD	9667	89.85	182.69	S 2.69 W	30	5325.70	#####	#####	S	19.28	W	4757.54	180.23	1.41	-0.80	-1.17

	TARGET
TVD	4420.38
VS	3.87
N/S	3.87 S
E/W	0.03 W

Inc. Needed	Direction Needed	Dist To Target
----------------	---------------------	-------------------

0.07	180.3	4.98
0.09	180.3	6.54
0.14	180.2	9.13
0.19	182.4	11.19
0.19	183.1	11.27
0.20	183.9	11.02
0.20	188.2	10.77
0.27	216.1	11.96
0.48	261.2	17.61
1.03	282.4	29.01
2.03	286.9	40.06
3.16	285.7	46.61
5.31	284.6	51.82
11.83	284.5	56.56
31.99	283.2	60.08
51.79	282.8	61.22
75.39	283.2	62.20
-76.12	284.7	63.58
-54.03	287.3	65.48
-40.70	290.9	68.07
-32.59	295.3	71.30
-27.68	300.1	74.88
-24.53	305.4	79.24
-22.53	310.9	84.70
-21.28	316.3	91.28
-20.56	321.4	99.10
-20.24	326.0	107.95
-20.11	330.2	117.90
-20.09	333.9	128.45
-20.22	337.3	139.92
-20.43	340.4	152.15
-20.70	343.3	165.02
-21.07	345.8	178.60
-21.58	348.1	194.01
-22.17	350.2	210.65
-22.84	352.0	228.46
-23.58	353.5	247.64
-24.38	354.8	268.02
-25.20	356.1	289.17
-26.05	357.2	311.28
-26.94	358.2	334.52
-27.83	359.1	358.38
-28.67	359.8	382.41
-29.46	0.5	406.54
-30.20	1.1	430.77
-30.90	1.6	455.21
-31.61	2.1	479.61
-32.40	2.5	505.93
-33.26	2.8	533.39
-34.13	3.1	560.85
-35.05	3.4	589.83
-36.00	3.6	619.43
-36.97	3.7	649.65

	TARGET
TVD	4420.38
VS	3.87
N/S	3.87 S
E/W	0.03 W

Inc. Needed	Direction Needed	Dist To Target
-37.97	3.9	680.37
-38.35	3.9	692.01
-40.08	3.9	744.92
-41.12	3.9	776.64
-42.20	3.8	808.55
-43.28	3.8	840.53
-45.36	3.6	904.48
-47.32	3.4	968.42
-50.03	3.2	1064.30
-52.45	2.9	1159.16
-54.69	2.7	1255.00
-56.69	2.4	1351.83
-58.43	2.2	1447.63
-60.00	1.9	1542.44
-61.44	1.7	1639.23
-62.73	1.5	1734.97
-63.91	1.3	1830.72
-65.02	1.1	1927.50
-66.04	0.9	2024.27
-67.00	0.7	2121.02
-67.88	0.5	2217.76
-68.71	0.3	2314.48
-69.46	0.2	2409.24
-70.18	0.0	2505.03
-70.85	359.9	2600.85
-71.46	359.8	2696.67
-72.04	359.7	2791.51
-72.60	359.6	2886.42
-73.12	359.5	2980.36
-73.62	359.5	3076.34
-74.08	359.5	3171.33
-74.53	359.4	3266.33
-74.97	359.4	3362.32
-75.38	359.4	3457.31
-75.61	359.4	3515.31
-75.84	359.4	3579.29
-76.16	359.5	3674.24
-76.47	359.5	3770.17
-76.78	359.6	3865.08
-77.09	359.6	3960.96
-77.39	359.7	4056.82
-77.69	359.8	4151.66
-77.98	359.9	4247.48
-78.25	359.9	4342.31
-78.48	0.0	4437.12
-78.71	0.1	4532.95
-78.93	0.2	4627.82
-79.15	0.2	4723.70
-79.22	0.2	4753.67

Section 36  
31S 20W

Section 31  
31S 19W

**BRENTLEY 1-6H**



Miss Entry: 5395'  
-99.433876 37.292533


Top Perf: 5490'  
-99.433919 37.292303

Section 1  
32S 20W

Section 6  
32S 19W

Bottom Perf: 9255'  
-99.433655 37.281996

BHL: 9667'  
-99.433722 37.280866



Section 12  
32S 20W


Section 7  
32S 19W



**Actual Bottom-Hole Location of Brentley 1-6H**  
Comanche County, Kansas  
T&R: 32S 19W  
Section: 6, 777' FWL & 309' FSL  
Long/Lat: -99.433722 37.280866  
1 in = 667 ft



- Actual BH Location
- SandRidge Wells
- Perf
- Sections



Draftsman: Aaron Birk	Draft Date: 4/25/2012
Drawing Name/Number: Addendum_Brentley_1-6H.mxd	
Coordinate System: NAD 1927 State Plane Kansas South FIPS: 1502	