

1 071023

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-101-21,568 -00-00 33R

N/2 NE NW, SEC. 33, T. 17 S, R. 27 W/EK

4950 feet from S section line

3300 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 9041

Lease Name L.J. Spanier Well # 1

Operator: Joseph H. Strabala Oil

County Lane

Name & Address 312 E. Unintah St.

Well Total Depth 4650 151.12 feet

Address 312 E. Unintah St.

Colorado Springs, CO 80903

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 257

Abandoned Oil Well Gas Well _____ Input Well _____ SMD Well _____ D&A _____

Other well as hereinafter indicated _____

Plugging Contractor Joseph H. Strabala Oil License Number 9041

Address 312 E. Unintah St., Colorado Springs, CO 80903

Company to plug at: Hour: 10:10 a.m. Day: 11 Month: 2 Year: 19 92

Plugging proposal received from Terry Williamson

(company name) agent for Strabala (phone) 913-731-2408

were: 4 1/2" at 4649' w/390 sx cement, PBD 4620', Perfs at 4204-4549', 2-staged

1st plug pump 2 sx hulls, fill with cement.

Check backside.

Plugging Proposal Received by Steve Pfeifer (TECHNICIAN)

Plugging Operations attended by Agent?: All Part _____ None _____

Operations Completed: Hour: 10:30 a.m. Day: 11 Month: 2 Year: 19 92

ACTUAL PLUGGING REPORT 1st plug pumped 200 lbs. hulls in first part of 280 sx cement down

4 1/2". Maximum pressure 0 psi and shut in on vacuum.

Cement at surface on backside.

RECEIVED

Was perforated at 1350', cemented with 220 sx 60/40 Pozmix and 75 sx common cement, circulated.

FEB 13 1992

CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 65/35 Pozmix 6% gel by Allied. No casing recovery.

(if additional description is necessary, use BACK of this form.)

Observe this plugging.

Signed Dan Gooders (TECHNICIAN)

DATE MAR 1 1992

34218