*TO: STATE CORPORATION COMMISSION

i	API	N	JMBI	ΞR	15-101-	21,77	75	C	<u>00</u>	0			
100	'N	SE	NE	NW	SEC.	-5	_	т	16	S.	R	29	W

CONSERVATION DIVISION - PLUGGING SECTION890FEET FROM NORTH SECTION LINE
WICHITA STATE OFFICE BLDG., 130 S. MARKET2310FEET FROM WEST SECTION LINE
WICHITA, KANSAS 67202 LEASE NAME SPEER WELL # 1
technician's plugging report 26 county <u>lane</u> 68.88
OPERATOR LICENSE # 5046 WELL TOTAL DEPTH 3350 FEET
OPERATOR: RAYMOND OIL COMPANY, INC. PRODUCTION CSG: SIZE " FEET "
NAME AND PO BOX 48788 SURFACE CASING: SIZE 856" @ 257' WITH SX
ADDRESS WICHITA, KS 67201-8788
ABANDONED OIL WELLGAS WELLINPUT WELLSWD WELLD/A X
OTHER WELL AS HEREINAFTER INDICATED
PLUGGING CONTRACTOR SHIELDS DRILLING LICENSE NUMBER 5184
ADDRESS PO BOX 709 RUSSELL, KS 67665-0709
COMPANY TO PLUG AT: HOUR: 11:00 PM DAY: 05 MONTH: 02 YEAR: 2000
PLUGGING PROPOSAL RECEIVED FROM BURT BEERY
(COMPANY NAME) SHIELDS DRILLING (PHONE) 785-483-3141
WERE:
1ST PLUG AT 2060' WITH 50 SX CEMENT. 2ND PLUG AT 1260' WITH 80 SX CEMENT.
3RD PLUG AT 600' WITH 40 SX CEMENT. 4TH PLUG AT 290' WITH 40 SX CEMENT.
5TH PLUG AT 40' WITH 10 SX CEMENT. 6TH PLUG TO CIRCULATE RAT HOLE WITH 15 SX CEMENT.
7TH PLUG TO CIRCULATE MOUSE HOLE WITH 10 SX CEMENT.
PLUGGING PROPOSAL RECEIVED BY RICHARD LACEY
PLUGGING OPERATIONS ATTENDED BY AGENT?: ALLPARTNONE _X
OPERATIONS COMPLETED: HOUR: 3:00 AM DAY: 06 MONTH: 02 YEAR: 2000 RECEIVED
ACTUAL PLUGGING REPORT LOAD HOLE WITH HEAVY MUD SPOT PLUGS THRU DRILLTATE PERPORATION COMMISSION
1ST PLUG AT 2060' WITH 50 SX CEMENT. 2ND PLUG AT 1260' WITH 80 SX CEMENT. FEB 1 4 2000
3RD PLUG AT 600' WITH 40 SX CEMENT. 4TH PLUG AT 290' WITH 40 SX CEMENT. CONSERVATION DIVISION
5TH PLUG AT 40' WITH 10 SX CEMENT. 6TH PLUG TO CIRCULATE RAT HOLE WITH 15 Winderman.
7TH PLUG TO CIRCULATE MOUSE HOLE WITH 10 SX CEMENT.
REMARKS: USED 60/40 POZMIX 6% GEL X# FLO SEAL BY ALLIED. (IF ADDITIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM.)
I DID NOT OBSERVE THIS PLUGGING. 2/5/00 SIGNED Ribbord W. Facty (TECHNICIAN) FORM CP-2/3
Ula46 (TECHNICIAN) FORM CP-2/3