

To: I 052234
STATE CORPORATION COMMISSION
Wichita State Office Bldg. - PLUGGING SECTION
130 S. Market, Room 2078
Wichita, KS 67202

3-24 API NUMBER 15- 101-21,756 - 00-00
NW SE NE, SEC. 19, T 16 S, R 27 W/R
1650 feet from NSK section line
990 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 31283

Lease Name Gates B Well # 1

Operator: Rheem Resources, Inc.

County Lane 150.15

Name & Address 100 S. Main, Ste. 505

Well Total Depth 4640 feet

Wichita, KS 67202-3738

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 210

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Shields Drilling Co. Inc. License Number 5184

Address P.O. Box 709, Russell, KS 67665

Company to plug at: Hour: 10 p.m. Day: 23 Month: 3 Year: 19 98

Plugging proposal received from Burt Beery

(company name) Shields Drilling Co., Inc. (phone) 785-483-3141

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2156-96' Elevation 2735' GL

1st plug at 2190' with 50 sx cement, 2nd plug at 1360' with 80 sx cement,

3rd plug at 650' with 40 sx cement, 4th plug at 240' with 40 sx cement,

5th plug at 40' with 10 sx cement,

6th plug to circulate rathole with 15 sx cement, 7th plug to circulate mousehole with 10 sx

cement. Plugging Proposal Received by Richard Lacey (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 1 a.m. Day: 24 Month: 3 Year: 19 98

ACTUAL PLUGGING REPORT 1st plug at 2190' with 50 sx cement,

2nd plug at 1360' with 80 sx cement, 3rd plug at 650' with 40 sx cement,

4th plug at 240' with 40 sx cement,

5th plug at 40' with 10 sx cement,

6th plug to circulate rathole with 15 sx cement,

7th plug to circulate mousehole with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel 1/4# floseal by Allied. (If additional description is necessary, use BACK of this form.)

INVOICED (did not) observe this plugging.

DATE 3-30-98

Signed Richard W. Lacey (TECHNICIAN)

INV. NO. 50325

EFFECTIVE DATE: 12.17.97
DISTRICT #
SSA? Yes No

State of Kansas
NOTICE OF INTENTION TO DRILL 101-21,756-0000
FORM MUST BE TYPED
FORM MUST BE SIGNED
ALL BLANKS MUST BE FILLED

Expected Spud Date JANUARY 12 1998
month day year

Spot
NW SE NE Sec 19 Twp 16 S. Rg 27 East
 West

OPERATOR: License # 31283
Name: RHEEM RESOURCES, INC.
Address: 100 S. MAIN SUITE 505
City/State/Zip: WICHITA, KS 67202-3738
Contact Person: WARREN TOMLINSON
Phone: 316-262-5099

1650 feet from South/North line of Section
990 feet from East/West line of Section
IS SECTION REGULAR IRREGULAR

CONTRACTOR: License # 5559 5184
Name: SHIELDS DRILLING
(SHIELDS OIL PRODUCERS, INC.)
Well Drilled For: Well Class: Type Equipment:

(NOTE: Locate well on the Section Plat on Reverse Side)
County: LANE
Lease Name: GATES "B" Well #: 1
Field Name: NONE

Oil ... Enh Rec ... Infield Mud Rotary
... Gas ... Storage ... Pool Ext. ... Air Rotary
... OUVG ... Disposal Wildcat ... Cable
... Seismic; ... # of Holes ... Other
... Other
If OUVG, old well information as follows:
Operator:
Well Name:
Comp. Date: Old Total Depth

Is this a Prorated/Spaced Field? ... yes no
Target Formation(s): KANSAS CITY MARMATON
Nearest lease or unit boundary: 990
Ground Surface Elevation: 2738 feet MSL
Water well within one-quarter mile: ... yes no
Public water supply well within one mile: ... yes no

Directional, Deviated or Horizontal wellbore? ... yes no
If yes, true vertical depth:
Bottom Hole Location:
Exp. 6/12/98

Depth to bottom of fresh water: 180
Depth to bottom of usable water: 1340
Surface Pipe by Alternate: 1 2
Length of Surface Pipe Planned to be set: 300'
Length of Conductor pipe required: NONE
Projected Total Depth: 4650
Formation at Total Depth: MISSISSIPPIAN
Water Source for Drilling Operations:
... well farm pond ... other

Pusher
SPUD DATE 3-12-98 INIT. SD
LENGTH SURFACE PLANNED 210
RESERVE PIT STATUS- REMOVE FLUID LINED
after salt sect. bbls. when done bbls.
RATHOLED AHEAD? Y N SIZE HOLE
SURFACE PIPE 8 3/8 @ 210 CONDUCTOR
ANHYDRITE T-2156 B-2196 ELEVATION 2740 KK
35 GL
TD 4640 FORMATION
RAN PIPE @ DV TOOL ALT II DONE
SX Y N
Arbuckle Plug @ Ft. W/ SX
Hug./Council @ Ft. W/ SX
Anhydrite Base @ 2180 Ft. W/ 50 SX
1/2 Base Anyh. @ 1760 Ft. W/ 80 SX
1/2, 1/2 Plug @ 650 Ft. W/ 40 SX
Bottom Surface @ 240 Ft. W/ 40 SX
40' Plug @ 40 Ft. W/ 10 SX
RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ 10 SX
WATER WELL SX (Irr. Well Pond
Hauling
TECHNICIAN R. L. DATE 3-20-98
TYPE OF CEMENT 60/40 per 6% gel 1/4 Flow
STARTING TIME 10:00 (AM/PM) DATE 3-27-98
COMPLETION TIME 1:00 (AM/PM) DATE 3-24-98
CEMENT COMPANY Alliant

200' Alt
STILL DRUG.
483-2018-587