

To: 1 00027 3-18
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 101-21,696-00-00
W/2 W/2 SE, SEC. 7, T 16 S, R 27 W/E
1320 feet from S section line
2310 feet from E section line

TECHNICIAN'S PLUGGING REPORT
Operator License # 5393
Operator: A.L. Abercrombie, Inc.
Name & Address: 150 N. Main, Ste. 801
Wichita, KS 67202

Lease Name Bentley Well # 1
County Lane
Well Total Depth 4530 147.23 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 222

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X
Other well as hereinafter indicated _____

Plugging Contractor Abercrombie RTD, Inc. License Number 30684
Address 150 N. Main, Ste. 801, Wichita, KS 67202

Company to plug at: Hour: _____ Day: 18 Month: 3 Year: 19 95

Plugging proposal received from Tony Martin
(company name) Abercrombie RTD, Inc. (phone) 316-262-1841

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2096'
1st plug at 2100' with 50 sx cement, 2nd plug at 1220' with 80 sx cement,
3rd plug at 610' with 40 sx cement, 4th plug at 250' with 40 sx cement,
5th plug at 40' with 10 sx cement,
6th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Steve Middleton (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X
Operations Completed: Hour: 7:30 p.m. Day: 18 Month: 3 Year: 19 95

ACTUAL PLUGGING REPORT 1st plug at 2100' with 50 sx cement,
2nd plug at 1220' with 80 sx cement,
3rd plug at 610' with 40 sx cement,
4th plug at 250' with 40 sx cement,
5th plug at 40' with 10 sx cement,
6th plug to circulate rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel 1/2# floseal by Allied.
(if additional description is necessary, use BACK of this form.)

I (index) did not observe this plugging.

DATE MAR 20 1995
INV. NO. 43475

RECEIVED STATE CORPORATION COMMISSION
MAR 23 1995
Signed [Signature] (TECHNICIAN)

FOR KCC USE:

STATE OF KANSAS
NOTICE OF INTENTION TO DRILL
FORM MUST BE TYPED
FORM MUST BE SIGNED
ALL BLANKS MUST BE FILLED

LANE

EFFECTIVE DATE: 3-7-95

DISTRICT # 4

SGA? Yes / No

Must be approved by the K.C.C. five (5) days prior to commencing well.

Spot 101-21,696-00-00 East
W/2 - W/2 - SE. Sec .7. Twp .16. S, Rg 27. XX West

Expected Spud Date 03 02 95
month day year

1320 feet from South / North line of Section
2310 feet from East / West line of Section
IS SECTION X REGULAR IRREGULAR?

(NOTE: Locate well on the Section Plat on Reverse Side)

County: Lane

Lease Name: Bentley Well #: 1

Field Name: WC

Is this a Prorated/Spaced Field? yes X no ✓

Target Formation(s): L/KC

Nearest lease or unit boundary: 330'

Ground Surface Elevation: Unknown feet MSL

Water well within one-quarter mile: yes X no

Public water supply well within one mile: yes X no

Depth to bottom of fresh water: 100/180

Depth to bottom of usable water: 1200

Surface Pipe by Alternate: 1 X 2

Length of Surface Pipe Planned to be set: 220'

Length of Conductor pipe required: -0-

Projected Total Depth: 4500'

Formation at Total Depth: Mississippi

Water Source for Drilling Operations:

well farm pond X other

OPERATOR: License # 5393
Name: A. L. Abercrombie, Inc.
Address: 150 N. Main, Suite 801
City/State/Zip: Wichita, Ks. 67202
Contact Person: Jerry Langrehr
Phone: 316-262-1841

CONTRACTOR: License #: 30684
Name: Abercrombie RTD, Inc.

Well Drilled For: Well Class: Type Equipment:

X Oil Enh Rec Infield X Mud Rotary
Gas Storage Pool Ext. Air Rotary
OWWO Disposal X Wildcat Cable
Seismic # of Holes Other

If OWWO: old well information as follows:

Operator: N/A

Well Name: N/A

Comp. Date: Old Total Depth

Directional, Deviated or Horizontal wellbore? yes X no

If yes, true vertical depth: N/A

Bottom Hole Location: N/A

Will Cores Be Taken? yes X no

If yes, proposed zone: 200' Alt. II Req.

Exp. 9/2/95

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq.

It is agreed that the following minimum requirements will be met:

Pusher Lang SPUD DATE 3-11-95 INIT. OR

LENGTH SURFACE PLANNED 220

RESERVE PIT STATUS- REMOVE FLUID LINED
after salt sect. bbls. when done bbls.

RATHOLED AHEAD? Y N SIZE HOLE
SURFACE PIPE 8 5/8" @ 222' CONDUCTOR
ANHYDRITE T- B-2096 ELEVATION

TD 4520 FORMATION

RAN PIPE @ SX DV TOOL SX ALT II DONE Y N

Arbuckle Plug @ Ft. W/ SX

Hug./Council @ Ft. W/ SX

Anhydrite Base @ 2100 Ft. W/ 50 SX

1/2 Base Anhy. @ 1220 Ft. W/ 80 SX

1/2, 1/2 Plug @ 610 Ft. W/ 40 SX

Bottom Surface @ 250 Ft. W/ 40 SX

40' Plug @ 40 Ft. W/ 10 SX

RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ SX

WATER WELL SX (Irr. Well) Pond Hauling

TECHNICIAN SA DATE 3-15-95

TYPE OF SA RECEIVED 6/16/95

STARTING 3:30 (AM/PM) DATE 3-18

COMPLETION 3:30 (AM/PM) DATE 3-18

CEMENT Allen