## KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

| Type Test:  |  |                 |  |                                      | (\$6                                  | ee instructio                                    | ns on Rev                        | erse Side)                                       | )                                   |                |  |  |  |  |
|---|--|-----------------|--|--------------------------------------|---------------------------------------|--|----------------------------------|--|-------------------------------------|----------------|--|--|--|--|
| Type Test: Open Flow Deliverability                             |  |                 |  |                                      | Test Date: 10-11- 2011                |  |                                  |  | API No. 15 -119-211070000           |                |  |  |  |  |
| Company EAGLE CREEK CORPOR                                      |  |                 |  |                                      | ATION HOLAKE                          |  |                                  | en E   | Well Number                         |                |  | ber                                    |  |  |
|   | 4466   |                 | Location   |                                      | Section                               |  | TWP                              |  | RNG (E/V                            | ŋ              | A  | cres At                                | ributed                                      |  |
| County. Location  MEADE 2310 FEL ; 1556                         |  |                 |  | 17                                   | 34                                    | 345  |                                  |  | 160                                 |                | 2  |  |  |  |
| Cald  |  |                 |  | Reservoir                            |                                       |  |                                  | Gas Gathering Connection                         |                                     |                |  |  |  |  |
| ADAM  | us K   | Zan.            | C4   |                                      | Morroa                                | 2 <i>50</i>                                      |                                  |  | DCI                                 | MIDS           | TREAM  |  |  |  |
| ADAMS CANCH Completion Date                                     |  |                 |  | Plug Back Total Depth                |                                       |  |                                  | Packer Se  |                                     |                |  |  |  |  |
| 7/2 /2003   |  |                 |  | 474                                  |                                       |  | No                               |  |                                     |                |  |  |  |  |
|   |  |                 | Internal Diameter, Set at 4,095 6215   |                                      |                                       | ıt   | Perforations<br>5824             |  | <sup>™</sup> 58                     | " <i>58</i> 29 |  |  |  |  |
| Casing Size Weight 10.5 #                                       |  |                 | 5  |                                      |                                       |  | Daria milana                     |  |                                     |                |  |  |  |  |
|   |  | ,               | Weinnt   |                                      | Internal Diameter                     |  | Set at 5824                      |  | Perforations                        |                | N ENDED  |  |  |  |
| 2.375" 4,7 #  |  |                 |  | 1,995" 5824<br>Type Fluid Production |                                       |  | 827                              | Pump Unit or (raveling Plunger? Yes) No          |                                     |                |  |  |  |  |
| Type Com  | pletion  | (Des            |  |                                      | Type Fluid                            | Production                                       | <br>                             |  | Pump Uni                            | t or traveling | Pidigeri   | 110                                    |  |  |
| <u> </u>  | ngle   | G1              | 5  |                                      |                                       | Cont   |                                  | 76   | % Nitroge                           | <u> </u>       | Gas Gra  | vitv - G                               |  |  |
|   |  | •               | lus / Tubing   | •                                    | % Carbon Dioxide                      |  |                                  |  | A LINION                            | 41             |  | . 686                                  |  |  |
| 7   | 481  | 11/4            | <u> </u>   |                                      |                                       |  |                                  |  |                                     |                |  | (Meter Run) (Prover) Size              |  |  |
| Vertical D  |  |                 |  |                                      | Pressure Taps                         |  |                                  |  |                                     |                | 3.06   |  |  |  |
|   | 82   |                 |  |                                      |                                       |  | -/ange                           |  |                                     |                |  |  |  |  |
| Description   | Builder  | · SI            | nut In   | >-10 20                              | (1 at                                 | 9:00   | (AM) (PM)                        | Taken  | 10-11-                              | 20             | 11 at 9:08                                       | <u> </u>                               | AM)(PM)                                      |  |
| Pressure  | Danant   | j. Gi           |  |                                      |                                       |  |                                  |  |                                     |                |  |  | AM) (PM)                                     |  |
| Well on L   | ine:   | S               | arted  | 20                                   | at                                    |  | (AM) (PM)                        | 18Ken  |                                     |                | at   |  |  |  |
|   |  |                 | <del>, , , , , , , , , , , , , , , , , , , </del>  |                                      |                                       |  | - OUDEAG                         | E DATA   |                                     |                | Duration of Shut-                                | in                                     | Hours  |  |
|   |  |                 |  | <del></del>                          |                                       | ORSEHAE  | D SURFAC                         |  | 1 1                                 | ubing          | Dulution of Office                               |  |  |  |
| Static / Orifice<br>Dynamic Size<br>Property (Inches            |  | ce              | Circle one:<br>Meter   | Pressure<br>Differential             | Flowing                               | Well Head  | Walinead Pressure                |  | Wellhead Pressure                   |                |  |  | d Produced<br>Barrels)                       |  |
|   |  | Prover Pressure |  |                                      | Temperature<br>t                      | Temperature<br>t                                 | $(P_w)$ or $(P_t)$ or $(P_c)$    |  | $(P_u) \propto (P_1) \propto (P_c)$ |                | (Hours)  | (6                                     |  |  |
|   |  | 88)             | psig (Pm)  | Inches H <sub>2</sub> 0              | · · · · · · · · · · · · · · · · · · · | <u> </u>   | paig pala                        |  | psig psia                           |                |  |  |  |  |
| Shut-In   |  |                 |  |                                      |                                       | 1  | 140                              | 154.4  | 150                                 | 164.4          | 24   | Ĺ                                      |  |  |
|   | <del>                                     </del> |                 |  | <del></del>                          | <del></del>                           | <del>                                     </del> | +                                | <del>                                     </del> | - <del> </del> -                    |                | <del>                                     </del> |  |  |  |
| Flow  |  |                 | _  |                                      |                                       |  |                                  | <u> </u>   |                                     |                | <u> </u>   | ــــــــــــــــــــــــــــــــــــــ |  |  |
|   |  |                 |  |                                      |                                       | FLOW STE   | REAM ATT                         | RIBUTES  |                                     |                | <del></del>                                      |  | 1  |  |
| <del></del>   |  |                 | Circle one: Press  |                                      |                                       |  | Flowing                          |  | viation                             | Metered Flo    | w GOR  |  | Flowing<br>Fluid                             |  |
| Plate<br>Coeffictient   |  |                 | Vieter or  | Extension                            | Press Gra                             |  | tor Temperature                  |  | actor                               | R              | (Cubic Fe  | (Cubic Feet/                           |  |  |
| (F <sub>b</sub> ) (F <sub>c</sub> )                             |  | Prov            | er Pressure  | √ P_xh                               | √ P <sub>xh</sub> F                   |  | I Sector                         |  | F <sub>pv</sub>                     | (Mcfd)         | Barrel   | ,                                      | G,   |  |
| Mcfd  |  |                 | psla   |                                      |                                       |  |                                  |  |                                     |                |  |  | <u> </u>                                     |  |
|   |  |                 |  |                                      |                                       | 1  |                                  |  |                                     |                |  |  | <u>                                     </u> |  |
| <u></u>   |  | <u> </u>        |  | <u> </u>                             | (OREN E)                              | OW) (DELI\                                       | /FRABILIT                        | Y) CALCU   | LATIONS                             |                | <i>t</i> ₽ '                                     | $)^2 = 0.2$                            | 207  |  |
|   |  |                 |  |                                      | •                                     |  |                                  |  | + 14.4 = _                          | :              | \'.<br>(P.                                       |  |  |  |
| (P <sub>o</sub> ) <sup>2</sup> =                                |  | <u>-:</u>       | (P_)2 =  |                                      | Pa=                                   |  | <del></del>                      |  |                                     |                | 1  | Т                                      |  |  |
| (0.12.40.12   |  | ٫ ا             | (P <sub>a</sub> ) <sup>2</sup> - (P <sub>a</sub> ) <sup>2</sup> 1. P <sub>a</sub> <sup>2</sup> - P <sub>a</sub> <sup>2</sup> |                                      | 2: LOG or                             |  | Backpressure Curr<br>Slope = "n" |  | n x ŁOG                             |                |  |  | Open Flow<br>Deliverability                  |  |
| (P <sub>e</sub> ) <sup>2</sup> · (P <sub>e</sub> ) <sup>2</sup> |  | , (F            | 'a' 'w'  |                                      | tomula<br>1, or 2.                    |  | or                               |  | " x tod                             |                | Antilog  |  | R x Antilog                                  |  |
| (P <sub>a</sub> ) <sup>2</sup> - (P <sub>a</sub> ) <sup>2</sup> |  |                 | 2, P, 2-P, 2   |                                      | end divide   p 2 - p 2                |  | Assigned<br>Standard Slope       |  | .                                   |                |  |  | (Mcfd)                                       |  |
|   |  | <b> </b>        |  | divided by: $P_a^2 - P_a$            | ·                                     |  |                                  |  |                                     |                |  | 7                                      |  |  |
| ļ   |  | ļ               | 1  |                                      |                                       |  | _                                |  |                                     |                | <del> </del>                                     | +-                                     |  |  |
|   |  | 1               |  |                                      |                                       |  | ]                                |  |                                     |                |  |  |  |  |
|   |  | 1,              | 1  |                                      | <del></del>                           |  |                                  | - Lille -  | <del></del>                         |                | Mcfd @ 14.65 p                                   | sia                                    |  |  |
| Open Fl   |  |                 |  | Mcfd Ø 14                            |                                       |  | Deliven                          |  |                                     |                |  |  |  |  |
|   |  |                 | d authority (  | on hehalf of the                     | Company.                              | states that                                      | he is duly                       | authorized                                       | to make                             | the above rep  | oort and that he h                               | ias knoi                               | wledge of                                    |  |
| ine   | e under  | signe           | authorny, v  | ),, 00,10 o. u                       | ,                                     | _  |                                  | 157  | dan at                              | Dece           | MBER   |  | 20 //  |  |
| the facts   | stated   | there           | in, and that s   | said report is tru                   | e and corre                           | ct. Execute                                      | d this the _                     | <del></del> -                                    | _ day of _                          | 1 1000         | 1  |  | ··   |  |
|   |  |                 |  |                                      |                                       |  |                                  |  | Λ                                   |                | 1  |  |  |  |
|   |  |                 | 1484   | At and                               |                                       |  |                                  | <del></del>                                      |                                     | F              | и Ортприлу                                       |  |  |  |
|   |  |                 | Witness  | ų ∎uy)                               |                                       |  |                                  |  |                                     |                |  | RE                                     | CENER  |  |
|   |  |                 | For Corr   | mission                              |                                       |  |                                  |  |                                     | G              | hecked by  |  |  |  |
|   |  | •               |  |                                      |                                       |  |                                  |  |                                     |                |  | DFC                                    | 1 9 20                                       |  |
|   |  |                 |  |                                      |                                       |  |                                  |  |                                     |                |  |  | , 1 3 ZU                                     |  |

KCC WICHITA

| i declare under penalty of perjury under the laws of the state of Kansas that I am authorized to request exempt status under Rule K.A.R. 82-3-304 on behalf of the operator <u>EAGLE CLEEK COLORATION</u> and that the foregoing pressure information and statements contained on this application form are true and correct to the best of my knowledge and belief based upon available production summaries and lease records of equipment installation and/or upon type of completion or upon use being made of the gas well herein named.  I hereby request a one-year exemption from open flow testing for the <u>HORAGE 3-17</u> gas well on the grounds that said well: |
|--|
| (Check one)  is a coalbed methane producer  is cycled on plunger lift due to water  is a source of natural gas for injection into an oil reservoir undergoing ER  is on vacuum at the present time; KCC approval Docket No.  Is not capable of producing at a daily rate in excess of 250 mcf/D  I further agree to supply to the best of my ability any and all supporting documents deemed by Commission staff as necessary to corroborate this claim for exemption from testing.  |
| Date:  |
| Signature: Unallust  Title: Resident   |

Instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under **OBSERVED SURFACE DATA**. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption **IS** denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.