Form CP-4 Rev. 12-15-80

## STATE OF KANSAS STATE CORPORATION COMMISSION 200 Colorado Derby Bldg. Wichita, Kansas 67202

0 Colorado Derby Bldg. ichita, Kansas 67202 \5-101-20583-00-00

## WELL PLUGGING RECORD

ake Required Affidavit	COUNTY L			SEC. 16			RGE . 2	27W E/W
•	Location a			footage f				· ·
		NE SE SI		<del></del>				<del></del>
	Lease Owner Lease Name		R. ASI			Wall 1	No. 1	
	- 1		#1 Ro	x 56, Rose				
	1			ed as Oil,				
	i			eu as oir,		DLY IX	ore): <u>7</u>	11010
	1	-		iled 11/				
					/29/81 /29/81			
	Plugging of Plugging of	_		11,				
		_		well or pr		forma	tion	
Locate Well				-	•			
correctly on above		•	•	ty of oil om the Con	9			
Section Platt.	•						ISION C	or ir s
ome of Consequentian Asso				s commence				<del></del>
ame of Conservation Age	-						D 4640	<u> </u>
roducing formation		_			.OIII	+··	U 4040	<u> </u>
how depth and thickness		i, oil and	gas IC	THECTOHS.				
IL, GAS OR WATER RECORD	S		<del></del>				Casin	g Record
	Content	From	To	Size	Put in		Pul	led Out
ormation		,						
ormation							<del></del>	
ormation				·				
Describe in detail t luid was placed and the r other plugs were used	he manner in method or m	ethods use character	ed in in	troducing	it into	the h	old. I	f cement
Describe in detail t luid was placed and the r other plugs were used ofeet for ea	he manner in method or more, state the conditions of the condition	ethods use character @ 1840' w @ 280' w @ 40' So	ed in in of same with 10 ith 40	and depth  or sx.  sx. ge with I	it into	the h	old. I	f cement
Describe in detail t luid was placed and the r other plugs were used ofeet for ea	he manner in method or man, state the character of plug set.  Set 1st plug set 2nd plug set 3rd	ethods use character @ 1840' w @ 280' w @ 40' So hole. 5 s	ed in in of same with 10 ith 40 I. Brid X. in M	and depth  or sx.  sx. ge with I	it into	the h	old. I	f cement
Describe in detail t luid was placed and the r other plugs were used ofeet for ea	he manner in method or more, state the conditions of the condition	ethods use character @ 1840' w @ 280' w @ 40' So hole. 5 s	ed in in of same with 10 ith 40 I. Bridx. in Mel.	o sx. sx. ge with IO ousehole.	it into placed,	the h	old. I	f cement
Describe in detail to a little land the	he manner in method or more than the chapture set. Set 1st plug set. Set 2nd plug set 3rd plug set 3rd plug sx. in Rat Common, 2% c	ethods use character @ 1840' w @ 280' w @ 40' So hole. 5 s	ed in in of same with 10 ith 40 I. Bridx. in Mel.	o sx. sx. ge with IO ousehole.	it into placed,	the h	old. I	f cement
Describe in detail to a little control of the contr	he manner in method or more than the chapture set. Set 1st plug set. Set 2nd plug set 3rd plug set 3rd plug sx. in Rat Common, 2% c	ethods use character @ 1840' w @ 280' w @ 40' So hole. 5 s	ed in in of same with 10 ith 40 I. Bridx. in Mel.	o sx. sx. ge with IO ousehole.	it into placed,	the h	old. I	f cement
Describe in detail to luid was placed and the rother plugs were used to feet for ea (If additional)	he manner in method or man, state the control of th	ethods use character @ 1840' w @ 280' w @ 40' So hole. 5 s. .c., 3% g n @ 11:00	with 10 ith 40 I. Brid x. in Mel. a.m.,	or sx. sx. ge with TO ousehole. 11/29/81.	of placed strike	the h	old. I	f cement
Describe in detail to fluid was placed and the prother plugs were used to feet for each feet feet for each feet feet for each feet feet feet feet feet feet feet fee	he manner in method or man, state the control of th	ethods use character @ 1840' w @ 280' w @ 40' So hole. 5 s. .c., 3% g n @ 11:00	with 10 ith 40 I. Brid x. in Mel. a.m.,	or sx. sx. ge with TO ousehole. 11/29/81.	of placed strike	the h	old. I	f cement
fluid was placed and the prother plugs were used tofeet for ea	he manner in method or man, state the control of th	ethods use character @ 1840' w @ 280' w @ 40' So hole. 5 s. .c., 3% g n @ 11:00	with 10 ith 40 I. Brid x. in Mel. a.m.,	or sx. sx. ge with TO ousehole. 11/29/81.	of placed strike	the h	old. I	f cement
Describe in detail to deta	he manner in method or man, state the och plug set.  Set 1st plug set.  Set 2nd plug set 2nd plug set 3rd plug set.  The set 3rd plug set 2nd plug set 3rd plug set.  The set 3rd plug set 2nd plug set 3rd plug set 2nd plug set 3rd plug set	ethods use character  @ 1840' @ 280' w @ 40' So hole. 5 s .c., 3% g n @ 11:00  n is neces rombie D  Sedgw (employ ly sworn on	with 10 ith 40 i	or says: The log of	this showner or	neet)	ator) o	of the
Describe in detail to deta	he manner in method or man, state the och plug set.  Set 1st plug set.  Set 2nd plug set 2nd plug set 3rd plug set.  The set 3rd plug set 2nd plug set 3rd plug set.  The set 3rd plug set 2nd plug set 3rd plug set 2nd plug set 3rd plug set	ethods use character  @ 1840' @ 280' w @ 40' So hole. 5 s .c., 3% g n @ 11:00  n is neces rombie D  Sedgw (employ ly sworn on	with 10 ith 40 i	or says: The log of	this shows the above	neet)	ator) c	of the well as
Describe in detail to deta	he manner in method or method or method or method or method or method set.  Set 1st plug set.  Set 2nd plug set 3rd plug s	ethods use character  @ 1840' w @ 280' w @ 40' So hole. 5 s .c., 3% g n @ 11:00  sedgw (employ ly sworn containe correct.	with 10 ith 40 i	se BACK of says: The log of p me God.	this shows the above	neet)	ator) of wledge cribed ichits	of the well as
Describe in detail to fluid was placed and the prother plugs were used to feet for each feet feet feet feet feet feet feet fee	he manner in method or method or method or method or method or method set.  Set 1st plug set.  Set 2nd plug set 3rd plug s	ethods use character  @ 1840' w @ 280' w @ 40' So hole. 5 s .c., 3% g n @ 11:00  sedgw (employ ly sworn containe correct.	with 10 ith 40 i	se BACK of says: The log of p me God.	this showner or the above the above (A)	neet)	ator) of wledge cribed ichits	of the well as

15-101-20583-00-00

WELL LOG

# 1 EITEL 150' OF N/2 SW SW SEC 16-17S-27W Lane County, KS

NAME OF OPERATOR: Mull Drilling Company, Inc.

P.O. Box 2758 Wichita, KS 67201

DATE COMPLETED: January 30, 1982

	TO	FROM
Sand	1024	0
Sand and Shale	1400	1024
Shale	1740	1400
Sand and Shale	2360	1740
Shale and Lime	2900	2360
Sand and Shale	3136	2900
Shale and Lime	4260	3136
Lime	4328	4260
Lime and Shale	4409	4328
Lime	4508	4409
Lime and Shale	4610	4508
T.D.		4610

STATE OF KANSAS

COUNTY OF BARTON ss

George E. Miller, Jr., President of Blue Goose Drilling Company, Inc. being first duly sworn on oath says: That I have knowledge of the facts, statements and matters herein contained and the log of the above described well as filed and that the same are true and correct.

George E. Miller, Jr.

Subscribed and sworn before me this 2nd Day of February 1982.

HELEN C. STANDLEY
Barton County, Kansas
My Appt. Exp. 12-8-83

Helen C. Standley, Notary Public

My Commission Expires: 12-8-83

RECEIVED
FEB - 5 1982

CONSERVATION DIVISION
Wichita. Kansas