

1 060806

273 R

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 101-21,282-00-00

NW NW SW, SEC. 17, T 16 S, R 29 W/EX

2310 feet from S section line

4950 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5131

Lease Name Magie Well # 2

Operator: Thunderbird Drilling, Inc.

County Lane 146.74

Name & Address P. O. Box 18407

Well Total Depth 4515 Mississippi feet

Wichita, KS 67218

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 337

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Thunderbird Drilling, Inc. License Number 5131

Address P. O. Box 18407, Wichita, KS 67218

Company to plug at: Hour: 10:00 pm Day: 14 Month: February Year: 19 86

Plugging proposal received from Ed Cook

(company name) Thunderbird (phone) 316-685-1441

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2169' Elevation 2774

1st plug at 4350' with 50 sx cement

2nd plug at the base of the Anhydrite with 50 sx cement

3rd plug at the base of the Cheyenne with 100 sx cement

4th plug 30' below the base of the surface pipe with 50 sx cement  
solid bridge

5th plug hulls - plug at 40' -- cement to surface with 10 sx cement

7th plug to circulate rat hole with 10 sx cement

Plugging Proposal Received by Paul A. Luthi  
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 12:30 am Day: 15 Month: February Year: 19 86

ACTUAL PLUGGING REPORT 1st plug at 4500' with 50 sx cement, 2nd plug at 2175' with 50  
sx cement, 3rd plug at 1320' with 100 sx cement, 4th plug at 370' with 50 sx cement,

5th & 6th plugs - solid bridge - hulls - plug at 40' -- cement to surface with 10 sx

cement, 7th plug to circulate rat hole with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Allied.

(If additional description is necessary, use BACK of this form.)

INVOICED (did not) observe this plugging.

DATE FEB 27 1986

RECEIVED signed Paul A. Luthi  
STATE CORPORATION COMMISSION (TECHNICIAN)

INV. NO. 12721

FEB 24 1986  
02-24-1984  
CONSERVATION DIVISION

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date 2 8 86 month day year

API Number 15- 101-21282-09-00 NW NW SW Sec. 17 Twp. 16 S, Rg. 29 East 2310 Ft. from South Line of Section 4950 Ft. from East Line of Section

OPERATOR: License # 5131 Name Thunderbird Drilling, Inc. Address P.O. Box 18407 City/State/Zip Wichita, Kansas 67218 Contact Person Burke Krueger Phone (316) 685-1441

Nearest lease or unit boundary line 330 feet County Lane

CONTRACTOR: License # 5131 Name Thunderbird Drilling, Inc. City/State Wichita, Ks 67218

Lease Name MAGIE Well # 2 Ground surface elevation 2774 feet MSL

Well Drilled For: Well Class: Type Equipment: X Oil SWD Infield X Mud Rotary Gas Inj X Pool Ext Air Rotary OWWO Expl Wildcat Cable

Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no Surface pipe by Alternate: 1 2 X Depth to bottom of fresh water 200 Depth to bottom of usable water 1100 Surface pipe planned to be set 320 Projected Total Depth 400 Formation Mississippian

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. cementing will be done immediately upon setting production casing. Date 1-27-86 Signature of Operator or Agent Edward De Jesus Title Land Mgr

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 200 feet per All This Authorization Expires 7-28-86 Approved By 1-28-86 2-3-86 set 8 1/8 - 320

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 4350 feet depth with 50 sxs of 60-40 pozmix 6 7/8 gpd 2nd plug @ 2125 feet depth with 50 sxs of 3rd plug @ 350 feet depth with 50 sxs of 4th plug @ 40 feet depth with 10 sxs of 5th plug @ feet depth with sxs of (2) Rathole with 10 sxs (b) Mousehole with

PUSHER Ed. Cook TD 4515 FORMATION MLSS SURFACE PIPE 8 7/8 @ 337 ANHYDRITE 2/69 ELEVATION 2774 STARTING TIME & DATE 2-15-86 COMPLETION TIME & DATE 12:30 AM 1st PLUG @ 4500 FT. W/ 50 SX 2nd PLUG @ 2175 FT. W/ 50 SX 3rd PLUG @ 1320 FT. W/ 100 SX 4th PLUG @ 370 FT. W/ 50 SX RAT HOLE CIRCULATED W/ 10 SX MOUSE HOLE CIRCULATED W/ SX WATER WELL PLUGGED W/ CEMENT COMPANY GYP/POZ 6 7/8 gpd. TECHNICIAN ALUED.

RECEIVED STATE CORPORATION COMMISSION FEB 24 1986 02-24-1984 CONSERVATION DIVISION Wichita, Kansas