1 (0/1024	API NUMBER 15- 10	1-20,754-00-00
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 20C COLORADO DERBY BUILDING			, יד <u>. 17</u> s, R <u>27 w/s</u>
			feet from S section line
WICHITA, KANSAS			
TECHNICIAN'S PLUG			feet from E section line
Operator License	5992	<u> </u>	Mell / 1
M !	011 Company	CountyLane	7500
Address 5660 S.	Syracuse Circle, Ste. 1200	Well Total Depth_	4599 feet
Englewo	ood, CO 80111	Conductor Pipe: S	lzefeet
		Surface Casing: S	1ze 8 5/8 fact 402
Abandoned OII Wei	iX Gas Well	Input Well	SWD WellD&A
Other well as her	einafter indicated		
	or Plains Inc.		
	346, Ness City, KS 67560		
Severe to elucia	st: Hour:9:15 a.m. Day:	7 Month:	2 Year: 19 92
•	I received from Max Parsons		4-1 913-798-3995
(company name)	Plains Inc.	58' Parfs at 4468-4	4553'
lst plug pump 300 lbs. hulls and 200 lbs. hulls in first part of 100 sx ATL cement displaced			
	100, 110110 0110		
to 1400',			A MET
2nd plug perforate at 1350', pump 50 sx cement followed by 50 sx ATL cement,			
3rd plug pump 100) sx cement down backside.		
Plugging Proposal Received by Dan Goodrow			
•		. v .	(TECHNICIAN)
	ons attended by Agent?: Al	• •	
Operations Compt	eted: Hour: 11:30 a.m Day:	7 Honth:	2 Year: 19 94
	REPORT 1st plug pumped 300 lt	os. hulls and 200 los	, nuits in tirst part of
	t displaced to 1400',	(10/10 7)	# 3) fallowed by 50 gy
2nd plug perfora	ted at 1350° , pumped 50 sx ce	ement (60/40 Pozmix 6	Mark Bel) tollowed by 30 sx
ATL cement. Max	imum pressure 1000 psi and sl	nut in 900 psi.	**************************************
3rd plug pumped	100 sx 60/40 Pozmix 6% gel de	own backside. Maximu	m pressure 800 psi and shut
in 700 psi.			
Remarks: Used A	TL & 60/40 Pozmix 6% gel by	Allied. No casing re	ecovery.
(11	additional description is	necessary, use BACK	of this form.)
! (did / stannant observe this plugging.			

Signed Sim Soften