

1 020045

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 101-21,354 -00-00

C NE, SEC. 7, T 17 S, R 27 W/E

3960 feet from S section line

1320 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5181

Lease Name Hanks "R" Well # 1

Operator: Slawson, Donald C.

County Lane 150.48

Name &

Address 200 Douglas Building

Well Total Depth 4630 feet

Wichita, KS 67202

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 240

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Slawson Drilling Company License Number 5657

Address 200 Douglas Bldg, 104 S. Broadway, Wichita, KS 67202

Company to plug at: Hour: 11 p.m. Day: 30 Month: 12 Year: 19 86

Plugging proposal received from Bob Rowe

(company name) Slawson Drilling Company (phone) 316-263-3201

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2130'

1st plug at Base Anhydrite with 50 sx cement, 2nd plug at 1300' with 75 sx cement,

3rd plug at 280' with 50 sx cement, 4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Richard Lacey (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 4:15 a.m. Day: 31 Month: 12 Year: 19 86

ACTUAL PLUGGING REPORT 1st plug at 2130' with 50 sx cement,

2nd plug at 1300' with 75 sx cement,

3rd plug at 280' with 50 sx cement,

4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 10 sx cement,

6th plug to circulate mousehole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by B.J. Titan.

(if additional description is necessary, use BACK of this form.)

INVOICED (if not observe this plugging.)

DATE 1-5-87

Signed [Signature] (TECHNICIAN)

INV. NO. 15766

12-31

STATE CORPORATION COMMISSION

JAN 2 1987

CONSERVATION DIVISION
Wichita, Kansas

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date December 18 1986
month day year 3/1

API Number 15- 101-21,354-00-00

OPERATOR: License # 5181
Name .. SLAWSON, DONALD. C.
Address 200 Douglas Building
City/State/Zip .. Wichita, Kansas. 67202
Contact Person .. Bill Horigan
Phone (316) 263-3201

..... C. NE Sec. 7 Twp. 17 S, Rg. 27 X West
..... 3960' Ft. from South Line of Section
..... 1320' Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5657
Name .. Slawson Drlg. Co.
City/State .. Wichita, Kansas

Nearest lease or unit boundary line .. 1320' feet
County .. Lane

Well Drilled For: Well Class: Type Equipment:
X Oil SWD Infield X Mud Rotary
Gas Inj Pool Ext Air Rotary
OWWO Expl X Wildcat Cable

Lease Name .. HANKS 'B' Well # 1
Ground surface elevation .. 2696' GR. (Est.) feet MSL
Domestic well within 330 feet: yes no
Municipal well within one mile: yes no

If OWWO: old well info as follows:

Operator
Well Name
Comp Date Old Total Depth

Depth to bottom of fresh water 140'
Depth to bottom of usable water 1100' / 1300'
Surface pipe by Alternate: 1 2 X
Surface pipe planned to be set 240'
Conductor pipe required
Projected Total Depth 4700' feet
Formation Mississippian

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Western Kansas
Date 12/17/86 Signature of Operator or Agent Robert B Jenkins Title District Geologist

For KCC Use:
Conductor Pipe Required feet; Minimum Surface Pipe Required 200 feet per Alt. 40
This Authorization Expires 6-17-87 Approved By 12-17-86

set 240 of 85/8 on 12-19-86

Handwritten initials and signatures: RCH/KCC, [Signature]

..... C. NE Sec. 7 Twp. 17 S, Rg. 27 X West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 2130' Anhydrite feet depth with 50 sxs of 60/40 Poz. w/6% Gel
2nd plug @ 1150' 1300 feet depth with 60 75 sxs of 60/40 Poz. w/6% Gel
3rd plug @ 260' 280 feet depth with 50 sxs of 60/40 Poz. w/6% Gel
4th plug @ 40' feet depth with 10 sxs of 60/40 Poz. w/6% Gel
5th plug @ feet depth with sxs of
(2) Rathole with 10 15 sxs (b) Mousehole with sxs

Table with columns: PUSHER (Bob Rowe), TD (4630), SURFACE PIPE (8 7/8 @ 240), ANHYDRITE (2130 ELEVATION), STARTING TIME & DATE (11 PM 12/30), COMPLETION TIME & DATE (4:15 AM 12-31-86), 1st PLUG @ (2130 FT. W/ 50 SX), 2nd PLUG @ (1300 FT. W/ 75 SX), 3rd PLUG @ (280 FT. W/ 50 SX), 4th PLUG @ (40 FT. W/ 10 SX), RAT HOLE CIRCULATED W/ (10 SX), MOUSE HOLE CIRCULATED W/ (15 SX), WATER WELL PLUGGED W/ (SX), CEMENT COMPANY (BJS TITAN), TECHNICIAN

STATE CORPORATION COMMISSION

IAN 2 1987

CONSERVATION DIVISION
Wichita, Kansas