

1120810

8-2

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-135-23,764-00-00
NE SW SE, SEC. 19, T 16 S, R 21 W/EX

TECHNICIAN'S PLUGGING REPORT

Operator License # 31231
Operator: Hyde-Marrs, Inc. &
Name: Rains & Williamson Oil Co.
Address: 155 N. Market, Ste. 710
Wichita, KS 67202

990 feet from S section line
1650 feet from E section line
Lease Name Cambron Well # 1
County Ness 140.72
Well Total Depth 4330 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 269

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X
Other well as hereinafter indicated _____

Plugging Contractor Mallard J.V. Inc. License Number 4958
Address P.O. Box 905, McPherson, KS 67460

Company to plug at: Hour: 8:30 p.m. Day: 2 Month: 8 Year: 19 93

Plugging proposal received from Wanda
(company name) Mallard J.V. Inc. (phone) 316-241-4640

work: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1617-50'
1st plug at 1650' with 50 sx cement, 2nd plug at 810' with 50 sx cement,
3rd plug at 400' with 50 sx cement, 4th plug at 270' with 50 sx cement,
5th plug at 40' with 10 sx cement, 6th plug to circulate rathole with 15 sx cement,
7th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Duane Rankin (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 10 p.m. Day: 2 Month: 8 Year: 19 93

ACTUAL PLUGGING REPORT 1st plug at 1650' with 50 sx cement,
2nd plug at 810' with 50 sx cement,
3rd plug at 400' with 50 sx cement,
4th plug at 270' with 50 sx cement,
5th plug at 40' with 10 sx cement, 6th plug to circulate rathole with 15 sx cement,
7th plug to circulate mousehole with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel 1/2# floseal by Halliburton.
(if additional description is necessary, use BACK of this form.)

STATE CORPORATION COMMISSION
08-11-1993
AUG 11 1993

did not observe this plugging.
AUG 18 1993

Signed Duane Rankin (TECHNICIAN)

DATE 38379
REV. NO.

EFFECTIVE DATE: 7-21-93

State of Kansas

NOTICE OF INTENTION TO DRILL

135-23,764-00-00

FORM MUST BE TYPED

FORM MUST BE SIGNED

ALL BLANKS MUST BE FILLED

WELL NO. 167 Yes No

Must be approved by the K.C.C. five (5) days prior to commencing well

Expected Spud Date 8 month 1 day 93 year

Spot NE SW SE Sec 19 Twp 16 S Rg 21 East

OPERATOR: License # 31231 Name: Hyde-Marrs, Inc. & Rains & Williamson Oil Co. Address: 155 N. Market, Suite 710, Wichita, Kansas 67202. Contact Person: Thomas C. Hyde. Phone: 316-262-8339

990 feet from South / WAXX line of Section 1,650 feet from East / WAXX line of Section COIS SECTION X REGULAR IRREGULAR

CONTRACTOR: License # 4958 Name: Mallard J.V. Inc.

(NOTE: Locate well on the Section Plat on Reverse Side) County: Ness. Lease Name: Cambron Well #: 1. Field Name: Unnamed. Is this a Prorated/Spaced Field? yes X no. Target Formation(s): Cherokee Sand. Nearest lease or unit boundary: 990. Ground Surface Elevation: 2310 feet MSL. Water well within one-quarter mile: yes X no. Public water supply well within one mile: yes X no. Depth to bottom of fresh water: 100 feet. Depth to bottom of usable water: 900 feet. Surface Pipe by Alternate: 1 X 2. Length of Surface Pipe Planned to be set: 250. Length of Conductor pipe required: Projected Total Depth: 4,300. Formation at Total Depth: Mississippian. Water Source for Drilling Operations: well X farm pond other

Well Drilled For: Well Class: Type Equipment: X Oil ... Enh Rec ... Infield X Mud Rotary Gas ... Storage ... Pool Ext. ... Air Rotary GWD ... Disposal X Wildcat ... Cable Seismic: # of Holes Other

If GWD: old well information as follows: Operator: Well Name: Comp. Date: Old Total Depth

Directional, Deviated or Horizontal wellbore? yes X no. If yes, true vertical depth: Bottom Hole Location:

DWR Permit #: Will Cores Be Taken? yes X no. If yes, proposed zone: 200' Alt. II Req.

Exp. 1/16/94

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-181, et. seq. It is agreed that the following minimum requirements will be met:

Pusher W.R.N.D.H. SPUD DATE 7-27-1993 INIT. G.B. LENGTH SURFACE PLANNED 250' RESERVE PIT STATUS- REMOVE FLUID LINED after salt sect. bbls. when done bbls. RATHOLED AHEAD? Y N SIZE HOLE SURFACE PIPE 8 1/2" @ 265' CONDUCTOR ANHYDRITE T-1617 B-1650 ELEVATION Q. reg 1825 TD 4330 FORMATION BRAN PIPE @ DV TOOL ALT II DONE SX Y N Arbuckle Plug @ Ft. W/ SX Hug./Council @ Ft. W/ SX Anhydrite Base @ 1650 Ft. W/ 50 SX 1/2 Base Anyh. @ 810 Ft. W/ 50 SX 1/2, 1/2 Plug @ 400 Ft. W/ 50 SX Bottom Surface @ 220 Ft. W/ 50 SX 40' Plug @ 40 Ft. W/ 10 SX RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ 10 SX WATER WELL SX (Irr. Well Fond Hauling) TECHNICIAN D.R. DATE TYPE OF CEMENT 60-40-670 to FS STARTING TIME 8:30 (AM/PM) DATE AUG 1 1993 COMPLETION TIME 08:10 (AM/PM) DATE 8-2 1993 CEMENT COMPANY Hall