

To: 1 060174 8-7  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 135-23,767-00-00  
NE SE SE, SEC. 6, T. 17 S, R. 21 W/E

TECHNICIAN'S PLUGGING REPORT

Operator License # 6668  
Operator: Theodore I. Leben  
Name: Theodore I. Leben  
Address: 105 S. Broadway, Ste. 640  
Wichita, KS 67202

990 feet from S section line  
330 feet from E section line  
Lease Name Ruby Well # 2-6  
County Ness  
Well Total Depth 4312 140.14 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 315

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Duke Drilling Company, Inc. License Number 5929

Address 310 W. Central, Wichita, KS 67202

Company to plug at: Hour: 1:15 p.m. Day: 7 Month: 8 Year: 1993

Plugging proposal received from Rich Wheeler

(company name) Duke Drilling Company, Inc. (phone) 316-267-1331

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1535-68'

1st plug at 1600' with 50 sx cement,

2nd plug at 950' with 80 sx cement, 3rd plug at 350' with 50 sx cement,

4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Case Morris  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 3:30 p.m. Day: 7 Month: 8 Year: 1993

ACTUAL PLUGGING REPORT 1st plug at 1600' with 50 sx cement,

2nd plug at 950' with 80 sx cement,

3rd plug at 350' with 50 sx cement,

4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Allied.

(if additional description is necessary, use BACK of this form.)

did not observe this plugging.

AUG 11 1993

08-11-1993

DATE AUG 11 1993

Signed Case Morris  
(TECHNICIAN)

38381  
8-7

OCT 06 1993

EFFECTIVE DATE: 8-4-93

DISTRICT #

SEAT Yes No

State of Kansas  
NOTICE OF INTENTION TO DRILL

15-135-23,767-0008

FORM MUST BE TYPED  
FORM MUST BE SIGNED  
ALL BLANKS MUST BE FILLED

Must be approved by the K.C.C. five (5) days prior to commencing well

Expected Spud Date 08 02 93  
month day year

Spot NE SE SE Sec 6 Twp 17 S Rg 21 East West

OPERATOR: License # 6668  
Name: THEODORE I. LEBEN  
Address: 105 S. BROADWAY, SUITE 640  
City/State/Zip: WICHITA, KS 67202  
Contact Person: GERALD W. ZORGER  
Phone: 316-264-2375

990 feet from South North line of Section  
330 feet from East West line of Section  
IS SECTION X REGULAR IRREGULAR

CONTRACTOR: License # 5929  
Name: DUKE DRILLING COMPANY, INC.

County: NESS  
Lease Name: RUBY Well #: 2-6  
Field Name: RUBY

Well Drilled For: Well Class: Type Equipment:  
X Oil ... Enh Rec ... Infield X Mud Rotary  
Gas ... Storage X Pool Ext. ... Air Rotary  
GWD ... Disposal ... Wildcat ... Cable  
Seismic: # of Holes Other

Is this a Prorated/Spaced Field? yes X no  
Target Formation(s): MISSISSIPPIAN  
Nearest lease or unit boundary: 330'  
Ground Surface Elevation: 2248' feet MSL

If GWD: old well information as follows:  
Operator:  
Well Name:  
Comp. Date: Old Total Depth

Water well within one-quarter mile: yes X no  
Public water supply well within one mile: yes X no  
Depth to bottom of fresh water: 120' 430'  
Depth to bottom of usable water: 850'

Directional, Deviated or Horizontal wellbore? yes no  
If yes, true vertical depth:  
Bottom Hole Location:

Surface Pipe by Alternate: 1 X 2  
Length of Surface Pipe Planned to be set: 320'  
Length of Conductor pipe required: N/A  
Projected Total Depth: 4300'  
Formation at Total Depth: MISSISSIPPIAN

Water Source for Drilling Operations:  
... well X farm pond other

DWR Permit #:  
Will Cores Be Taken? yes X no  
If yes, proposed zone:

AFFIDAVIT

250' Alt. II Req.

Exp. 1/30/94

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101. at

Pusher: Rick Wheeler  
SPUD DATE: 8-2-93 INIT. CIL  
LENGTH SURFACE PLANNED: 315' 3 5/8"  
RESERVE PIT STATUS- REMOVE FLUID LINED  
after salt sect. bbls. when done bbls.  
RATHOLE AHEAD? Y N SIZE HOLE  
SURFACE PIPE 5 5/8" @ 315' CONDUCTOR  
ANHYDRITE T-1526 B-1548 ELEVATION  
TD 4312 FORMATION  
RAN PIPE @ DV TOOL ALT II DONE  
SX SX Y N  
Arbuckle Plug @ Ft. W/ SX  
Hug./Council @ Ft. W/ SX  
Anhydrite Base @ 1600' Ft. W/ 50 SX  
1/2 Base Anyh. @ 950 Ft. W/ 80 SX  
1/2, 1/2 Plug @ Ft. W/ SX  
Bottom Surface @ 350 Ft. W/ 50 SX  
40' Plug @ 40 Ft. W/ 10 SX  
RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ SX  
WATER WELL SX (Irr. Well Pond Hauling)  
TECHNICIAN CM DATE 8-6-93  
TYPE OF CEMENTS 60/40 6%  
STARTING TIME 8:12 (AM/PM) DATE 8-7-93  
COMPLETION TIME 3:20 (AM/PM) DATE 8-7-93  
CEMENT COMPANY Allied  
8-11-1993