

8 062061

1505105566.0001 19

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- D-1582
NE SEC. 31 T 11 S, R 17
4950 feet from S section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 6509
Operator: Cla Mar Oil Co.
Name: Box 1107
Address: Hays, Ks. 67601

660 feet from E section line
Lease Name C. M. Hadley Well # B-4
County Ellis 116.55
Well Total Depth 3586 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 1006

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ x D&A _____

Other well as hereinafter indicated _____

Plugging Contractor Rapid Well Service License Number 7049
Address Box 208 Russell, Ks. 67665

Company to plug at: Hour: 10:00 AM Day: 3 Month: Jan Year: 19 90

Plugging proposal received from Jim Clark
(company name) Cla Mar Oil Co. (phone) 913-625-3863

were: Order 300 sks common cement 300 sks 65/35 poz 8% gel 3 sks celoflake.

RECEIVED
STATE CORPORATION COMMISSION

JAN 17 1990

CONSERVATION DIVISION

Wichita, Kansas

Plugging Proposal Received by Don Butcher/Bill Bryson
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part _____ None _____

Operations Completed: Hour: 11:30AM on 4th Day: 3 & 4 Month: Jan Year: 19 90

ACTUAL PLUGGING REPORT 8 5/8" set at 1006' w/325 sks. 5 1/2" set at 3523' w/250 sks.

Open hole 63'. Ran 2" tubing to 1175' w/packer set at 750' and pumped 200 sks common.

Pulled tubing and packer and perf at 690'; 2 shots. Ran tubing to 1100' and pumped 300 sks of 65/35 poz 8% gel and 3 sks celoflake, followed w/100 sks common w/400 psi.

January 4, 1990: Tubing stacked out at 460', hard cement at 450' and soft cement from 410' to 450'. Ran perf gun to 370', pulled gun to 365' and perf two shots. Pumped 40 sks cement down casing w/400 psi. Cmt circ to surface outside of 5 1/2" w/33 sks cmt. Shut

in 5 1/2" casing w/400 psi. Pumped in 4 1/2" casing 1/3 of a sk cement w/600 psi for 5 min.

Shut in at 600 psi. Job completed. Cedar Hills and Dakota cemented off and salt most

Remarks: likely has cement. Max psi 600#. Shut in at 600 psi.

(If additional description is necessary, use BACK of this form)

I (did / did not) observe this plugging.
Total sks cement used 640. Maximum pump pressure inside of casing & pressure needed for circulation were both 400 psi. Backside of 5 1/2" casing pressured to 600 psi.

INVOICED
Signed Don Butcher DATE JAN 26 1990
Don Butcher (TECHNICIAN)
Gib Scheck INV. NO. 27184
FORM CP-2/3 Rev. 01-84