

1060366

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 135-22,688 -00-00

E/2 NW NW, SEC. 23 ; T 17 S, R 21 W/4  
4620 feet from N SE Corner of  
4290 feet from W SE Corner of  
WXX section line  
WXX section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 8572

Lease Name Ryan Well # 1

Operator: Reach Oil Corp., dba The Reach Group  
Name & Address: 3751 East Douglas  
Wichita, KS 67218

County Ness  
Well Total Depth 4190 136.18 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 380

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SMD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Murfin Drilling Co. License Number 6033

Address 250 North Water, Suite 300, Wichita, KS 67202

Company to plug at: Hour: 9:00 pm Day: 12 Month: October Year: 19 84

Plugging proposal received from Lloyd Dellett

(company name) Murfin (phone) 316-267-3241

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 1450' with 50 sx cement

2nd plug at 620' with 70 sx cement  
solid bridge

3rd plug hulls - plug at 40' -- cement to surface with 10 sx cement

5th plug to circulate rat hole with 15 sx cement.

Plugging Proposal Received by Paul A. Luthie (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 11:00 pm Day: 12 Month: October Year: 19 84

ACTUAL PLUGGING REPORT 1st plug at 1450' with 50 sx cement, 2nd plug at 620' with 70  
sx cement, 3rd & 4th plugs - solid bridge - hulls - plug at 40' -- cement to surface  
with 10 sx cement, 5th plug to circulate rat hole with 15 sx cement.

10-17-1984  
OCT 17 1984

Remarks: Used 60/40 Pozmix 2% gel 3% cc by Sun.

(If additional description is necessary, use BACK of this form.)

I (did not) observe this plugging.

Signed Paul A. Luthie (TECHNICIAN)

10-18-84

4405

NOV 19 1984