

2-15

To: 1 051130  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-135-23,040-00-01  
90' E  
NW NW SE, SEC. 6, T. 17 S, R. 22 W/EX

TECHNICIAN'S PLUGGING REPORT  
Operator License # 3536

2310 feet from S section line  
2220 feet from E section line

Operator: RAMCO Energy Corporation  
Name & Address 127 Lee Street  
P.O. Box 99  
Belpre, OH 45714

Lease Name Pfaff (OWWO) Well # 1  
County Ness 35.00

Well Total Depth 1004 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 243

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Abercrombie Drilling, Inc. License Number 5422

Address 801 Union Center, Wichita, KS 67202

Company to plug at: Hour: 2 p.m. Day: 15 Month: 2 Year: 19 89

Plugging proposal received from Wilmer Drilling

(company name) Abercrombie Drilling, Inc. (phone) 316-262-1841

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2359'GL

1st plug at 990' with 80 sx cement,

2nd plug at 280' with 50 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION

FEB 17 1989

Plugging Proposal Received by Richard W. Lacey (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 4:30 p.m. Day: 15 Month: 2 Year: 19 89

ACTUAL PLUGGING REPORT 1st plug at 990' with 80 sx cement,

2nd plug at 280' with 50 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.  
(if additional description is necessary, use BACK of this form.)

INVOICED  
did not observe this plugging.

DATE 2-20-89

Signed Richard W. Lacey (TECHNICIAN)

INV. NO. 23984  
2-15