TO:

D-17,113 20617 API number: 15-009-20,167-0001

| CONTROL CORPORATION CONTROL CONTROL   | AND KCC  |
|---|--|
| STATE CORPORATION COMMISSION<br>CONSERVATION DIVISION - PLUGGING            | <u>NW NE NW</u> /4 SEC. 10 , 18S, 15 W   |
| 200 COLORADO DERBY BUILDING   | 4950 feet from S section line  |
| WICHITA, KANSAS 67202   | 3630 feet from E section line  |
|   |  |
| Operator license# 6296  | Lease <u>Riedel SWD</u> well # 1   |
| Operator: Leroy Holt  | County Barton  |
| Address: P. O. Box 401  | Well total depth 3600 feet   |
|   | Conductor Pipe: inch @ feet  |
|   | Surface pipe 8 5/8 Inch @ 990 feet   |
| Aband. oil well, Gas well, In   | put well, SWD_X_, D & A  |
| Plugging contractor: Mike's Testing   | and Salvage License# 31529   |
| Address: P. O. Box 209, Chase, Kansa  | s 67524  |
| Company to plug at: Hour: AM Day  | : 31 Month: January Year: 1996   |
| Plugging proposal received from: Mike Kelso                                 |  |
| Company: Mike's Testing and Salvage phone: 316-938-2943                     |  |
| Were: Open hole from 3546' to 3600'.  | Good to 25001 and to 12 year   |
| Cement. 5 1/2" casing set at 3546'  | with 200 sx. Shoot and pull to 1750',  |
| Pump 125 sx 60/40 poz, 10% gel with 3                                       | 300# hulls. Pull to 1025' and nump   |
| 35 sx 60/40 poz, 10% gel. Pull to 35  | 50' and pump 65 sx 60/40 poz, 10% gel.   |
| Pull casing to surface and top with 2                                       |  |
|   |  |
| _   |  |
| Plugging Proposal Received by: Herb D                                       | Deines   |
| Plugging operations attended by agent                                       | ? All[XXX], Part[ ], None[ ]   |
| Completed: Hour: 1:15 PM, Day: 31, M  | onth: January , Year: 1996   |
| Actual plugging report: 5 1/2" casing                                       | shot at 2500'. Pulled to 1750' and   |
| 125 sx 60/40 poz, 10% geland 300# hul                                       | ls pumped down casing. Pulled to 1025'   |
| poz 10\$ gel pumped down casing cement                                      | wn casing. Pulled to 350' and 50 sx 60/40 circulated. Casing pulled to surface |
| and topped with 10 sx 60/40 poz, 10%  | gel.   |
|   |  |
|   |  |
| Demonistra 1994 - 7 Gament  |  |
| Remarks: Allied Cementing on location Condition of casing(in hole):GOOD X 1 |  |
| Bottom plug(in place):YES X , CALC  | Anhy. plug:YES NO Dakota plug:YES X . NO                                       |
| Plugged throughTUBING, CASING X   | Elevation: 1949GL  |
| <pre>I did(XX) / did not[ ] observe the r</pre>                             | olugging Sun (Sign)  |
| The state of the F  |  |

 $\cdot Q_{ij}$ 

Bruce D. Basye (agent)