TATE OF KANSAS TATE CORPORATION COMMISSION O Colorado Derby Bullding		GGING REC 02-3-11					
chito, Konses 67202					AME Walk		
× \	TYPE OR PRINT NOTICE: Fill out completely and return to Cons. Div. office within 30 days.				WELL NUMBER 2		
				1650 Ft. from & Section Line 990 Ft. from E Section Line			
Ritchie Exploration, Inc.			SEC. 34 THP. 16SRGE. 22 TRAME (#)				
			COUNTY	COUNTY Ness			
Wichita, KS 67202 DNE#(316) 267-4375 OPER#	2 Ntors Li c ense i	NO. 476	57		II Complet		96
practor of Well D&A				Pluggla	g Commence	d <u>2-7-</u>	96
II, Gas, D&A, SWD, Input, Wa	ater Supply We	11)		Pluggin	g Complete	d <u>2-:7-:</u>	96
o plugging proposal was appr	raved onF	ebruary	7, 19	996		· · · · · · · · · · · · · · · · · · ·	(date)
Richard	Lacv			(KC	C District	Agent's (Name).
ACO-1 filed? Yes 16							
							
				· · -			
oducing Formation	Dept			· · -	o'm	T.D. 4	
		h to Top_		Bott	o m		
ow depth and thickness of a	ll.wațer, oll	h to Top and gas f	ormati	Bott	o m	T.D. 4	
ow depth and thickness of a	ll.wațer, oli	h to Top and gas f	ormati C	Bott ons. ASING RECO	RD	7.0. <u>4</u> 03 -13-	-1994
ow depth and thickness of a	ll.wațer, oll	n to Top_ and gas f	ormati C	Bott ons. ASING RECO	omRDPulled ou	7.0. <u>4</u> 03 -13	-1994
ow depth and thickness of a	ll.wațer, oli	n to Top_ and gas f	ormati C	Bott ons. ASING RECO	RD	7.0. <u>4</u> 03 -13	-1994
ow depth and thickness of a	ll.wațer, oli	n to Top_ and gas f	ormati C	Bott ons. ASING RECO	omRDPulled ou	03 -13	-1994
ow depth and thickness of all, GAS OR WATER RECORDS ormation Content	From	n to Top_ and gas f	ormati C zo 5/8"	Bott ons. ASING RECO Put in 213	Pulled ou	7.0. 4 03 -13	-1994
ow depth and thickness of a IL, GAS OR WATER RECORDS ormation Content scribe in detail the manner aced and the method or met	From In which the hods used in 1	To Si	crmati Cze 5/8" plugge	Put in 213'	Pulled ou none	T.D. 4 03 -13	-1994
ow depth and thickness of all, GAS OR WATER RECORDS ormation Content scribe in detail the manner aced and the method or methor or used, state the characteristics.	From In which the hods used in iter of same	To Si	ormati C ze 5/8" plugge g It I	Put in 213' d, Indicat nto the ho	Pulled ou none	the mud to of test.	luld where plus ach see
creation Content scribe in detail the manner aced and the method or methor outed 50 sx. cement at aru drill pipe. Spotted	From In which the hods used in 1 ter of same 1710' thru	To Si To Si Well was ntroducin and depti drill pi	5/8" plugge g It In place	Put in 213' d, Indicate the head, from Spotted thru dril	Pulled ou none Ing where to to 80 sx. coll pipe,	the mud then for of ement at spotted	luid wher plus ach se 1030' 40 sx
cow depth and thickness of a lil, GAS OR WATER RECORDS cormation Content cormation Content cormation Content correct in detail the manner aced and the method or method are used, state the characteristic outled 50 sx. cement at a content at a content at 240 thru drill ement at 240 thru drill	From In which the hods used in 1 ter of same 1710' thru 1 40 sx. cem pipe. Spo	To Si To Si Well was ntroducin and depti drill pi	5/8" plugge g It In place	Put in 213' d, Indicate the head, from Spotted thru dril	Pulled ou none Ing where to to 80 sx. coll pipe,	the mud then for of ement at spotted	luid wher plus ach se 1030' 40 sx
scribe in detail the manner aced and the method or methor re used, state the characteristics of the country of the characteristics of the	From In which the hods used in iter of same 1710' thru it 40 sx. cem pipe. Spo	To Si To Si Well was ntroducin and depti drill pi ent at 5	5/8" plugge g it in place	Put in 213' d, Indicate the head, from Spotted thru drill cement at	Pulled ou none Ing where to 80 sx. c. 1 pipe. 40' thr	the mud then for of ement at spotted	luid wher pice ach se 1030' 40 sx
content scribe in detail the manner aced and the method or metro aced 50 sx. cement at a cotted 50 sx. cement at a country co	From In which the hods used in Iter of same 1710' thru if 40 sx. cem pipe. Spo	To Si To Si Woll was ntroducin and depti drill pi ent at 5 tted 10	5/8" plugge g It I n place	Put in 213' d, Indicat nto the ho ed, from Spotted thru dril cement at	Pulled ou none Ing where is, if cent to 80 sx. cl pipe. 40' thr	the mud to the ment or of ement at spotted u drill	1010 wher plus 1030' 40 sx pipe
content con	From In which the hods used in Iter of same 1710' thru if 40 sx. cem pipe. Spo	To Si To Si Woll was ntroducin and depti drill pi ent at 5 tted 10	5/8" plugge g It I n place	Put in 213' d, Indicat nto the ho ed, from Spotted thru dril cement at	Pulled ou none Ing where is, if cent to 80 sx. cl pipe. 40' thr	the mud to the ment or of ement at spotted u drill	1010 wher plus 1030' 40 sx pipe
scribe in detail the manner aced and the method or methor re used, state the characteristics of the country of the characteristics of the	From In which the hods used in Iter of same 1710' thru it 40 sx. cem pipe. Spo	To Si To Si No Si Well was ntroducin and depti drill pi ent at 5 tted 10 cessory, is Drill	5/8" 5/8" plugge g It I n place pe. 500' t sx. c	Put in 213' d, Indicate to the head, from Spotted thru drill cement at the lead of the l	Pulled ou none Ing where is, if cent to 80 sx. cl pipe. 40' thr	the mud to the ment or of ement at spotted u drill	1010 wher plus 1030' 40 sx pipe
content of the manner of and the method or method or method or method of the character of t	From In which the hods used in I ter of same 1710' thru 1 40 sx. cem pipe. Spo	To Si To Si No Si Well was ntroducin and depti drill pi ent at 5 tted 10 cessory, is Drill S 67201-	plugge g t h place b00' t sx. G	Put in 213' d, indicate the head, from Spotted thru drill tement at the head.	Pulled ou none Ing where to 80 sx. c. 1 pipe. 40' thrust form.)	the mud then to of the ment or of ement at spotted u drill	luid wher plus 1030' 40 sx pipe
content of the manner aced and the method or method or method or detail pipe. Spotted 50 sx. cement at a cement a cement at a cement a cement at a cement a cem	From In which the hods used in I ter of same 1710' thru it 40 sx. cem pipe. Spocription is new White & Ell. Wichita, Karpugging FEES	To Si To Si No Si Well was ntroducin and depti drill pi ent at i tted 10 cessory, is Drill S 67201- i: Rite	plugge g t h place 500' t sx. G use 3A ing.	Put in 213' d, Indicate the horse of from Spotted thru drill cement at the location of the second control of the second cement at the	Pulled ou none Ing where to 80 sx. cc. 1 pipe. 40' thrust form.) License No. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	the mud then to of the ment or of ement at spotted u drill	luid wher plus 1030' 40 sx pipe

(Address)

P. O. Box 48848 Wichita. KS 67201-8848

day of February

(Motery Public Carolyn J. Tjaden

tements, and matters heroin contained and the log of the abov

SUBSCRIBED AND SWORN TO before me this 12th

9-5-96

same are true and correct, so help me God.

CAROLYN J. TJADEN
NOTARY PUBLIC
STATE OF KANSAS
My Appl. Exp. 9-5-96