

STATE OF KANSAS  
STATE CORPORATION COMMISSION

Give All Information Completely  
Make Required Affidavit  
Mail or Deliver Report to:  
Conservation Division  
State Corporation Commission  
800 Bitting Building  
Wichita, Kansas

WELL PLUGGING RECORD

Reno County, Sec. 16 Twp. 24 Rge. 4W (E) (W)

Location as "NE/CNW/SW" or footage from lines N/2 NW/4

Lease Owner The Texas Company

Lease Name S. Collins (NCT-1) Well No. 6

Office Address 614 Bitting Building, Wichita, Kansas

Character of Well (completed as Oil, Gas or Dry Hole) Oil

Date well completed May 26 1936

Application for plugging filed February 25 1953

Application for plugging approved February 26 1953

Plugging commenced March 9 1953

Plugging completed March 10 1953

Reason for abandonment of well or producing formation

Ceased to be a commercial producer

If a producing well is abandoned, date of last production August 1952

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well Mr. Ruel Durkee

Producing formation Mississippi Chat Depth to top 3326 Bottom 3384 Total Depth of Well 3384 Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

FORMATION	CONTENT	FROM	TO	SIZE	PUT IN	PULLED OUT
				13"	512'	0
				8-5/8"	3326'	2659'

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from \_\_\_\_\_ feet to \_\_\_\_\_ feet for each plug set.

PLUGGED AS FOLLOWS:

- 3384' to 3320' - Sand
- 3320' to 3300' - 8 Sacks Cement
- 3300' to 350' - Heavy Mud
- 350' to 338' - Rock Bridge
- 338' to 295' - 5 Sacks Cement
- 295' to 18' - Heavy Mud
- 18' to bottom of cellar - 8 Sacks Cement

(If additional description is necessary, use BACK of this sheet)

Name of Plugging Contractor R & S Pipe Pulling Company

Address Box 192, Ellinwood, Kansas

STATE OF Kansas, COUNTY OF Sedgwick, ss.

M. C. Harrell (employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) M. C. Harrell

614 Bitting Building, Wichita, Kansas (Address)

SUBSCRIBED AND SWORN TO before me this 11th day of March, 1953

My commission expires September 20, 1956

24-2675-S 2-52-20M STATE CORPORATION COMMISSION

PLUGGING  
FILE SEC 16 T 24 R 42  
BOOK PAGE 81 LINE 14

RECEIVED  
MAR 12 1953  
3-12-53  
CONSERVATION DIVISION  
Wichita, Kansas

# LOG OF WELL

Form PO-214 Sheet 1 (12-50)20M

SHEET 1

OWNER The Texas Company DIVISION Oklahoma DATE MADE 6-11-36  
 DISTRICT Kansas LEASE Sam Collins WELL NO. 6  
 STATE Kansas COUNTY OR PARISH Reno TWP. \_\_\_\_\_ RANGE \_\_\_\_\_ SEC. \_\_\_\_\_  
 LOCATION OF WELL Located approximately 1320' from the East line and 330' from the South line in the N2 NW4 of Section 16-24S-4W.  
 COMMENCED RIGGING UP 5-3-36 COMMENCED DRILLING 5-7-36 COMPLETED DRILLING 5-26-36  
 DAY DRILLER \_\_\_\_\_ NIGHT DRILLER \_\_\_\_\_ CONTRACTOR Parker Drilling Co.  
 CABLE FROM \_\_\_\_\_ TO \_\_\_\_\_ ROTARY FROM 0' TO 3384' COMPANY RIG No. 6  
 TOTAL DEPTH 3384' MEASURED BY M. C. Harrell ELEVATION 1471

## CASING RECORD

SIZE	WEIGHT	PUT IN WELL		PULLED OUT		LOST IN WELL		SHOES		PACKERS			
		FEET	INS.	FEET	INS.	FEET	INS.	LENGTH	MAKE	KIND	LENGTH	SET AT	
12 1/2"	50#	512'		Cemented		W/300 sacks			T.P.				FT.
8-1/4"	32#	3326'		Cemented		W/200 sacks			T.P.				FT.
													FT.
													FT.
													FT.
													FT.
													FT.

WAS CASING CEMENTED? \_\_\_\_\_ IF SO, HOW MANY SACKS OF CEMENT USED? \_\_\_\_\_  
 LINER: STATE SIZE AND WEIGHT \_\_\_\_\_ WHERE SET \_\_\_\_\_ FT. AND INS. \_\_\_\_\_ FT. AND INS. \_\_\_\_\_  
 HOW PUT TOGETHER \_\_\_\_\_ COUPLING \_\_\_\_\_ FLUSH-JOINT \_\_\_\_\_ INSERTED \_\_\_\_\_  
 REMARKS: \_\_\_\_\_

## EQUIPMENT RECORD

TUBING				SUCKER RODS			PUMPING OUTFIT
SIZE	WEIGHT	FEET	INS.	FEET	INS.	SIZE AND KIND	DESCRIPTION, KIND, SIZE, ETC.

FLOWING, PUMPING, GASSER OR DRY pumping PRODUCTION FIRST 24 HOURS 134 PRODUCTION SETTLED \_\_\_\_\_  
 IF GAS WELL, OPEN FLOW CAPACITY \_\_\_\_\_ SHUT IN PRESSURE \_\_\_\_\_ ROCK PRESSURE \_\_\_\_\_  
 KIND OF SHOT \_\_\_\_\_ SIZE OF SHOT, QUARTS \_\_\_\_\_  
 NUMBER OF SHELLS \_\_\_\_\_ SIZE OF SHELLS \_\_\_\_\_ INCHES, DIAMETER \_\_\_\_\_  
 LENGTH OF SHELLS \_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ TOP OF SHOT \_\_\_\_\_  
 BOTTOM OF SHOT \_\_\_\_\_ ANCHOR \_\_\_\_\_ WELL BRIDGED TO \_\_\_\_\_  
 TOTAL DEPTH OF WELL \_\_\_\_\_ NUMBER OF SHOT \_\_\_\_\_ PRODUCTION BEFORE SHOT \_\_\_\_\_ BBLs. PER DAY \_\_\_\_\_  
 PRODUCTION AFTER SHOT \_\_\_\_\_ BBLs. PER DAY. SHOT FURNISHED BY \_\_\_\_\_  
 NAME OF SHOOTER \_\_\_\_\_ SHOT INSPECTED \_\_\_\_\_ BY \_\_\_\_\_ (COMPANY EMPLOYEE) \_\_\_\_\_  
 COMMENCED DRILLING DEEPER \_\_\_\_\_ COMPLETED \_\_\_\_\_ DRILLING DEEPER \_\_\_\_\_  
 TOTAL DEPTH \_\_\_\_\_ PRODUCTION FIRST 24 HOURS \_\_\_\_\_ PRODUCTION SETTLED \_\_\_\_\_  
 REMARKS: \_\_\_\_\_

## PLUGGING

FILE SEC 16 T 24 R 42  
 BOOK PAGE 81 LINE 14

NOTE: IF WELL WAS DRY, STATE UNDER REMARKS, WHEN, HOW, AND BY WHOM PLUGGED.  
 STATE UNDER REMARKS ANYTHING OF INTEREST NOT COVERED IN LOG.  
 IF THE SPACE PROVIDED FOR REMARKS IS NOT SUFFICIENT WRITE ON BOTTOM OF LAST SHEET OF LOG.

TOTAL NUMBER OF SHEETS \_\_\_\_\_

# LOG OF WELL

SHEET No. 2

District Kansas

Owner The Texas Company Farm Sam Collins

Well No. 6

FORMATION		AMOUNT	COLOR	HARD OR SOFT	DEPTH CORES TAKEN	REMARKS
Water Sand	275	275		Soft		Sey 512' of 12-1/2"
Shale & Lime Shells	425	150		Soft		
Shells	500	75		Soft		
Lime & Shale	840	340		Medium		
Broken Lime	904	64		Medium		
Water Sand	920	16		Soft		
Lime & Shale	1115	195		Medium		
Shale & Shells	1318	203		Medium		
Lime Broken	1350	32		Medium		
Lime & Shale	1505	155		Medium		
Shale & Shells	1699	194		Medium		
Shale	1867	168		Medium		
Lime & Shale	2071	204		Medium		
Shale	2194	123		Hard		
Lime	2284	90		Hard		
Lime & Shale	2385	101		Hard		
Lime	2400	15		Hard		
Shale	2475	75		Medium		
Lime	2502	27		Medium		
Sand	2532	30		Medium		
Shale & Lime	2570	38		Medium		
Lime	2636	66		Hard		
Lime & Shale	2710	74		Hard		
Lime	2960	250		Hard		
Lime & Shale	3062	102		Medium		
Lime	3114	52		Hard		
Shale	3290	176		Hard		
Chat	3384	94		Hard		
	T.D.	3384'				Set 3326' of 8-1/4" at 3339'

STATE COMMISSION  
 MAR 12 1953  
 CONSERVATION DIVISION  
 Wichita, Kansas