1 070575	8-8-88 API NUMBER 15-135-23,276-00-00
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	NW NE , SEC. 14 , T 17 S, R 24 W/K  4620 feet from S section line
TECHNICIAN'S PLUGGING REPORT	feet from E section line
Operator License # 6040	Lease Name Amstutz Well # 1
Operator: Bankoff Oil Company Name&	County Ness 147.88
Address Box 700657	Well Total Depth 4550 feet
Tulsa, OK 74170	Conductor Pipe: Size feet
	Surface Casing: Size 8 5/8 feet 262
Abandoned Oli Weil Gas Well Input Well SWD Well D&A X	
Other well as hereinafter indicated	
Plugging Contractor Abercrombie Drilling Company - License Number 5422	
Address 801 Union Center, Wichita, KS 67202	
Company to plug at: Hour: 5:45 p.m. Day: 8 Month: 8 Year:19 88	
Plugging proposal received from W.F. Dreiling	
(company name) Abercrombie Drilling Company (phone) 316-262-1841	
were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2492' Anhydrite 1789-1834'	
1st plug at 1820' with 50 sx cement, 2nd plug at 960' with 80 sx cement,	
3rd plug at 290' with 40 sx cement,	
4th plug at 40' with 10 sx cement,	
5th plug to circulate rathole with 15 sx cement.	
Plugging Proposal Received by Richard Lacey	
	(TECHNICIAN)
Plugging Operations attended by Agent?: Ali	X Part None
Operations Completed: Hour: 8 p.m. Day:	
ACTUAL PLUGGING REPORT 1st plug at 1820' with 50 sx cement DEIVED	
2nd plug at 1160' with 80 sx cement,	STATE CORPORATION COMMISSION
3rd plug at 290' with 40 sx cement,	AUG 15 1988
4th plug at 40' with 10 sx cement,	
5th plug to circulate rathole with 15 sx cem	ent. CONSERVATION DIVISION Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Allied.

(If additional description is necessary, use BACK of this form.)