

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-051-23402-0000

SW, SEC. 20, T. 11S, R. 18W

1650 FEET FROM N/S SECTION LINE

1750 FEET FROM W SECTION LINE

TECHNICIAN'S PLUGGING REPORT

OPERATOR LICENSE # 6273

LEASE NAME Frisbie "K" WELL # 1

OPERATOR: Robert R. Price
NAME &
ADDRESS Box 45442, Tulsa, Ok.
74145

COUNTY Ellis

WELL TOTAL DEPTH 3700 \$120.25 FEET

CONDUCTOR PIPE: SIZE _____ FEET _____

SURFACE CASING: SIZE 8 5/8" FEET 322'

ABANDONED OIL WELL X GAS WELL _____ INPUT WELL _____ SWD WELL _____ D&A _____

OTHER WELL AS HEREINAFTER INDICATED _____

PLUGGING CONTRACTOR Kelso Casing Pulling LICENSE NUMBER 6050

ADDRESS Box 176, Chase, Mo. 67524

COMPANY TO PLUG AT: HOUR: 9:00 AM DAY: 1 MONTH: 6 YEAR: 1983

PLUGGING PROPOSAL RECEIVED FROM Willard Kelso

(COMPANY NAME) Kelso Casing Pulling (PHONE) 316-938-2457

WERE: Order 165 lbs. 50% cement - 4% gel - 3% tal. cl., 15 lbs. gel,
5 lbs. bulls. & 8 5/8" plug.

PLUGGING PROPOSAL RECEIVED BY John E. Shub
(TECHNICIAN)

PLUGGING OPERATIONS ATTENDED BY AGENT?: ALL X PART _____ NONE _____

OPERATIONS COMPLETED: HOUR: 12:30 PM DAY: 1 MONTH: 7 YEAR: 1983

ACTUAL PLUGGING REPORT 8 5/8" - 322' w/ 175 lbs, 5 1/2" set at 3699' w/ 200 lbs.

Plug back to 3590'. Top perf. at 3089'. Plugged bottom w/ 5 lbs
cement, sand & 5 lbs. cement to 3000'. Shot pipe 1 time & recovered
2612'. Pumped in 8 5/8", 4 lbs. bulls, 12 lbs. gel, 65 lbs. cement,
3 lbs. gel, 1 lb. bulls, released plug & followed w/ 100 lbs.
cement w/ 500 pounds pressure.

REMARKS: Clor. 2060'
Cemented by Allied Cementing Co. Inc.

I (DID / ~~DID NOT~~) OBSERVE THIS PLUGGING.

RECEIVED
STATE CORPORATION COMMISSION

John E. Shub
(TECHNICIAN) ✓

INVOICED

DATE 7-19-83
INV. NO. 4879-W

JUL 19 1983
CONSERVATION DIVISION
Wichita, Kansas

FORM CP-2/3
REV. 6-83