TO:

STATE CORPORATION COMMISSION **CONSERVATION DIVISION - PLUGGIN**

130 SOUTH MARKET, SUITE 2078

WICHITA, KANSAS 67202

API Well Number: 15-207-20086-00-01

Spot: SESESESE

Sec/Twnshp/Rge: 8-25S-16E

Depth (ft) Pulled (ft) Comments

220 feet from S Section Line,

220 feet from E Section Line

Lease Name: FLORENCE TOEDMAN

Well #: 1

County: WOODSON

String Size

PROD 2.875

PROD 2.875

SURF 7

UIC Docket No: E15500.25

Total Vertical Depth: 970 feet

Operator License No.: 4485

Op Name: VERDE OIL COMPANY

Address: 1020 NE LOOP 410 STE 555

SAN ANTONIO, TX 78209

SURF 7 60

Date/Time to Plug: 07/06/2012 12:00 AM

110 SX

20 SX

Plug Co. License No.: 5491

Well Type: EOR

Plug Co. Name: W & W PRODUCTION COMPANY, GENERAL PARTNERSHIP

966

970

40

Proposal Rcvd. from: JEFFREY L. DALE

Company: VERDE OIL CO

Phone: (620) 754-3800

Plugging Method:

Proposed Squeeze plug from PBTD to surface with +/-40 sacks Class A cement. Well will be plugged from PBTD to surface.

Plugging Proposal Received By: LARRY MARCHANT

Date/Time Plugging Completed: 07/05/2012 9:00 AM

WitnessType: COMPLETE (100%)

KCC Agent: LARRY MARCHANT

Actual Plugging Report:

Perfs: Top

950

Bot

965

Thru

Comments

Establish Injection Rate of 1 Bbl per min. at 250 psi with water. Start pumping cement with
hulls @ 250 psi, pressured up to 1000 psi and set on for 1 min. to 0 psi. bumped 3 time to 1000
psi and shut in @ 500 psi. Used 30 sacks cement and 1/4 sack hulls.

ΚE	CE	M	=D

9 2012 /CM

KCC Chanute Dist. #3

Remarks:

Plugged through: CSG

District: 03

Signed

KCC WICHITA