

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 135-23,277-0000
C NW NE, SEC. 20, T 17 S, R 26 W
4620 feet from S section line
1980 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5151
Operator: Gear Petroleum Company, Inc.
Name & Address: 1075 Kansas State Bank Bldg.
125 North Market
Wichita, KS 67202

Lease Name Quenzer Well # 1-20
County Ness 145.60
Well Total Depth 4480 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 334

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor Chief Drilling Company, Inc. License Number 5883

Address 151 North Main, Suite 700, Wichita, KS 67202

Company to plug at: Hour: 2 a.m. Day: 24 Month: 8 Year: 1988

Plugging proposal received from Harold Dinkle

(company name) Chief Drilling Company, Inc. (phone) 316-262-3791

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1892-1926'

1st plug at 1925' with 50 sx cement, 2nd plug at 1060' with 80 sx cement,

3rd plug at 390' with 50 sx cement, 4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Paul A Luthi (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 4 a.m. Day: 24 Month: 8 Year: 1988

ACTUAL PLUGGING REPORT 1st plug at 1925' with 50 sx cement,

2nd plug at 1060' with 80 sx cement,

3rd plug at 390' with 50 sx cement,

4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

RECEIVED
STATE CORPORATION COMMISSION
AUG 25 1988
CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Allied.
(If additional description is necessary, use BACK of this form.)

NOTICE: Do not observe this plugging.

Signed Paul A. Luthi (TECHNICIAN)

DATE 8-29-88

INV. NO. 22046

(see rules on reverse side)

Expected Spud Date 7 month 27 day 88 year

API Number 15-135-23,277-0000

OPERATOR: License # 5151
Name Gear Petroleum Co., Inc.
Address 1075 KSB Bldg. 125 N. Market
City/State/Zip Wichita, KS 67202
Contact Person Jim Thatcher
Phone (316) 265-3351

CONTRACTOR: License # 5883
Name Chief Drilling Co., Inc.
City/State Wichita, KS 67202

Well Drilled For: Well Class: Type Equipment:
X Oil Storage Infield X Mud Rotary
Gas Inj Pool Ext Air Rotary
OWWO Expl X Wildcat Cable

If OWWO: old well info as follows:
Operator
Well Name
Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.
Date 7/21/88 Signature of Operator or Agent Title Drlg. & Prod. Mgr.

For KCC Use:
Conductor Pipe Required feet; Minimum Surface Pipe Required 200 feet per Alt. X (2)
This Authorization Expires 1-22-89 Approved By LKM 7-22-88

Spud 8-15-88
Set 320' 8/8

East
NW NE Sec. 20 Twp. 17 S. Rg. 26 X West
4620 Ft. from South Line of Section
1980 Ft. from East Line of Section
(Note: Locate well on Section Plat on reverse side)
Nearest lease or unit boundary line 660 feet
County Ness
Lease Name Quenzer Well # 1-20
Ground surface elevation unknown feet MSL
Domestic well within 330 feet: yes X no
Municipal well within one mile: yes X no
Depth to bottom of fresh water 100
Depth to bottom of usable water 100
Surface pipe by Alternate: 1 2 X
Surface pipe planned to be set 320
Conductor pipe required none
Projected Total Depth 4600 feet
Formation Mississippian

East
NW NE Sec. 20 Twp. 17 S. Rg. 26 X West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

Table with 4 columns: Plug depth (ft.), Formation, Plug length (SX), and Material. Includes entries for 1st plug @ 1850 ft. deep, 2nd plug @ 1075 ft. deep, 3rd plug @ 370 ft. deep, 4th plug @ 40 ft. deep, 5th plug @ ft. deep, and (2) Rathole to surface minus 5 feet 15 SX.

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging. In Addition: Call district office before well is either plugged or production casing is cemented in. (Call 7 a.m. to 5 p.m. workdays)

District office use only:

Handwritten notes and stamps: Jsher Harold Drinkle, 4480 FORMATION Miss, REFACE PIPE 5 1/2" @ 334', HYDRITE 1892 ELEVATION 8-24-88, CASKING TIME & DATE 2:00 AM, COMPLETION TIME & DATE 4:00 AM, 1st PLUG @ 1925 FT. W/ 50 SX, 2nd PLUG @ 1060 FT. W/ 80 SX, 3rd PLUG @ 390 FT. W/ 50 SX, 4th PLUG @ 40-0 FT. W/ 10 SX, 5th PLUG @ 15 SX, MUSE HOLE CIRCULATED W/ SX, WATER WELL PLUGGED W/ SX, CEMENT COMPANY Allied, RECEIVED STATE CORPORATION COMMISSION, AUG 25 1988, INSERVATION DIVISION Wichita, Kansas.