

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 135-21,738-~~E~~-00-01

N/2 N/2 SE SEC. 22, 7 18 S, R 24 W/E

2310 feet from S section line

1320 feet from E section line

Lease Name Cheyenne Well # 1 OWWO.

County Ness

Well Total Depth 4317 140.30 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 333

TECHNICIAN'S PLUGGING REPORT

Operator License # 30742

Operator: Palomino Petroleum, Inc.

Name & Address 4924 SE 84th St.

Newton, KS 67114-8827

\_\_\_\_\_

\_\_\_\_\_

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Palomino Petroleum, Inc. License Number 30742

Address 4924 SE 84th St., Newton, KS 67114-8827

Company to plug at: Hour: 1:30 p.m. Day: 10 Month: 12 Year: 1993

Plugging proposal received from Steve Robben

(company name) Palomino Petroleum, Inc. (phone) 913-735-9405

Work: 5 1/2" at 4302' w/600 sx cement, PBD 4281'. Perfs at 3681-84', Upper stage cemented w/350

1st plug hook onto 5 1/2" casing and pump in 2 sx hulls, 50 sx cement, 17 sx gel, and 170 sx cement

Check backside.

Plugging Proposal Received by Steve Middleton (TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 1:30 p.m. Day: 10 Month: 12 Year: 19 93

ACTUAL PLUGGING REPORT 1st plug hooked onto 5 1/2" casing and pumped in 2 sx hulls, 50 sx cement, 17 sx gel, and 170 sx cement. Maximum pressure 800 psi and shut in 650 psi.

Backside pressured to 300#.

Remarks: Used 65/35 Pozmix 8% gel by Allied. No casing recovery.

(If additional description is necessary, use BACK of STATE CORPORATION COMMISSION

I, (d) / observe this plugging.

12-30-93  
39602

Signed \_\_\_\_\_

RECEIVED  
DEC 16 1993  
STATE CORPORATION COMMISSION  
Wichita, Kansas