

To: 1 070627  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

DEC 15 1988

API NUMBER 15-135-23,312-00-00

NW SE NW, SEC. 21, T 19 S, R 21 W/E  
3630 feet from S section line  
3630 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 8061

Lease Name Meyer Well # 1

Operator: Oil Producers, Inc. of Kansas

County Ness

Name & Address P.O. Box 8647

Well Total Depth 4415 feet

Wichita, KS 67208

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 204

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Western Kansas Drilling Inc. License Number 4083

Address Box 126, Hays, KS 67601

Company to plug at: Hour: 2 p.m. Day: 15 Month: 12 Year: 19 88

Plugging proposal received from Jim Manley

(company name) Western Kansas Drilling Inc. (phone) 913-628-2296

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2252'  
Anhydrite 1472-1501'

1st plug at 1500' with 50 sx cement, 2nd plug at 850' with 60 sx cement,

3rd plug at 240' with 50 sx cement, 4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Duane Rankin  
(TECHNICIAN)

Plugging Operations attended by Agent?: All X Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 4 p.m. Day: 15 Month: 12 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug at 1500' with 50 sx cement,

2nd plug at 850' with 60 sx cement and 1 sx hulls,

3rd plug at 240' with 50 sx cement,

4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION

DEC 21 1988

12-21-1988

CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.

(If additional description is necessary, use BACK of this form.)

INVOICED (If applicable) observe this plugging.

DATE DEC 22 1988

Signed Dan Goodson  
(TECHNICIAN)

INV. NO. 23441

12-15 FEB 10 1989

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date: 11/28/88 month day year

API Number 15-135-23, 312-00-00 NW SE NW Sec. 21 Twp. 19 S, Rg. 21 East 3630 Ft. from South Line of Section 3630 Ft. from East Line of Section

OPERATOR: License # 8061 Name Oil Producers, Inc. of Kansas Address P.O. Box 8647 Wichita, Ks. 67208 Contact Person John S. Weir Phone 316-681-0231

(Note: Locate well on Section Plat on reverse side) Nearest lease or unit boundary line 660 feet County Ness

CONTRACTOR: License # 4083 Name Western Kansas Drilling Inc. City/State Hays, Ks. 67601

Lease Name Meyer Well # 1 Ground surface elevation feet MSL Domestic well within 330 feet yes no

Well Drilled For: Well Class: Type Equipment: X Oil Storage X Infield Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl Wildcat Cable

Municipal well within one mile yes no Depth to bottom of fresh water 200 Depth to bottom of usable water 790 650 Surface pipe by Alternate 1 2 X

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

Surface pipe planned to be set 200 Conductor pipe required Projected Total Depth 4450 feet Formation Cherokee, Mississippi

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Date 11/22/88 Signature of Operator or Agent John Weir Title President

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 200 feet per Alt. X 2 This Authorization Expires 5-29-89 Approved By LKM 11-29-88

EFFECTIVE DATE: 12-1-88

Set 200' of 8 5/8 on 12-7-88

RECEIVED STATE CORPORATION COMMISSION 12-21-1988

NW SE NW Sec. 21 Twp. 19 S, Rg. 21 East

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep 50 either side of salt formation on top of Dakota or formation with Dakota feet of 50 each side of base to surface feet of 50 either side of base to surface feet of 50 or formation with feet of 50 or formation with feet of (2) Rathole to surface minus 5 feet (b) Mousehole to surface minus 5 feet

Table with columns: PUSHED TO, SURFACE PIPE, ANHYDRITE, STARTING TIME & DATE, COMPLETION TIME & DATE, 1st PLUG @ 150 FT. W/ 50 SX, 2nd PLUG @ 850 FT. W/ 60 SX, 3rd PLUG @ 240 FT. W/ 50 SX, 4th PLUG @ 40 FT. W/ 10 SX, RAT HOLE CIRCULATED W/ 15 SX, MOUSE HOLE CIRCULATED W/ SX, WATER WELL PLUGGED W/ SX, CEMENT COMPANY added

TECHNICIAN 18 50 60 70 80