| $\mathcal{I} \mathcal{I} \mathcal{L} \mathcal{I} \mathcal{I} \mathcal{I} \mathcal{I} \mathcal{I} \mathcal{I} \mathcal{I} I$  | 8-10-88   |
|--|---|
| 1 370574   | API NUMBER 15-135-23,264-00-00                                  |
| STATE CORPORATION COMMISSION<br>CONSERVATION DIVISION - PLUGGING SECTION   | C SW NW, SEC. 32, T 19 S, R 21                                  |
| 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202  | 3300 feet from S section line                                   |
| TECHNICIAN'S PLUGGING REPORT   |   |
| Operator License # 5184  | Lease Name_Batt "C" Well # 1                                    |
| Operator: Shields Oil Producers, Inc.  | CountyNess 143.91   |
| Nome& RECEIVED Address Shields Building RECEIVED   | Well Total Depth 4428 feet                                      |
| Russell, KS 67665  | Conductor Pipe: Sizefeet  |
| AUG 1 5 1988   | Surface Casing: Size 8 5/8 feet 622                             |
| D875-1989  | ——————————————————————————————————————                          |
| 2012511111014 814191014  | Input Well D&AX   |
| Other well as hereInafter Indicated Wichita Kansas   |   |
| Plugging Contractor Shields Drilling Company   | License Number 5055   |
| Address Box 709, Russell, KS 67665   |   |
| Company to plug at: Hour: 7:30 a.m. Day:   | 10 Month: 8 Year: 19 88   |
| Plugging proposal received from Burt Beer  | <u>y</u>  |
| (company name) Shields Oil Producers   |   |
| were: to fill hole with heavy mud and spot   | cement through drill pipe Elevation 2273 GL Aphydrite 1500-1534 |
| 1st plug at 1535' with 50 sx cement, 2nd p   | •   |
| 3rd plug at 40-0' with 10 sx cement,   |   |
| 4th plug to circulate rathole with 15 sx cer   | ment.   |
| 5th plug to circulate mousehole with 10 sx of  |   |
|  | Received by Paul A. Luthi                                       |
| Frugging Propose   | (TECHNICIAN)  |
| Plugging Operations attended by Agent?: Ail  | Part X None   |
|  |   |
| Operations Completed: Hour: 10:30 a.mbay:  | 10 Month: 8 Year:19 88  |
| Operations Completed: Hour: 10:30 a.m. Day: ACTUAL PLUGGING REPORT Lost circulation at 27  | <del></del>   |
|  | 776', mixed LCM, circulation in 15 minutes.                     |
| ACTUAL PLUGGING REPORT Lost circulation at 2   | 776', mixed LCM, circulation in 15 minutes.                     |
| ACTUAL PLUGGING REPORT Lost circulation at 2   | 776', mixed LCM, circulation in 15 minutes.                     |
| ACTUAL PLUGGING REPORT Lost circulation at 2.  1st plug at 1535' with 50 sx cement.  2nd plug at 865' with 80 sx cement,  3rd plug at 630' with 50 sx cement,  | 776', mixed LCM, circulation in 15 minutes.                     |
| ACTUAL PLUGGING REPORT Lost circulation at 23  1st plug at 1535' with 50 sx cement.  2nd plug at 865' with 80 sx cement,  3rd plug at 630' with 50 sx cement,  4th plug at 40' with 10 sx cement,  | 776', mixed LCM, circulation in 15 minutes.                     |
| ACTUAL PLUGGING REPORT Lost circulation at 27  1st plug at 1535' with 50 sx cement.  2nd plug at 865' with 80 sx cement,  3rd plug at 630' with 50 sx cement,  4th plug at 40' with 10 sx cement,  5th plug to circulate rathole with 15 sx cement   | 776', mixed LCM, circulation in 15 minutes.                     |
| ACTUAL PLUGGING REPORT Lost circulation at 2.  1st plug at 1535' with 50 sx cement.  2nd plug at 865' with 80 sx cement,  3rd plug at 630' with 50 sx cement,  4th plug at 40' with 10 sx cement,  5th plug to circulate rathole with 15 sx cer  Remarks: Used 60/40 Pozmix 6% gel by Allied.  (If additional description is not | ment,6th plug to circulate mousehole with 10 sx                 |
| ACTUAL PLUGGING REPORT Lost circulation at 27  1st plug at 1535' with 50 sx cement.  2nd plug at 865' with 80 sx cement,  3rd plug at 630' with 50 sx cement,  4th plug at 40' with 10 sx cement,  5th plug to circulate rathole with 15 sx cer  Remarks: Used 60/40 Pozmix 6% gel by Allied.                                    | ment,6th plug to circulate mousehole with 10 sx                 |

FORM CP-2/3 Rev.01-84