

1 060525

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-135-22,765-0000  
SE SE NW, SEC. 2, T 19 S, R 24 W/EX

2970 feet from S section line  
2970 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 9310

Lease Name Brandt Well # 1

Operator: Bentley Oil & Gas Company

County Ness 143.33

Name & Address P. O. Box 5012

Well Total Depth 4410 feet

Wichita Falls, TX 76307

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 553

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor DaMac Drilling, Inc. License Number 6333

Address Box 1164, Great Bend, KS 67530

Company to plug at: Hour: 10:00 pm Day: 27 Month: March Year: 19 85

Plugging proposal received from John Crowe

(company name) DaMac (phone) 316-792-1353

work: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 1550' with 50 sx cement

2nd plug at 770' with 50 sx cement

3rd plug at 560' with 50 sx cement

4th plug <sup>solid bridge</sup> hulls - plug at 40' -- cement to surface with 10 sx cement

Plugging Proposal Received by Paul A. Luthi  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 12:00 am Day: 28 Month: March Year: 19 85

ACTUAL PLUGGING REPORT 1st plug at 1550' with 50 sx cement, 2nd plug at 770' with 50

sx cement, 3rd plug at 560' with 50 sx cement, 4th & 5th plugs - solid bridge - hulls -

plug at 40' -- cement to surface with 10 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION

APR 04 1985

Remarks: Used 60/40 Pozmix 2% gel 3% cc by Halliburton CONSERVATION DIVISION  
Wichita, Kansas  
(If additional description is necessary, use BACK of this form.)

INVOICED (did not) observe this plugging.

DATE 4-8-85

Signed Paul A. Luthi  
(TECHNICIAN)

INV. NO. 7508

3-28