KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

			500 ///01/400	tions on Reve		7)			
						API	No. 15	, ·	
у		<i>5-22-</i>	12			071	-20379 - 0		
pany eshoe Operating, Inc.					Lease Sandifer A		ð.	Well Number	
Location C NW/4		Section 33		TWP 19S		RNG (E/W) 39W		Acres Attributed	
		Reservoir Winfield						ection	
				h	,	Packer S	Set at		
Weight 14.0	Politica (international des la constantidad de la constantidad de la	Internal Diameter 5.012		Set at 2939'		Perforations 2819'		_{То} 2827'	
Weight		Internal Diameter		Set at		Perforations		То	
(Describe)	scribe) Type Fluid Produc					Pump Unit or Traveling Plunger? Yes / No			
3.0									
Annulus / Tubing)		, % C	arbon Dioxi	ae.	,	% Nittog	ен	Gas Gr	avity - Gg
	······································			•					Run) (Prover) Size
Shut in5	-21 20	12 at _			aken	5-2	2	_	3 (AM) (PM)
		-				• .			_
									- A1/
	T		OBSERVE	T.		1 :		Duration of Shut-	in 4 Hou
ic / Orifice		٠,	wing Well Head Wellhead Pres		essure	Wellhead Pressure		Duration Liquid Produ (Hours) (Barrets)	
psig (Pm)	Inches H ₂ 0	t	t	psig	psia	psig	psia	(Hours)	(Daireis)
5				42				24	
	<u> </u>								
		 	FLOW STR	EAM ATTRIB	UTES		 		
Circle one: Meter or	Press Extension	Grav Fact	~ 1 1	Flowing Temperature		ctor	Metered Flow	GOR (Cubic Fe	Flowing
Prover Pressure psia	√ P _m xh	F.		Factor F _{ft}		pv	(Mcfd)	Barrel)	ev Cravity
	P _m xh	F _a		1		pv	(Mcfd)	Barrel)	Gravity
psia	, , ,	(OPEN FLO	OW) (DELIV	F _{r.} ERABILITY) (CALCUL	ATIONS	(Mcfd)	(P _a)	Gravity G _m 2 = 0.207
psia	, , ,	•	OW) (DELIV	F _{rt} ERABILITY) (% (P _c	CALCUL - 14.4) +	ATIONS	(Mcfd)		Gravity G _m 2 = 0.207 2 ±
psia	000se formula 1 or 2: 1. P _c ² - P _a ²	(OPEN FLO	OW) (DELIV	F _n ERABILITY) (% (P _c Backpress: Slope	CALCUL - 14.4) + ure Curve = "n"	.ATIONS	: : :	(P _a)	Gravity G _m 2 = 0.207
psia	oose formula 1 or 2:	(OPEN FLC	OW) (DELIV	F _n ERABILITY) (% (P _c Backpress: Slope	CALCUL - 14.4) + ure Curve = "n"	.ATIONS	: :	(P _a)	Gravity G _m 2 = 0.207 2 = Open Flow
psia	oose formula 1 or 2: 1. P _c ² - P _a ² 2. P _c ² - P _d ²	(OPEN FLC Pd = LOG of formula 1. or 2. and divide	DW) (DELIVI	F _{ft} ERABILITY) (% (P _c Backpress Slope	CALCUL - 14.4) + ure Curve = "n"	.ATIONS	: :	(P _a)	Gravity G _m 2 = 0.207 2 ± Open Flow Deliverability Equals R x Antilo
psia	: oose formula 1 or 2: 1. P _c ² - P _a ² 2. P _c ² - P _d ² ided by: P _c ² - P _a ²	(OPEN FLC Pd = LOG of formula 1. or 2. and divide by:	DW) (DELIVI	F ₁₁ ERABILITY) (% (P _c Backpressistope	CALCUL - 14.4) + ure Curve = "n" rned 1 Slope	.ATIONS	:	(P _a) (P _d)	Gravity G _m 2 = 0.207 2 ± Open Flow Deliverability Equals R x Antilo (Mcfd)
psia	oose formula 1 or 2: 1. P _c ² - P _a ² 2. P _c ² - P _d ²	(OPEN FLC Pd = LOG of formula 1. or 2. and divide by:	DW) (DELIVI	F _{ft} ERABILITY) (% (P _c Backpress Slope	CALCUL - 14.4) + ure Curve = "n" rned 1 Slope	.ATIONS	:	(P _a)	Gravity G _m 2 = 0.207 2 ± Open Flow Deliverability Equals R x Antilo (Mcfd)
psia	oose formula 1 or 2: 1. P _c ² - P _a ² 2. P _c ² - P _d ² ided by: P _c ² - P _a ² Mcfd @ 14.6	(OPEN FLC Pd = LOG of formula 1. or 2. and divide by:	DW) (DELIVI	F ₁₁ ERABILITY) (% (P _c Backpress Slope	CALCUL - 14.4) + ure Curve = "n" re ned 1 Slope	ATIONS 14.4 =	: _og []	(P _a): (P _d): Antilog Mcfd @ 14.65 psi	Gravity Gravity G _m 2 = 0.207 2 = Open Flow Deliverability Equals R x Antilo (Mcfd)
psia $ (P_w)^2 = {Cht} $ $ (P_c)^2 \cdot (P_w)^2 \qquad divi$ and authority, on the prein, and that said	oose formula 1 or 2: 1. P _c ² - P _a ² 2. P _c ² - P _d ² ided by: P _c ² - P _d ² Mcfd @ 14.6: behalf of the C	(OPEN FLO Pd = LOG of formula 1. or 2. and divide by: 5 psia Company, si	DW) (DELIV) Pc-Pw tates that he	F _{ft} ERABILITY) (% (P _c Backpress Slope Assig Standard Deliverabilit e is duly autr	CALCUL - 14.4) + ure Curve = "n" rined d Slope	ATIONS 14.4 =	: _og []	(P _a): (P _d): Antilog Mcfd @ 14.65 psi	Gravity Gravity G _m 2 = 0.207 2 = Open Flow Deliverability Equals R x Antilo (Mcfd)
psia $ (P_w)^2 = \frac{Chv}{(P_c)^2 \cdot (P_w)^2} $ $ divi$ and authority, on the	oose formula 1 or 2: 1. P _c ² - P _a ² 2. P _c ² - P _d ² ided by: P _c ² - P _d ² Mcfd @ 14.6: behalf of the C	(OPEN FLO Pd = LOG of formula 1. or 2. and divide by: 5 psia Company, si	DW) (DELIV) Pc-Pw tates that he	F _{ft} ERABILITY) (% (P _c Backpress Slope Assig Standard Deliverabilit e is duly autr	CALCUL - 14.4) + ure Curve = "n" rined d Slope	ATIONS 14.4 = n x l	: _og []	(P _a): (P _d): Antilog Mcfd @ 14.65 psi	Gravity Gravity G _m 2 = 0.207 2 = Open Flow Deliverability Equals R x Antilo (Mcfd)
	Location C NW/4 Weight 14.0 Weight 4.7 (Describe) Annulus / Tubing) Shut in	Weight 14.0 Weight 4.7 (Describe) Annulus / Tubing) Shut in 5-21 Started 20 Started 20 Circle one: Meter Prover Pressure psig (Pm) Inches H ₂ 0 Circle one: Press	Section Winfield Plug Back 2891' Internal D 5.012 Weight Internal D Section Se	Pressure Differential Flowing Proyer Pressure Psig (Pm) Circle one: Meter Proyer Pressure psig (Pm) Press Circle one: Press Plant Pressure Psig (Pm) Press Press Plant Proyer Pressure Psig (Pm) Press Press Plant Psig (Pm) Press Press Plant Psig (Pm) Press Press Plant Psig (Pm) Press Press Psig (Pm) Pre	Lease Sandifer A Location Section TWP C NW/4 33 19S Reservoir Winfield Plug Back Total Depth 2891' Weight Internal Diameter Set at 14.0 5.012 2939' Weight Internal Diameter Set at 4.7 1.995 2713' (Describe) Type Fluid Production Water Annulus / Tubing) % Carbon Dioxide Pressure Taps Flange Shut in 5-21 20/2 at 7:23 (AM) (PM) T Started 20 at (AM) (PM) T OBSERVED SURFACE Casin In Circle one: Meter Prover Pressure Differential in Inches H ₂ 0 Flowing Temperature Temperatur	Lease Sandifer A Location Section TWP C NW/4 33 19S Reservoir Winfield Plug Back Total Depth 2891' Weight Internal Diameter Set at 14.0 5.012 2939' Weight Internal Diameter Set at 1.995 2713' (Describe) Type Fluid Production Water Annulus / Tubing) % Carbon Dioxide Pressure Taps Flange Shut in 5-21 20/2 at 7:23 (AM) (PM) Taken Started 20 at (AM) (PM) Taken OBSERVED SURFACE DATA OBSERVED SURFACE DATA OBSERVED SURFACE DATA Casing Well Head Temperature Temperature (P,) or (P,) o	Annulus / Tubing) Section Section TWP RNG (E/C NW) 4 33 198 39W Reservoir Winfield DCP M Plug Back Total Depth 2891 Weight Internal Diameter Set at Performance Set at S	Trating, Inc. Lease Sandifer A Location C NW/4 33 19S 39W Reservoir Winfield Plug Back Total Depth 2891' Weight Internal Diameter Set at Perforations 14.0 5.012 2939' Weight Internal Diameter Set at Perforations 4.7 1.995 2713' (Describe) Type Fluid Production Water Pressure Taps Flange Shut in 5-21 20/2 at 7:23 (AM) (PM) Taken 20 OBSERVED SURFACE DATA OBSERVED SUR	Section Section TWP RNG (E/M) 39W

l de	clare under penalty of perjury under the laws of the state of Kansas that I am authorized to request
	status under Rule K.A.R. 82-3-304 on behalf of the operator Horseshoe Operating, Inc.
	the foregoing pressure information and statements contained on this application form are true and
	o the best of my knowledge and belief based upon available production summaries and lease records
	ment installation and/or upon type of completion or upon use being made of the gas well herein named.
l he	eby request a one-year exemption from open flow testing for the Sandifer A #1
gas well	on the grounds that said well:
staff as ı	is a coalbed methane producer is cycled on plunger lift due to water is a source of natural gas for injection into an oil reservoir undergoing ER is on vacuum at the present time; KCC approval Docket No. ✓ is not capable of producing at a daily rate in excess of 250 mcf/D ther agree to supply to the best of my ability any and all supporting documents deemed by Commission necessary to corroborate this claim for exemption from testing.
	Signature: <u>Janice Ripley</u> Title: Production Assistant

Instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under **OBSERVED SURFACE DATA**. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption **IS** denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.