

1 050488

API NUMBER 15- 135-22,766-00-00

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION E/2 E/2 SE, SEC. 31, T 18 S, R 25 W/R  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

1450 feet from S section line  
330 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 9310

Lease Name D.D. Johnson Well # 1

Operator: Bentley Oil & Gas Co.

County Ness 148.30

Name & Address P. O. Box 5012

Well Total Depth 4563 feet

Wichita, Falls, TX 76307

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 725 ✓

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Hembree Well Service, Inc. License Number 336907

Address Box 458, Ness City, KS 67560

Company to plug at: Hour: 5:00 pm Day: 30 Month: March Year: 19 85

Plugging proposal received from Warren Richardson

(company name) Bentley (phone) 817-723-0897

were: 4 1/2" at 4563' PBSD 4285' Perfs 4155-4178 - Well never produced CIBP at 4105'

1st plug squeezed well with 3sx hulls, 152sx gel, 100 sx cement, 5 sx gel, 1 sack hulls,

release 8 5/8" rubber plug and pump 50 sx cement.

Plugging Proposal Received by Richard W. Lacey  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 6:45 pm Day: 30 Month: March Year: 19 85

ACTUAL PLUGGING REPORT CIBP at 4105', 1st plug squeezed well with 3 sx hulls, 15 sx gel,

100 sx cement, 5 sx gel, 1 sack hulls, released 8 5/8" rubber plug and pumped an

additional 50 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION

Maximum pressure 500 psi and shut in 150 psi

APR 04 1985  
04-04-1985

Remarks: Recovered 1400' 4 1/2" casing. Used 60/40 Pozmix 2% w/gel 3% case by Halliburton.  
(If additional description is necessary, use BACK of this form.)

INVOICED

(did not) observe this plugging.

Signed Richard W. Lacey  
(TECHNICIAN)

DATE 4-8-85

INV. NO. 7509

3-30