

1 070495

1-2-87

API NUMBER 15-135-23,192-00-00

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

SW NW NW, SEC. 29, T 18 S, R 25 W XX

4290 feet from S section line

4950 feet from E section line

Lease Name Dennis Johnson Well # 1

County Ness 145.57

Well Total Depth 4479 feet

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 223

TECHNICIAN'S PLUGGING REPORT

Operator License # 3447

Operator: Ranken Energy Corporation

Name & Address 2932 N.W. 122nd, Suite 18

Oklahoma City, OK 73120

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor R & C Drilling Company, Inc. License Number 9087

Address P.O. Box 296, Hays, KS 67601

Company to plug at: Hour: 1 p.m. Day: 2 Month: 1 Year: 19 88

Plugging proposal received from John Weis

(company name) R & C Drilling Company, Inc. (phone) 913-625-4548

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2464' Anhydrite 1741-76'

1st plug at 1790' with 50 sx cement, 2nd plug at 850' with 80 sx cement,

3rd plug at 250' with 40 sx cement, 4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Dan Goodrow (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 4 p.m. Day: 2 Month: 1 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug at 1790' with 50 sx cement,

2nd plug at 850' with 80 sx cement,

3rd plug at 250' with 40 sx cement,

4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

RECEIVED
STATE CORPORATION COMMISSION
JAN 05 1988
CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.

(If additional description is necessary, use BACK of this form.)

I (XXX) did not observe this plugging.

Signed Dan Goodrow (TECHNICIAN)

DATE 1-11-88

INV. NO. 19497

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date. Dec. 12, 1987 month day year

API Number 15-135-23,192-00-20

OPERATOR: License # 3447 Name RANKEN ENERGY CORPORATION Address 2932 N.W. 122nd, Suite #18 City/State/Zip Oklahoma City, OK, 73120 Contact Person Gary Misak Phone (316) 792-3664

SW/4 NW/4 NW/4 Sec. 29 Twp. 18 S, Rg. 25 East X West 4290' Ft. from South Line of Section 4950' Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

Nearest lease or unit boundary line 330' feet County NESS

CONTRACTOR: License # Not known at this time Name City/State

Lease Name DENNIS JOHNSON Well # 1 Ground surface elevation 2464' est. feet MSL Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no

Well Drilled For: Well Class: Type Equipment: X Oil Storage Infield Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl X Wildcat Cable

Depth to bottom of fresh water 75' Depth to bottom of usable water 930' Surface pipe by Alternate: 1 X Surface pipe planned to be set 200' Conductor pipe required Projected Total Depth 4500' feet Formation MISSISSIPPIAN

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Date NOV. 17, 1987 Signature of Operator or Agent Randolph L. Coy Title Randolph L. Coy, President

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 200 feet per Alt. X 2 This Authorization Expires 5-19-88 Approved By Ret 11-19-87

EFFECTIVE DATE: 11-24-87

SPUD 12-17-87

8 5/8" 225'

SW/4 NW/4 NW/4 Sec. 29 Twp. 18 S, Rg. 25 East X West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep. ANHYDRITE BASE or formation with 50 SXS feet of 60-40 Poz. w/6% gel 950' 2nd plug @ ft. deep. BASE SURF. PIPE or formation with 100 SXS feet of " " " " " 3rd plug @ ft. deep. 40' FROM SURFACE or formation with 50 SXS feet of " " " " " 4th plug @ ft. deep. or formation with 10 SXS feet of " " " " " 5th plug @ ft. deep. or formation with feet of (2) Rathole to surface minus 5 feet (b) Mousehole to surface minus 5 feet 10 SXS

PUSHER John Wise TD 4479 FORMATION Mis. SURFACE PIPE 8 5/8" @ 223' ANHYDRITE 1741-76 ELEVATION 2464 STARTING TIME & DATE 1:00 pm 1-2-88 COMPLETION TIME & DATE 4:00 pm 1-2-88 1st PLUG @ 1790 FT. W/ 50 SX 2nd PLUG @ 850 FT. W/ 80 SX 3rd PLUG @ 250 FT. W/ 40 SX 4th PLUG @ 40 FT. W/ 10 SX RAT HOLE CIRCULATED W/ 15 SX MOUSE HOLE CIRCULATED W/ SX WATER WELL PLUGGED W/ SX CEMENT COMPANY Halliburton TECHNICIAN P.G.

REC-1110 STATE CORPORATION COMMISSION

JAN 05 1988

CONSERVATION DIVISION Wichita, Kansas

01-05-1988

60/40 69%