

15-135-0029700-00

WELL PLUGGING RECORD

OR

FORMATION PLUGGING RECORD

Strike out upper line when reporting plugging off formations.

STATE OF KANSAS STATE CORPORATION COMMISSION

Give All Information Completely Make Required Affidavit Mail or Deliver Report to: Conservation Division State Corporation Commission 100 Bitting Building Wichita, Kansas

Ness County. Sec. 19. Twp. 18. Rge. 25. 18/1/1 (W)

Location as "NE1/4NW1/4SW1/4" or footage from lines. NW 1/4 SE

Lease Owner. Newton Oil Company

Lease Name. D. O. Teeny Well No. 1

Office Address. 910 Equitable Bldg., Denver, Colorado

Character of Well (completed as Oil, Gas or Dry Hole). Abandoned Oil Well

Date well completed. 19. 19. 19.

Application for plugging filed. July 4, 1945

Application for plugging approved. July 6, 1945

Plugging commenced. July 31, 19. 45

Plugging completed. July 31, 19. 45

Reason for abandonment of well or producing formation. Oil depleted

If a producing well is abandoned, date of last production. 19.

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

H. W. Kerr

Name of Conservation Agent who supervised plugging of this well.

Producing formation. Depth to top. Bottom. Total Depth of Well. 4466 Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Table with 7 columns: Formation, Content, From, To, Size, Put In, Pulled Out. The table is mostly empty.

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hold. If cement or other plugs were used, state the character of same and depth placed, from...feet to...feet for each plug set.

The hole was filled with mud from 4466 feet to bridge at 4316 feet. Cement bridge from 4316 feet to 4286 feet, with 10 sacks Mud from 4286 feet to 450 feet. 25 sacks of cement from 450 feet to 420 feet. Mud from 420 feet to 10 feet and cement into base of cellar with 10 sacks. 1992 feet of 10-3/4 inch pipe cemented and left in hole.

07-08-1947

(If additional description is necessary, use BACK of this sheet)

Correspondence regarding this well should be addressed to. Newton Oil Company, 910 Equitable Bldg., Denver, Colorado

STATE OF COLORADO CITY AND COUNTY OF DENVER

H. L. Jewell, Treasurer (employee of owner) or (owner or operator) of the above-described well,

being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) H. L. Jewell, Treas.

910 Equitable Building, Denver Colo (Address)

SUBSCRIBED AND SWORN to before me this 7th day of July

July 30, 1949

Notary Public signature

Notary Public

My commission expires.

PLUGGING FILE 19-18-R25W 1949

15-135-00297-00-00

DRILLER'S LOG

S. H. KEOUGHAN, et al, Well #1

CASING RECORD

D. O. Tenny Farm
 Location 330' South and 660'
 West of the NE corner NW₄ of
 SE₄ Sec 19, T 18S, R 25W
 Contractor: Adkins Drilling Co.

530' 15¹/₂" - Pulled
 1198' 12¹/₂" - Pulled
 1942' 10-3/4" - No recovery
 4369¹/₂' 6-5/8" - Recovered 1968'

NESS COUNTY, KANSAS

Elevation - 2544

<u>Formation</u>	<u>Depth</u>	<u>Formation</u>	<u>Depth</u>
Ft. Hays Lime	0 to 65	Lime	1206 to 1210
Blue Shale	65 " 295	Lime	1210 to 1218
Sandy Shale	295 " 320	Red rock	1218 to 1232
Shale & Shells	320 " 435	Shale	1232 to 1237
Blue Shale	435 " 460	Sand	1237 to 1260
Sand	460 " 475 Water at 469	Red Rock	1260 to 1265
Sand	475 " 500	Red rock	1265 to 1275
Blue Shale	500 " 531 Set 15 ¹ / ₂ Casing	Sand (H.F.W. 1278)	1275 to 1293
Sandy Lime	531 " 538	Sand	1293 to 1300
Red Rock	538 " 543	Red rock	1300 to 1308
Blue Shale	543 " 560	Sand	1308 to 1315
Gran. Shale	560 " 594	Red Rock	1315 to 1317
Lime Shell	594	Sand	1317 to 1353
Sand	594 " 618 13 Bailers of Water Per hour at 600	Red Rock	1353 to 1380
Sandy Shale Brkn	618 to 635	Sandy Shale	1380 to 1440
Gray Shale	635 to 645	Sand	1440 to 1505
Blue shale	645 to 658	Red Rock	1505 to 1530
Brown shale	658 to 675	Red shale	1530 to 1553
Blue shale	675 to 717	Hard sand	1553 to 1568
Sandy shale	717 to 729	Red Rock	1568 to 1590
Blue Shale	729 to 752	Sand	1590 to 1600
Brown Shale	752 to 771	Red Rock	1600 to 1640
Blue shale	771 to 811 Set 12 ¹ / ₂ Casing	Red Rock	1640 to 1670
Blue shale	811 to 815	Sand	1670 to 1675
Sand	815 to 829 14 F.W. 825	Red rock	1675 to 1694
Blue shale	829 to 871 Under digging from 833	Red rock	1694 to 1712
Sandy shale	871 to 875	Sandy shale	1712 to 1725
Sand	875 to 903	Red Rock	1725 to 1752
Shale	903 to 908 Caving	Broken lime	1752 to 1762
Lime	908 to 913	Sand	1762 to 1776
Blue shale	913 to 918	Sand	1776 to 1790
Red Rock	918 to 923	Anhydrate	1790 to 1808
Blue Shale	923 to 932	Red Rock	1808 to 1950
Sandy Lime	932 to 941	Sand	1950 to 1955
Sandy Lime	941 to 948	Red Rock	1955 to 1969
White sand	948 to 960	Shale	1969 to 1990
Red sand	960 to 1072 Water 965 H.F.	Red Rock	1990 to 2000
Red rock	1072 to 1081	Blue shale	2000 to 2075
Red rock	1081 to 1095	Blue shale	2075 to 2100
Red rock	1095 to 1128	Red Rock	2100 to 2110
Sand	1128 to 1155 Salt water 1128 H.F.	Brown shale	2110 to 2130
Red rock	1155 to 1185	Blue Shale	2130 to 2225
Red rock	1185 to 1188	Broken lime	2225 to 2260
Anhydrate	1188 to 1198	Showing of oil	2255 to 2260
Lime	1198 to 1204	Salt	2260 to 2280
Red Rock	1204 to 1206	Broken lime	2280 to 2315
		Showing of gas	2285

LOGGING
 19 12R 25W
 PAGE 19 - LINE 15

08-27-1945

S. H. KEOUGHAN Well No. 1
 D. O. Tenny Farm
 Location 330' South and 660'
 West of the NE corner NW₄ of SE₄
 Section 19, 18S, 25W.

Formation	Depth
Salt	2315 - 2335
Lime shell, salt	2335 - 2398
Blue shale	2398 - 2443
Lime	2443 - 2445
Lime	2445 - 2465
Lime & shale shells	2465 - 2505
" & shells, br shale	2505 - 2552
Lime brown	2552 - 2560
Lime, shells, shale	2560 - 2610
Lime, shells, br shale	2610 - 2633
Red shale	2633 - 2655
Lime (W.2660)	2655 - 2740
Broken Lime	2740 - 2775
Blue shale	2775 - 2785
Brown shale	2785 - 2795
Lime	2795 - 2815
Brown shale	2815 - 2820
Sandy lime	2820 - 2835
Red rock	2835 - 2840
Lime	2840 - 2865
Blue shale	2865 - 2870
Lime	2870 - 2880
Red shale	2880 - 2885
Lime (3EW 2960)	2885 - 3038
Red Rock	2038 - 3040
Lime	3040 - 3082
Shale	3082 - 3090
Lime	3090 - 3175
Black shale	3175 - 3180
Lime	3180 - 3218
Shale	3218 - 3225
Lime	3225 - 3250
Shale	3250 - 3257
Lime	3257 - 3298
Shale	3298 - 3319
Sandy Lime	3319 - 3323
Lime	3323 - 3331
Shale	3331 - 3372
Lime	3372 - 3383
Shale	3383 - 3408
Lime	3408 - 3475
Shale	3475 - 3478
Lime	3478 - 3502
Shale	3502 - 3524
Lime	3524 - 3548
Lime (Topeka)	3548 - 3568 Water
Lime	3568 - 3587
Shale	3587 - 3595
Shale	3595 - 3604
Lime	3604 - 3613
White Lime	3613 - 3630
Lime	3630 - 3640
Sand	3640 - 3655 Water
White Sand	3655 - 3670
Blue Shale	3670 - 3675
Lime	3675 - 3825
Shale	3825 - 3828
Lime	3828 - 3832

BEING
 19 18 25W
 19 18 25W

Formation	Depth
Blue shale	3832 - 3852
Lime	3852 - 3858
White sand	3858 - 3863
Lime	3863 - 3907
Black Lime (Water)	3907 - 3911
Shale	3911 - 3914
Lime	3914 - 3916
Black shale	3916 - 3918
White lime	3918 - 3920
White Lime	3920 - 3928
Lime	3928 - 3933
Red shale	3933 - 3935
Lime	3935 - 3944
White sand (Water)	3944 - 3970
White lime	3970 - 3980
Sandy lime (Water)	3980 - 3985
Lime	3985 - 3987
Black shale	3987 - 3990
Shale	3990 - 4003
Brown sandy lime	4003 - 4018 (Water)
Lime	4018 - 4025
White Lime	4025 - 4038
Lime	4038 - 4040
Shale	4040 - 4048
White Lime	4048 - 4050
Chart	4050 - 4055
Black shale	4055 - 4060
Lime	4060 - 4095
Black shale	4095 - 4098
Sandy lime	4098 - 4105
Lime	4105 - 4162
Red shale	4162 - 4166
Broken lime	4166 - 4180
Black sandy lime	4180 - 4195
Blk. brokn. lime	4195 - 4205
Lime	4205 - 4208
Brkn Lime & shale	4208 - 4223
Shale	4223 - 4230
Lime	4230 - 4248
Black shale	4248 - 4255
Broken lime	4255 - 4310
Shale	4310 - 4315
Lime	4315 - 4323
Brkn Lime and black shale	4323 - 4348
Shale & shells	4348 - 4360
Brn & black shale	4360 - 4373
Brown hard lime	4373 - 4376
Lime soft	4376 - 4382
Lime & black shale	4382 - 4389
Sandy lime	4389 - 4394
Lime and shale	4394 - 4401
Black shale and gray lime	4401 - 4406
Black shale and dolomite	4406 - 4411
Sh Lime & Dolomite	4411 - 4419
SLM	4419 - 4419

S. H. KEOUGHAN Well No. 1
D. O. Tenny Farm
Location 330' South and 660'
West of the NE corner NW $\frac{1}{4}$ of SE $\frac{1}{4}$
Section 19, 18S, 25W

<u>Formation</u>	<u>Depth</u>
Cherty lime, dolomite black shale	4419 - 4422
Lime, Dolomite shale	4422 - 4429
" " "	4429 - 4435
Black shale	4435 - 4438
Shale and Dolomite	4438 - 4444
Black shale	4444 - 4448
Black shale Caving	4448 - 4451
TOTAL DEPTH	4451

July 31, 1945
Plugging Record
By M. A. Raglin, Great Bend, Kansas

Ran 10 sax cement @ 4316' -
mudded hole to 450' - ran 25
sax cement - mudded to 20' -
and ran 10 sax cement - all
mudding and plugging done as
instructed by State Plugger,
Mr. H. W. Kerr

19 18 25W
19 15