

To: 1 051134
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 135-23,323-00-00

SE SE NE, SEC. 17, T 18 S, R 25 W&R
2970 feet from S section line
330 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 4868

Lease Name Buster Well # 1

Operator: Asher
Name:
Address 5660 South Syracuse Circle
Englewood, CO 80111

County Ness 146.25

Well Total Depth 4500 feet

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 226

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor H-30, Inc. License Number 5107

Address 251 North Water, Suite 10, Wichita, KS 67202

Company to plug at: Hour: 1 p.m. Day: 18 Month: 2 Year: 19 89

Plugging proposal received from Dick Davis

(company name) H-30, Inc. (phone) 316-263-2043

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2487' GL
Anhydrite 1761-92'

1st plug at 1800' with 50 sx cement, 2nd plug at 930' with 80 sx cement,

3rd plug at 260' with 50 sx cement,

4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Paul Luthi
(TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 4:45 p.m. Day: 18 Month: 2 Year: 19 89

ACTUAL PLUGGING REPORT 1st plug at 1800' with 50 sx cement,

2nd plug at 930' with 80 sx cement,

3rd plug at 260' with 50 sx cement,

4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

RECEIVED
STATE CORPORATION COMMISSION

FEB 21 1989

02-21-1989
CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Allied.

(If additional description is necessary, use BACK of this form.)

INVOICED
Observe this plugging.

DATE 2-22-89

INV. NO. 24011
2-18

Signed Richard W. Lacy
(TECHNICIAN)

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date... January 15, 1989

API Number 15-135-23,323-00-00

OPERATOR: License # 04868
Name Asher/Petro Energy
Address 5660 S. Syracuse Circle
City/State/Zip Englewood, CO 80111
Contact Person Harold Patton
Phone 303-770-4100

SE SE NE Sec. 17 Twp. 18 S. Rg. 25
2970 Ft. from South Line of Section
330 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5107
Name H-30, Inc.
City/State Wichita, KS

Nearest lease or unit boundary line 330 feet
County Ness

Well Drilled For: X Oil, Gas, OWWO
Well Class: Infield, Pool Ext., Wildcat
Type Equipment: X Mud Rotary, Air Rotary, Cable

Lease Name Buster Well # 1
Ground surface elevation feet MSL

If OWWO: old well info as follows:

Operator
Well Name
Comp Date Old Total Depth

Domestic well within 300 feet: yes X no
Municipal well within one mile: yes X no

I certify that well will comply with K.S.A. 55-101, et seq. plus eventually plugging hole to KCC specifications.

Date 1/6/89 Signature of Operator or Agent [Signature] Title Agent

Depth to bottom of fresh water 180
Depth to bottom of usable water 1000

Surface pipe by Alternate: 1 2 X
Surface pipe planned to be set 200'

Conductor pipe required
Projected Total Depth 4500 feet

Formation Mississippi

For KCC Use:

Conductor Pipe Required feet; Minimum Surface Pipe Required 200' feet per Alt. X (2)

This Authorization Expires 7-9-89 Approved By [Signature] 1-9-89

EFFECTIVE DATE: 1-14-89

Spud 2-10-89

225' of 8 5/8"

NO W.W.

SE SE NE Sec. 17 Twp. 18 S. Rg. 25 East X West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep. Base of Anhydrite or formation with 50 sks feet of... 60/40 Poz. 6% gel
2nd plug @ ft. deep. Base of Cheyenne or formation with 80 sks feet of... 60/40 Poz. 6% gel
3rd plug @ ft. deep 200' or formation with 40 sks feet of... 60/40 Poz. 6% gel
4th plug @ ft. deep 40' or formation with 10 sks feet of... 60/40 Poz. 6% gel
5th plug @ ft. deep or formation with feet of...
(2) Rathole to surface minus 5 feet 15 R.H. (b) Mousehole to surface minus 5 feet

PUSHER Dick Davis
TD 4500' FORMATION
SURFACE PIPE 8 5/8" @ 826
ANHYDRITE 1761 ELEVATION 2487.64
STARTING TIME & DATE 1 pm
COMPLETION TIME & DATE 4:45 pm 2-15-89
1st PLUG @ 1800 FT. WI 50 SX
2nd PLUG @ 930 FT. WI 80 SX
3rd PLUG @ 260 FT. WI 50 SX
4th PLUG @ 40-0 FT. WI 10 SX
RAT HOLE CIRCULATED WI 15 SX
MOUSE HOLE CIRCULATED WI SX
WATER WELL PLUGGED WI SX
CEMENT COMPANY Allied
TECHNICIAN P.A.L.
60/40 w/ 2 1/2" 2 1/2"

RECEIVED STATE CORPORATION COMMISSION
FEB 21 1989
02-21-1989
CONSERVATION DIVISION
Wichita, Kansas