

*Counted spot*

*SW, NW, SW*

CARD MUST BE TYPED

CARD MUST BE SIGNED

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date. April 7, 1988  
month day year

API Number 15- 199-20,150-0000  
Approximately

OPERATOR: License # 5171  
Name TXO Production Corp.  
Address 155 N. Market, Suite 1000  
City/State/Zip Wichita, Kansas 67202  
Contact Person Cory West  
Phone (316) 269-7655  
CONTRACTOR: License # 6033  
Name Murfin Drilling Company  
City/State Wichita, Kansas

SW NW SW Sec. 31 Twp. 14 S, Rg. 42  East  
 West  
1650' Ft. from South Line of Section  
460' Ft. from East Line of Section  
(Note: Locate well on Section Plat on reverse side)

Well Drilled For:  Oil  Storage  Infield  Mud Rotary  
 Gas  Inj  Pool Ext.  Air Rotary  
 OWWO  Expl  Wildcat  Cable

Nearest lease or unit boundary line 460' feet  
County Wallace  
Lease Name HIBBERT 'C' Well # 12  
Ground surface elevation TBD feet MSL  
Domestic well within 330 feet:  yes  no  
Municipal well within one mile:  yes  no  
Depth to bottom of fresh water 300'  
Depth to bottom of usable water 1800'

If OWWO: old well info as follows:  
Operator  
Well Name  
Comp Date Old Total Depth

RECEIVED  
STATE CORPORATION COMMISSION  
APR 6 1988

Surface pipe by Alternate: 1 2   
Surface pipe planned to be set ±680'  
Conductor pipe required none  
Projected Total Depth 5300' feet  
Formation Morrow Sand

I certify that well will comply with K.S.A. 55-101, et al. conservatively plugging hole to KCC specifications.  
Date 4-6-88 Signature of Operator or Agent Cory West Title Drig & Prod Engineer

For KCC Use:  
Conductor Pipe Required \_\_\_\_\_ feet; Minimum Surface Pipe Required 350 feet per Alt.  (2)  
This Authorization Expires 10-6-88 Approved By 4-6-88

EFFECTIVE DATE: 4-11-88  
Water Pipe From Trg. Pond.  
S.P. 680 - 8 7/8,  
9' Tand. Spud. PM, 4-9-88

Approx. SW NW SW Sec. 31 Twp. 14 S, Rg. 42  East  
 West

PLUGGING PROPOSAL IF ABOVE IS D & A

*Jul*

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep. <u>4500'</u>	or formation with <u>11</u> sxs	feet of. <u>60-40</u> poz
2nd plug @ ft. deep. <u>1950'</u>	or formation with <u>11</u> "	feet of. " "
3rd plug @ ft. deep. <u>700'</u>	or formation with <u>40</u> "	feet of. " "
4th plug @ ft. deep. <u>300'</u>	or formation with <u>25</u> "	feet of. " "
5th plug @ ft. deep. <u>40'</u>	or formation with <u>10</u> "	feet of. " "
(2) Rathole to surface minus 5 feet		(b) Mousehole to surface minus 5 feet

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging.  
In Addition: Call district office before well is either plugged or production casing is cemented in.  
(Call 7 a.m. to 5 p.m. workdays)

District office use only:  
API #15- 199-20,150-00-00  
Surface casing of \_\_\_\_\_ feet set with \_\_\_\_\_ sxs at \_\_\_\_\_ hours, 19 \_\_\_\_\_  
Alternate 1 \_\_\_\_\_ or 2 \_\_\_\_\_ surface pipe was used.  
Alternate 2 cementing was completed @ \_\_\_\_\_ ft. depth with \_\_\_\_\_ sxs on \_\_\_\_\_, 19 \_\_\_\_\_  
Hole plugged \_\_\_\_\_, 19 \_\_\_\_\_, agent \_\_\_\_\_

Received  
KCC District #6  
APR 7 1988  
4-7-88  
Hays, Kc