6-<u>090480</u>

105 R

TO:	API number: 15-109-20,530-000
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING	NE NE NW /4 SEC. 29 , 11 S, 33 W
200 COLORADO DERBY BUILDING	4840 feet from S section line
WICHITA, KANSAS 67202	3080 feet from E section line
WICHITA, KANDAD 07202	reet from E section fine
Operator license# <u>5393</u>	Lease D & L H. Enterprises Well # 2
	County Logan
Address: 150 N. Main, Suite 801 Wichita, Kansas 67202	Well total depth 4745 feet
(316) 262-1841	Surface pipe 8 5/8 Inch @ 307 feet
Aband. oil well, Gas well, Inp	ut well, SWD, D & A _X_
Plugging contractor: Abercrombie RTD, Inc. License#30684	
Address: Wichita, Kansas 67202	
Company to plug at: Hour: PM Day: 18 Month: March Year: 1992 Plugging proposal received from: Harold Maley	
Were: Spot plugs through drill pipe w/	heavy mud between all plugs. Rat hole: 15 sacks Mousehole: sacks CONSTRUCTION COMMISSION NOTICE TO SERVE TO
1st plug 0 <u>2630</u> feet with 25 sacks	Rat hole: 15 sacks
2nd plug @ <u>1630</u> feet " 100 "	Mousehole: sacks
3rd plug 0 <u>360</u> feet " 40 "	4PD MATION ED
4th plug @ 40 feet " wiper plug &	10 sks. humacher P.I.R.T. III APROPATION COMMISSION All[], Part[], None[X]
5th plug @ feet "	TILE NOW ONLY
Plugging Proposal Received by: <u>Ed Sc</u>	humacher P.I.R.T. III
Plugging operations attended by agent?	All[], Part[], None[X]
Completed: Hour: 7:00 PM, Day: 19, Mo	·
Actual plugging report: Hole reporte	d plugged as above.
Order 190 sx 60/40 pozmix w/ 6% gel an	d 2 sx celloflake or flowcel.
Remarks: Elevation: 3131 GL, Anhydr	ito donthe 2611 - 2624 foot
Anhy. plug: YES Dakota plug: YES	Bottom hole plug in place:
Plugged through drill pipe: YES	. ,
Did Not penetrate Arbuckle, cemented b	y Allied Cementing Company
I did[] / did not[X] observe the p	lugging. Ed Schumacher
DATE 4-24-92	Ed Schumacher
NV. NO. 3502/	(agent)
NV. NO.	Form CP-2/3