

2-28

4-061053

TO: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Number: 15-109-20,642-0000

SW NE NW /4 SEC. 11, 11 S, 33 W  
4290 feet from S section line  
3630 feet from E section line

Operator license# 5003

Lease Schippers A Well # 1-11

Operator: McCoy Petroleum Corporation

County: Logan 154.37

Address: 3017 N. Cypress Street  
Wichita, Kansas 67226-4003

Well total depth 4750 feet  
Conductor Pipe: 0 inch @ 0 feet  
Surface pipe 8 5/8 Inch @ 300 feet

Aband. oil well\_\_\_, Gas well\_\_\_, Input well\_\_\_, SWD\_\_\_, D & A X

Plugging contractor: Sweetman Drilling, Inc. License# 5658

Address: Wichita, Kansas 67202

Company to plug at: Hour: 8:00 P.M. Day: 28 Month: February Year: 1997

Plugging proposal received from: Brad Bortz

Company: Sweetman Drilling, Inc. Phone: \_\_\_\_\_

Were: Order 200 sxs 60/40 posmix - 6% gel with 1/4# floseal per sack.  
Space all plugs with heavy drilling mud through drill pipe.

RECEIVED  
KANSAS CORP COM  
1997 MAR 12 P 1:23

Plugging Proposal Received by: Herb Deines/Steve Durrant

Plugging operations attended by agent? All[ ], Part[ ], None[ X ]

Completed: Hour: 10:50 P.M., Day: 28, Month: February, Year: 1997

Actual plugging report: \_\_\_\_\_

- 1st. Plug at 2650' w/25 sxs. Anhydrite 2620' - 2649'.
- 2nd. Plug at 1740' w/100 sxs.
- 3rd. Plug at 330' w/40 sxs.
- 4th. Plug at 40' w/10 sxs.
- 15 sxs in rathole.
- 10 sxs in mousehole.

Remarks: Allied Cementing.

Condition of casing(in hole): GOOD X BAD \_\_\_\_\_ Anhy.plug: YES X NO \_\_\_\_\_  
Bottom plug(in place): YES \_\_\_\_\_, CALC \_\_\_\_\_, NO X Dakota plug: YES X, NO \_\_\_\_\_  
Plugged through TUBING \_\_\_\_\_, CASING \_\_\_\_\_. Elevation: \_\_\_\_\_ GL

I did [ ] / did not [ X ] observe the plugging.

[Signature]  
(agent)  
Form CP-2/3

**INVOICED**  
DATE MAR 12 1997  
47741  
**INV. NO.**

2-28