

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Well Number: 15-063-21208-00-00  
Spot: N2NWSWSW Sec/Twnshp/Rge: 27-15S-28W  
1220 feet from S Section Line, 4950 feet from E Section Line  
Lease Name: ROBERTS A Well #: 1  
County: GOVE Total Vertical Depth: 4349 feet

Operator License No.: 9067  
Op Name: DAMAR RESOURCES, INC.  
Address: 234 W 11TH STE A PO BOX 70  
HAYS, KS 67601

String	Size	Depth (ft)	Pulled (ft)	Comments
PROD	5.5	4378		155 SX
SURF	8.625	346		190 SX

Well Type: OIL UIC Docket No: \_\_\_\_\_ Date/Time to Plug: 08/10/2012 1:30 PM  
Plug Co. License No.: 99977 Plug Co. Name: QUALITY OIL WELL CEMENTING  
Proposal Rcvd. from: CURTIS R LONGPINE Company: \_\_\_\_\_ Phone: (785) 625-0020

Proposed Plugging Method: Ordered 375 sx 60/40 pozmix 4% gel cement w/500 # hulls.  
Port Collar @ 1953' w/250 sx cement.  
Perfs from 4009' to 4292'

Plugging Proposal Received By: CASE MORRIS Witness Type: COMPLETE (100%)  
Date/Time Plugging Completed: 08/14/2012 10:30 AM KCC Agent: MARVIN MILLS

Actual Plugging Report:

Tied on to casing, pumped 75 sx cement w/300 # hulls followed by 14 sx gel and 300 sx cement. Strong vacuum in casing. Shut down, dropped rock and found cement is 52 seconds from surface. Will have to come back next week to re-plug well.  
08/14/12-Moved rig in. Ran tubing and tagged cement at 1675'. Pumped 150 sx cement. Cement circulated.  
Pulled tubing out. Topped off w/25 sx cement. Staying full.  
Pressured backside to 300 psi.

Perfs:

Top	Bot	Thru	Comments
4009	4292		


RECEIVED  
AUG 27 2012  
KCC WICHITA

Remarks: QUALITY OILWELL/AVEN WEAVERLING

Plugged through: CSG

District: 04

Signed

  
8/31/12 (TECHNICIAN)

CM

AUG 15 2012