

1 051693

7-11

STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 165-21,635-0000
80'E & 50' S of
NW SE NW, SEC. 10, T. 16 S, R. 20
3580 feet from S section line
3550 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5815

Lease Name Moran Well # 1

Operator: C & R Drilling

County Rush 129.57

Name & Address 4901 E. Drycreek Rd., Ste. 270

Well Total Depth 3987 feet

Littleton, CO 80122

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 360

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SMD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor Allen Drilling Company License Number 5418

Address P.O. Box 1389, Great Bend, KS 67530

Company to plug at: Hour: 4 a.m. Day: 11 Month: 7 Year: 19 93

Plugging proposal received from Marvin Petz

(company name) Allen Drilling Co. (phone) 316-793-5681

Work: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1380-1425'
1st plug at 1420' with 50 sx cement, 2nd plug at 780' with 80 sx cement,
3rd plug at 390' with 40 sx cement, 4th plug at 40' with 10 sx cement,
5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Richard Lacey (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 6:15 a.m. Day: 11 Month: 7 Year: 19 93

ACTUAL PLUGGING REPORT 1st plug at 1420' with 50 sx cement,
2nd plug at 780' with 80 sx cement,
3rd plug at 390' with 40 sx cement,
4th plug at 40' with 10 sx cement,
5th plug to circulate rathole with 15 sx cement.

RECEIVED STATE CORPORATION COMMISSION

JUL 14 1993

Remarks: Used 60/40 Pozmix 6% gel 1/4# floseal by HOWCO.

CONSERVATION DIVISION WICHITA, KANSAS

(If additional description is necessary, use BACK of this form.)

INVOICED

(did not) observe this plugging.

DATE 7-28-93

Signed Richard M. Lacey (TECHNICIAN)

INV. NO. 38225

EFFECTIVE DATE: 7-5-93

DISTRICT # 1
35A7

State of Kansas
NOTICE OF INTENTION TO DRILL 165-21,635-0000

FORM MUST BE TYPED
ALL BLANKS MUST BE FILLED

Must be approved by the K.C.C. five (5) days prior to commencing well

Expected Spud Date July 6, 1993
month day year

Spot 80' E & 50' S of
NW SE NW Sec 10 Twp 16S. 3. Rg 20 East West

OPERATOR: License # 5815
Name: C & R DRILLING
Address: 4901 E. Drycreek Rd., Ste. 270
City/State/Zip: Littleton, CO 80122
Contact Person: Les Olson
Phone: 303/741-0621

3580 feet from South / North line of Section
3550 feet from East / West line of Section
IS SECTION Y REGULAR IRREGULAR?

(NOTE: Locate well on the Section Plat on Reverse Side)

County: Rush
Lease Name: MORAN Well #: 1
Field Name:

Is this a Prorated/Spaced Field? yes X no

Target Formation(s): LKC

Nearest lease or unit boundary: 910

Ground Surface Elevation: 2140 feet MSL

Water well within one-quarter mile: yes X no

Public water supply well within one mile: yes X no

Depth to bottom of fresh water: 200 530

Depth to bottom of usable water: 823 750

Surface Pipe by Alternate: 1 X 2

Length of Surface Pipe Planned to be set: (350) 200

Length of Conductor pipe required: N/A

Projected Total Depth: 4500

Formation at Total Depth: Reagan

Water Source for Drilling Operations:
... well X farm pond other

DWR Permit #:

Will Cores Be Taken? yes X no

If yes, proposed zone:

Well Drilled For: Well Class: Type Equipment:
X Oil Enh Rec Infield X Mud Rotary
 Gas Storage X Pool Ext. Air Rotary
 OUVG Disposal Wildcat Cable
 Seismic: # of Holes Other

If OUVG: old well information as follows:
Operator: N/A
Well Name:
Comp. Date: Old Total Depth

Directional, Deviated or Horizontal wellbore? yes X no

If yes, true vertical depth:

Bottom Hole Location:

Exp. 12/30/93

AFFIDAVIT

200' Alt. II Req.

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq.
It is agreed that the following minimum requirements will be met:

Pusher Marvin Kelly
SPUD DATE 7-5-93 INIT. GB
LENGTH SURFACE PLANNED 330
RESERVE PIT STATUS- REMOVE FLUID LINED
after salt sect. bbls. when done bbls.
RATHOLED AHEAD? Y N SIZE HOLE
SURFACE PIPE 8 3/4 @ 340 CONDUCTOR
ANHYDRITE T- 1380 B- 1425 ELEVATION
TD 3987 FORMATION arb - top of arb 3965
RAN PIPE @ SX DV TOOL @ SX ALT II DONE Y N
Arbuckle Plug @ 40 Ft. W/ 50 SX
Hug./Council @ Ft. W/ SX
Anhydrite Base @ 1420 Ft. W/ 50 SX
1/2 Base Anyh. @ 780 Ft. W/ 80 SX
1/2, 1/2 Plug @ Ft. W/ SX
Bottom Surface @ 390 Ft. W/ 40 SX
40' Plug @ 40 Ft. W/ 10 SX
RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ SX
WATER WELL SX (Irr. Well Pond)
Hauling
TECHNICIAN A.L. DATE 7-9-93
TYPE OF CEMENT 60/40 port 6 paged 1/4 Flowseal
STARTING TIME 4:00 (AM/PM) DATE 7-11-93
COMPLETION TIME 4:40 (AM/PM) DATE 7-11-93
CEMENT COMPANY Flowseal

RECEIVED
KANSAS CORPORATION COMMISSION

CONSERVATION DIVISION
Kans