

4- 060295

2-7

175
R

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15-109-20,528.0000

SE SE SW /4 SEC. 20, 12 S, 33 W
330 feet from S section line
2970 feet from E section line

Operator license# 5886

Lease Bertrand "A" well # 1-20

Operator: Chief Drilling, Inc.

County Logan

Address: 224 E. Douglas
Wichita, Kansas 67202

Well total depth 4770 feet ^{155.02}
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 300 feet

Aband. oil well , Gas well , Input well , SWD , D & A

Plugging contractor: Chief Drilling, Inc. License# 5886

Address: Wichita, Kansas 67202

Company to plug at: Hour: 6:30 P.M. Day: 7 Month: February Year: 92

Plugging proposal received from: Harold Dinkle

Company: Chief Drilling, Inc. Phone: 316-262-3791

Were: Order 200 sxs. 60/40 posmix - 6% gel. - 1/4# flocele per sx.
Space all plugs with heavy drilling mud through drill pipe.

Plugging Proposal Received by: Herb Deines
Plugging operations attended by agent? All[], Part[], None[]

Completed: Hour: 6:30 P.M., Day: 7, Month: February, Year: 1992

Actual plugging report:

1st. plug at 2650' with 25 sxs. - Anhydrite 2640' - 2663'
2nd. plug at 1610' with 100 sxs. - Dakota 1308' - 1608'.
3rd. plug at 350' with 40 sxs. - Surface pipe to 300'.
4th. plug at 40' with 10 sxs.
Rathole with 15 sxs.
Mousehole with 10 sxs.

RECEIVED
STATE CORPORATION COMMISSION
MAR - 3 1992
3-3-92
CONSERVATION DIVISION
Wichita, Kansas

Remarks: Allied Cementing.
Condition of casing(in hole): GOOD BAD Anhy. plug: YES NO
Bottom plug(in place): YES , CALC , NO Dakota plug: YES , NO
Plugged through TUBING , CASING . Elevation: 3158 GL

I did / did not observe the plugging.

DATE MAR 10 1992

INV. NO. 34706

(agent)
Form CP-2/3

Feb. S