

To: 1 051362  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

11-21  
API NUMBER 15-071-20,488-0000  
C SE NW, SEC. 22, T 20 S, R 40 W ~~EX~~  
3300 feet from S section line  
3300 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 9922  
Operator: Hughes Seewald  
Name &  
Address P.O. Box 1650  
Amarillo, TX 79105

Lease Name Wallace Well # 2  
County Greeley 94.90  
Well Total Depth 2920 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 302

Abandoned Oil Well \_\_\_\_\_ Gas Well  Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Allied Cementing License Number \_\_\_\_\_

Address \_\_\_\_\_

Company to plug at: Hour: 12 p.m. Day: 2 Month: 11 Year: 19 90

Plugging proposal received from Robert Higginbottom

(company name) Hughes Seewald (phone) 316-624-3767

were: 4 1/2" at 2916' w/875'sx cement, PBTB 2914', Perfs at 2808-26'

1st plug pump down 4 1/2" with 300 lbs. hulls and 120 sx cement.

Plugging Proposal Received by Steve Durrant  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 12:45 p. Day: 2 Month: 11 Year: 19 90

ACTUAL PLUGGING REPORT 1st plug pumped down 4 1/2" with 300 lbs. hulls and 120 sx cement.

Attempted to pump 8 5/8" X 4 1/2" annulus. Pressured it to 1000 psi.

4 1/2" maximum pressure 2000 psi and shut in 1000 psi.

Remarks: Used 60/40 Pozmix 6% gel by Allied. No casing recovery.  
(If additional description is necessary, use BACK of this form.)

**INVOICED** observe this plugging.

DATE 11-19-90

INV. NO. 29998

Signed Richard W. Lucy  
(TECHNICIAN)