

1 030403

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 007-22,012 RF00  
SW SW SE, SEC. 30, T 31 S, R 12 W/X  
330 feet from S section line  
2310 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5428  
Operator: Graves Drilling Co., Inc.  
Name & Address 910 Union Center  
Wichita, KS 67202

Lease Name Vera Well # 1 \  
County Barber 146.06  
Well Total Depth 4494 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 266 ✓

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Graves Drilling Co., Inc. License Number 5428  
Address 910 Union Center, Wichita, KS 67202

Company to plug at: Hour: 4:00 pm Day: 14 Month: April Year: 19 85

Plugging proposal received from Clyde Kuhn  
(company name) Graves (phone) 316-265-7233

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 840' with 50 sx cement

2nd plug at 300' with 50 sx cement  
solid bridge

3rd plug hulls - plug at 40' -- cement to surface with 10 sx cement

5th plug to circulate rat hole with 10 sx cement

Plugging Proposal Received by Steve Durrant  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 6:00 pm Day: 14 Month: April Year: 19 85

ACTUAL PLUGGING REPORT 1st plug at 840' with 50 sx cement, 2nd plug at 300' with 50  
sx cement, 3rd & 4th plugs - solid bridge - hulls - plug at 40' -- cement to surface  
with 10 sx cement, 5th plug to circulate rat hole with 10 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION

APR 23 1985

CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Used 60/40 Pozmix 2% gel 3% cc by Sun  
(If additional description is necessary, use BACK of this form.)

INVOICED  
DATE 5-2-85  
INV. NO. 7917

Signed Steve Durrant  
(TECHNICIAN)