

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-095-22112-00-00 *FOR IMAGING ONLY - CANNOT INV. AS PLUG DT.*
Spot: SENWSESE Sec/Twnshp/Rge: 24-29S-6W *EX LEERS*
825 feet from S Section Line, 825 feet from E Section Line
Lease Name: SCHLICKAU Well #: 1 *5 YR. CUTOFF.*
County: KINGMAN Total Vertical Depth: 4611 feet

Operator License No.: 33168
Op Name: WOOLSEY OPERATING COMPANY, LL
Address: 125 N MARKET STE 1000
WICHITA, KS 67202

String	Size	Depth (ft)	Pulled (ft)	Comments
SURF	10.375	242		225 SX

Well Type: DH UIC Docket No: _____ Date/Time to Plug: 08/27/2007 8:00 AM

Plug Co. License No.: 33610 Plug Co. Name: FOSSIL DRILLING, INC.

Proposal Rcvd. from: CARL DURR Company: WOOLSEY OPERATIONS Phone: _____

Proposed Plugging Method: 35 SX ARBUCKLE, 35 SX 390', 25 SX 60'. 15 SX RH.

Plugging Proposal Received By: _____

Witness Type: NONE

Date/Time Plugging Completed: 08/27/2007 4:00 PM

KCC Agent: STEVE VANGIESON

Actual Plugging Report:

Perfs: _____

A 35 SK CEMENT PLUG WAS SPOTTED AT TOP OF ARBUCKLE AT 4565' THROUGH THE DRILL PIPE. PULLED DRILL PIPE TO 390' AND SPOTTED 35 SX OF CEMENT. PULLED DRILL PIPE TO 60' & CIRCULATED 25 SX OF CEMENT. THE RAT HOLE WAS CIRCULATED WITH 15 SX OF CEMENT.

Remarks: ALLIED CEMENT. 60/40 4% GEL.

Plugged through: DP

District: 02

Signed _____

(TECHNICIAN)

RECEIVED
OCT 05 2012
KCC WICHITA