RECEIVED (Rev. 8/98)

KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TESTOCT 1 7 2012

Type Tes	it:				(See Instru	ctions on Rev	erse Side)		KCO		_	
Open Flow				Test Date: 15-077-10165						KCC WIGHITA			
De	eliverabilty	1		icsi bak	••	· ·	12.0	17-	10162-	00-01			
Company	У					Lease					Well Nu	mber	
Mul1	Drill	ing Compa	ny, Inc.			Robin	son				2		
County Location				Section		TWP		RNG (E/W)		, , , , , , , , , , , , , , , , , , , 	Acres Attributed		
Harper NE NE NW			IE NW	27				9W			40		
Field			Reservoir					hering Connec					
Spivey-Grabs-Basil				Mississippian				Spivey Gas Plant Packer Set at					
Completion Date			Plug Back Total Depth				Packer S	Set at					
2-1960 Cosino Sino			h.*	4500 Internal Diameter Set at				Porto	orations	То			
Casing Size Weight 4 1/2" 14#			5.012		4520		reno		. •	1.1.71	1160		
Tubing Size Weight		nt	Internal Diameter		Set at		Perfo	rations	To	, 4464, 4474, 4469 To			
2" 4.7#		1.995		4426				10					
Type Cor	npletion (Describe)			d Production	n		-Pump Ui	nit or Traveling	Plunger? Yes	/ 18to		
Single				0il & Water				4845					
Producing	g Thru (A	nnulus / Tubing)	% Carbo	n Dioxide			% Nitrog	en	Gas Gr	avity - G	i.	
Annul	us											-	
Vertical D	epth(H)				Press	sure Taps	•			(Meter	Run) (Pr	over) Size	
Pressure Well on L									•	at	_		
					OBSERVI	ED SURFACE	DATA			Duration of Shut-		Hour	
Static /	Orifice	Circle one: Meter or	Pressure Differential	Flowing	Well Head	Casing Wellbaad Prossure		Tubing Wellhead Pressure (P _w) or (P ₁) or (P _c) psig psia		Duration	Liquid Produced (Barrels)		
Dynamic Property	Size inches	Prover Pressu psig	in (h) Inches H ₂ 0	Temperature t	Temperature t					(Hours)			
Shut-in	ואבה	~	30/50	0-150		250	•			24	2	Ð	
Flow													
	·				ELOW STE	REAM ATTRI	BIITEE	<u> </u>			<u> </u>		
		Circle one:	Ţ	1	FLOW 511		BU123	i					
Plate Coeffiect (F _b) (F Mcfd	ient p) F	Meter or Prover Pressure psia	Press Extension √P _m x H _w	Grav Fact F _s	tor	Temperature I		ation ctor pv	Metered Flow R (Mcfd)	GOR (Cubic Fe Barrel)		Flowing Fluid Gravity G _m	
							1						
/D \?		/m \ \ 1				/ERABILITY)					² = 0.20		
(P _c)² =	 :	(r _w)*=	Choose formula 1 or 2;	P ₄ =			- 14.4) +	1	: ,	(P _d)	² =		
(P _e) ² - (F or (P _e) ² - (F	2,)²	(P _c) ² - (P _w) ²	1. P _c ² -P _c ² 2. P _c ² -P _c ² divided by: P _c ² -P _w ²	P ² -P ² LOG of formula P ² -P ² 1. or 2. and divide		Backpressure Curve Slope = "n" or Assigned Standard Slope		n x i	LOG	Antilog	Deli Equals	Open Flow Deliverability Equals R x Antilog Mcfd	
Open Flow Mcfd @ 14.65 psia					Deliverability				Mcfd @ 14.65 psia				
			is true and corre				day of			that he has know	rledge of	the facts	
						_							
		For Comm	nission						Check	red by			

in the second of
I declare under penalty or perjury under the laws of the state of Kansas that I am authorized to request
exempt status under Rule K.A.R. 82-3-304 on behalf of the operator <u>Mull Drilling Company</u> , <u>Inc.</u>
and that the foregoing information and statements contained on this application form are true and correct to
the best of my knowledge and belief based upon gas production records and records of equipment installa-
tion and/or of type completion or upon use of the gas well herein named.
I hereby request a permanent exemption from open flow testing for the <u>Robinson #2</u>
gas well on the grounds that said well:
(Check one)
is a coalbed methane producer is cycled on plunger lift due to water
is a source of natural gas for injection into an oil reservoir undergoing ER
is a source of natural gas for injection into an oil reservoil didengoing En
is incapable of producing at a daily rate in excess of 150 mcf/D
Date: $9-19-12$
Signature: Man Serphell Title: Zim/Jose Prod Foreman
Title: Junitors Prod Foreman

Instructions:

All active gas wells must have at least an original G-2 form on file with the conservation division. If a gas well meets the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to obtain a testing exemption.

At some point during the succeeding calendar year, wellhead shut-in pressure shall be measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under "observed surface data." Shut-in pressure shall thereafter be reported yearly in the same manner.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than thirty (30) days after the taking of the pressure reading. The form must be signed and dated on the front side as though it was a verified report of test results.