Kansas Corporation Commission One Point Stabilized Open Flow or Deliverability Test

KCC WICHITATorm G-2 (Rev. 7/03)

| Type Test: | | | | | (Se | e Instru | ctions (| on Rev <mark>e</mark> rse | Side) | | | | | |
|---|-----------------------------|---|---|-----------------------------|--|---|---------------------|--|---------------------------------|---|-------------------------------|---------------|---------------------------|---|
| <u></u> | en Flow verability | | | Test Date | e: | 0 | 9/25/2 | 2012 | | | API No. | | 151892238 | 380000 |
| Company OXY USA | Inc | | | | | Lea: | se HREN | IS A 1 | | | | | We | II Number |
| County Stevens | 230 | Location 1 FNL & 2 | | | Section 7 | | TW | /P 1S | | | 3 (E/W) 5 W | | Acr | res Attributed 640 |
| ield VALKEN | IEYER S | E | | | Reservoir Morrow | | | | | | Gathering P Midstre | | n | |
| ompletion 8/08/200 | | | | | Plug Back 6,261' | Total De | pth | | | Pac | ker Set at | | | |
| asing Size | e | Weigh 15.5 # | | | Internal Di 4.950' | | | Set at , 728 ' | | | Perforation: 6,148' | 8 | To 6,15 6 | 6' |
| ubing Size | e | Weigh 4.7# | t | | Internal Di 1.995" | ameter | | Set at 6,160' | | | Perforation | S | То | |
| Type Completion (Describe) SINGLE-GAS | | | | Type Fluid Production WATER | | | | Pump Unit or Traveling Plunger? Yes / No Yes - Beam Pump | | | Yes / No | | | |
| oducing ' | Thru (Ann Annulus | ulus / Tubin | 3) | | % | Carbon [0.243 ° | |) | | | litrogen 3.717% | | Gas Gravit 0.65 | |
| ertical De 6,15 2 | | | | | | | ssure T lange | • | | | | | | n) (Prover) Size . 068'' |
| ressure B | Buildup: | Shut in | 09/2 | 4 | 20 12 | at <u>9:0</u> | 00 | | Taken | | 09/25 | 20 12 | et 9: | 00 |
| ell on Lin | ne: | Shut in | | | 20 | at | | | Taken | | | 20 | at | |
| | | | | | | OBSEI | RVED: | SURFACE | DATA | | | Ouration of | Shut-in | 24 Hours |
| Static / Dynamic | Orifice Size | Meter Differe Prover Pressure in | | | ntial Flowing Well He Temperature Tempera | | | ture (P_w) or (P_t) or (P_c) | | (P _w) or (P _t) or (P _c) | | Duration | Liquid Produced | |
| Property Shut-In | (inches) | psig (F | m) | Inches H | l ₂ 0 | | <u>t</u> | psig 18.0 | 95ia 32. | \rightarrow | psig 0.0 | psia 14.4 | (Hours) | (Barrels) |
| Flow | | <u> </u> | | | | | | - | | - | | | | |
| . 1011 | <u> </u> | | | | | FLOW | STRE | AM ATTRIE | BUTES | | | | ı | |
| Plate | | Circle one: | Dr | ess | | | Flowing | | | Т | | | | Flowing |
| Coefficient (F _b) (F _p) Mcfd | t | Meter or Wer Pressure psia | Exte | nsion x h | Gravity Factor F _e | | emperatur Factor | re Devi | iation ctor _{pv} | | Metered Flow R (Mcfd) | (Cubic | GOR : Feet/Barrel) | Fluid Gravity G _m |
| | | | | | (OPEN FL | .OW) (DI | ELIVE | RABILITY) | CALC | ULA | TIONS | | (P _a | $()^2 = 0.207$ |
| c) ² = | : | (P _w) ² = | 0.0 | <u> </u> | P _d = | | % | (P _c - 14 | 4.4) + 1 | 4.4 = | <u> </u> | <u> </u> | (P _d |)2 = 0 |
| $(P_c)^2 - (P_a)^2$ or $(P_c)^2 - (P_d)^2$ $(P_c)^2 - (P_w)^2$ | | ² - (P _w) ² | Choose Formula 1 or 2: 1. $P_c^2 - P_a^2$ 2. $P_c^2 - P_d^2$ divided by: $P_c^2 - P_w^2$ | | LOG of formula 1. or 2. and divide by: | formula 1. or 2. and divide $P_c^2 - P_w^2$ | | Backpressure Curve Slope = "n"or Assigned Standard Slope | | nxLOG | | | Antilog | Open Flow Deliverability Equals R x Antilog (Mcfd) |
| | | | | | Jy. | <u> </u> | | Ottalidate Off | орс | | | | | |
| | | | | | | | | | | | | | | |
| en Flow | | 0 | Mcf | d @ 14.6 | 5 psia | | Deli | iverability | | | | Mcfd @ |) 14.65 psia | |
| e facts state | d therein, and | The undersign | | | | any, states t ecuted this | | | d to make | e the al | bove report and | that he has k | nowledge of | 2012 |
| | | \Asi | ness | | | | | | | | (| OXY USA | | \rightarrow |
| | | | | | | | | | | | David (| | ky USA Ind | |
| ···· | | For Co | mmission | | | | | | | | David | <u> </u> | ., | |

Form G-2 (Rev. 7/03)

KCC WICHITA

| | | | KCC MICHIA |
|-------------------------------------|--|--|---|
| K.A.R. 82 contained and lease | on this application form are true and correct to the records of equipment installation and/or upon ty thereby request a one-year exemption from oper | usa inc. and that the fore the best of my knowledge and belief be the of completion or upon use being n | egoing pressure information and statements based upon available production summaries |
| (Check o | one) | | |
| | is a coalbed methane producer | | |
| | is cycled on plunger lift due to water | | |
| | is a source of natural gas for injection into an o | I reservoir undergoing ER | |
| | is on a vacuum at the present time; KCC appro | val Docket No. | |
| 7 | is not capable of producing at a daily rate in ex | cess of 250 mcf/D | |
| | 0.444.404.0040 | ` | |
| ate: _ | October 24, 2012 | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | Sigr | David Ogden OXY USA-Inc |
| | | | Title: Gas Business Coordinator |

Instructions: If a gas well meets one of the eligibility criteria set out in the KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under **OBSERVED SURFACE DATA**. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption **IS** denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31st of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.