- 1070083
TO: API NUMBER 15-135-24,060 $-$ COCO STATE CORPORATION COMMISSION $9-30$ NE NE SW SEC. 27 , T 20 S, R 23
CONSERVATION DIVISION - PLUGGING SECTION 2310 FEET FROM SOUTH SECTION LINE
WICHITA STATE OFFICE BLDG., 130 S. MARKET 2310 FEET FROM WEST SECTION LINE
WICHITA, KANSAS 67202 LEASE NAME BYROM WELL # 1
TECHNICIAN'S PLUGGING REPORT COUNTY NESS 145.47
OPERATOR LICENSE # 5228 WELL TOTAL DEPTH 4476 FEET
OPERATOR: PARRISH CORPORATION PRODUCTION CSG: SIZE " FEET
NAME AND 110 SOUTH MAIN #510 SURFACE CASING: SIZE 8% " FEET 655'
ADDRESS <u>WICHITA, KS 67212-3240</u>
ABANDONED OIL WELLGAS WELLINPUT WELLSWD WELLD/A _X
OTHER WELL AS HEREINAFTER INDICATED
PLUGGING CONTRACTOR L.D. DRILLING LICENSE NUMBER 6039
ADDRESS RR1 BOX 183-B, GREAT BEND, KS 67530
COMPANY TO PLUG AT: HOUR: 9:00 PM DAY: 20 MONTH: 09 YEAR: 1998
PLUGGING PROPOSAL RECEIVED FROM DORAN
(COMPANY NAME) L.D. DRILLING (PHONE) 316-793-3051
WERE:
1ST PLUG AT 1460' WITH 50 SX CEMENT, 2ND PLUG AT 685' WITH 50 SX CEMENT,
3RD PLUG AT 300' WITH 40 SX CEMENT, 4TH PLUG AT 0-40' WITH 10 SX CEMENT,
5TH PLUG TO CIRCULATE RATHOLE WITH 15 SX CEMENT.
PLUGGING PROPOSAL RECEIVED BY SCOTT ALBERG
PLUGGING OPERATIONS ATTENDED BY AGENT?: ALLPARTNONEX
OPERATIONS COMPLETED: HOUR: 11:15 PM DAY: 20 MONTH: 09 YEAR: 1998
ACTUAL PLUGGING REPORT LOAD HOLE WITH HEAVY MUD SPOT PLUGS THRU DRILL PIPE
1ST PLUG AT 1460' WITH 50 SX CEMENT, 2ND PLUG AT 685' WITH 50 SX CEMENT,
3RD PLUG AT 300' WITH 40 SX CEMENT, 4TH PLUG AT 0-40' WITH 10 SX CEMENT, 5TH PLUG TO CIPCULATE PATHOLE WITH 15 SY CEMENT
5TH PLUG TO CIRCULATE RATHOLE WITH 15 SX CEMENT.
N :
REMARKS: USED 60/40 POZMIX 6% GEL BY ALLIED. (IF ADDITIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM.)
I DID NOT OBSERVE THIS PLUGGING.

10-14-98 60123